

MOBIL OIL CORP -- DTE 25 -- 9150-00-993-6621

===== Product Identification =====

Product ID:DTE 25

MSDS Date:12/27/1993

FSC:9150

NIIN:00-993-6621

MSDS Number: BVBHW

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-662-4245

Emergency Phone Num:800-424-9300 CHEMTREC(609-737-4411)

CAGE:3U728

=== Contract

or Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWES ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

Company Name:R.E.DISTRIBUTING COMPANY

CAGE:0Y1K9

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: 95%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 P

PM

Ingred Name:MINERAL OIL

CAS:64742-65-0

RTECS #:PY8038500

Fraction by Wt: 2000 MG/KG

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE: NON-TOXIC AND PRACTICALLY
NON-IRRITATING TO SKIN & EYES ACCORDING TO TESTS. HARMFUL
CONCENTRATIONS OF MISTS/VAPORS ARE UNLIKELY TO BE ENCOUNTERED
THROUGH ANY CUSTOMARY OR REASONABLY FORESEEABLE HANDLING, USE OR
MISUSE OF THIS PRODUCT. CHRONIC: MFR
STUDIES HAVE SHOWN NO
TOXIC/CARCINOGENIC EFFECTS ON LAB ANIMALS.

Explanation of Carcinogenicity:CONTAINS CONVENTIONALLY REFINED MINERAL
OIL IARC LISTS AS A CARCINOGEN.

Effects of Overexposure:NONE LISTED.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. IF
IRRITATION OCCURS, SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER. HIGH
PRESSURE

ACCIDENTAL INJECTION INTO SKIN REQUIRES IMMEDIATE MEDICAL
ATTENTION. INGESTED: GIVE 1-2 GLASSES OF WATER TO VICTIM, IF
CONSCIOUS. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.
INHALATION: REMOVE TO FRESH AIR.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>395F,>202C

Lower Limits:0.6%

Upper Limits:7.0%

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG.
CAUTION-FOAM & WATER MAY CAUSE FROTHING.

Fire Fig

hting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE GEAR. PREVENT RUNOFF FROM FIREFIGHTING OR DILUTION
FROM ENTERING SEWERS OR WATERWAYS.

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB IN INERT MATERIAL AND PLACE IN A
CONTAINER FOR LATER DISPOSAL. REPORT SPILLS INTO WATERWAYS TO US
COAST GUARD AT 800-424-8802.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP CONTAINERS CLOSED. STORE IN A COOL, DRY, WELL VENTILATED AREA.
Other Precautions:DO NOT USE MATERIAL FOR AIR COMPRESSORS WHICH PROVIDE MAKE-UP AIR FOR HUMAN USE; SUCH AS FOR DIVING, SCBA, OR SIMILAR USES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE NORMALLY REQUIRED.
Ventilation:USE ADEQUATE MECHANICAL VENTILATION.
Protective Gloves:NONE NORMALLY REQUIRED.
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE NORMALLY REQUIRED.
Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.
Supplemental Safety and Health
MSDS PROVIDED BY CAGE 0Y1K9 FOR CONTRACT SPO-451-94-MR823.

=====
Physical/Chemical Properties
=====

HCC:V6
Boiling Pt:B.P. Text:>600F,>316C
Melt/Freeze Pt:M.P/F.P T
ext:-11F,-24C
Vapor Pres: