

EASTMAN KODAK COMPANY -- 826 6801;FLEXICOLOR AR DEVELOPER REPLENISHER;PT A;KAN449534 -- 6750-01-285-1766

=====
===== Product Identification =====

Product ID:826 6801;FLEXICOLOR AR DEVELOPER REPLENISHER;PT A;KAN449534

MSDS Date:08/03/1994

FSC:6750

NIIN:01-285-1766

MSDS Number: BVBMX

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Cou

ntry:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====
===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 55-60%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM CARBON

ATE
CAS:584-08-7
RTECS #:TS7750000
Fraction by Wt: 25-30%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SULFITE
CAS:10117-38-1
RTECS #:WT3530000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PENIETIC ACID, PENTA SODIUM SALT
CAS:140-01-2
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM BICARBONATE
CAS:298-14-6
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

R
outes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY
CAUSE IRRITATION.INGEST:EXPECTED TO BE ALOW HAZARD.MAY CAUSE GI
TRACT IRRITATION.INHAL:EXPECTED TO BE A LOW HAZARD.MAY CAUSE
RESPIRATORY IRRITATION.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:EYES/SKIN:IRRITATION.
Medical Cond Aggravated by Exposure:UNLIKELY TO AGGRIVATE EXISTING
MEDICAL CONDITIONS.

=====
===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND
WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH
AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT
INDUCE VOMITING. GET PROMPT QUALIFIED MEDICAL ATTENTION.IF
CONSCIOUS,GIVE 1-2 GLASSES OF WATER.

=====

= Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:MANUFACTURER STATES NONE.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIEL IN AN APPROPRIATE CONTAINER FOR

DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.FOR SMALL SPILLS,PH BETWEEN 3-12,FLUSH TO SEWER WITH PLENTY OF WATER.

Neutralizing Agent:DEPENDS ON PH;LOW PH USE LIME,SODIUM BICARBONATE/HIGH PH USE VINEGAR(ACETIC ACID

===== Handling and Storage =====

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION.KEEP CONTAINERS CLOSED.

Other Precautions:FOLLOW LABEL DIRECTIONS.AVOID BREATHING VAPORS.AVOID SKIN AND EYE CONTACT.

=====

== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.

Ventilation:USE GENERAL DILUTION VENTILATION.MFR RECOMMENDS 10 AIR CHANGES/HOUR.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDRY WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:B1

Boiling Pt:>100.C, 212.F

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.403

pH:10.9

Solubility in Water:COMPLETE

Appearance and Odor:LIQUID;COLORLESS;ODORLESS

Percent Volatiles by Volume:50-60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avo

id:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.PRETREATMENT MAY BE REQUIRED BEFORE RELEASE INTO SEWER IF PH IS OUTSIDE OF THE RANGE,3-12.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.