View NSN Online: https://aerobasegroup.ae/nsn/1620-00-315-4256

Product ID:RING TIE DOWN,161968 MSDS Date:07/01/1993 FSC:1620 NIIN:00-315-4256 MSDS Number: BVFLB === Responsible Party === Company Name: ALLIEDSIGNAL INC., AIRCRAFT LANDING SYSTEM Address:3520 WESTMOOR STREET **City:SOUTH BEND** State:IN ZIP:46628 Country:US Info Phone Num:219-231-2302 Emergency Phone Num:219-231-2000 CAGE:0B7T5 === Contractor Identification === **Company Name: HONEYWELL INTL INC** Address:101 COLUMBIA RD Box:City:MORRISTOWN State:NJ ZIP:07960 Country:US Phone:201-455-2000/800-707-4555 CAGE:0B7T5 Company Name: HONEYWELL INTL INC, AIRCRAFT LANDING SYSTEM ALS Address:3520 WESTMOOR STREET Box:City:SOUTH BEND State:IN ZIP:46628-1373 Country:US Phone:219-231-2201 CAGE:55284

Ingred Name:CADMIUM

(AS CD);(SARA III) CAS:7440-43-9 RTECS #:EU9800000 Fraction by Wt: TRACE Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 MG/M3 DUST; Z-2 ACGIH TLV:0.01 MG/M3 DUST;9394 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT RELEVENT. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, LU NG, KIDNEY,

PROSTATE. PRODUCT IS NOT HAZARDOUS. HEALTH HAZARDS ARE DUE TO DUSTS/FUMES CREATED DURING MACHINING. ACUTE- EYE:MAY CAUSE PAIN. SKIN/INHALE:MAY CAUSE IRRITATION. ORAL:MAY CAUSE HEADACHE, VOMITING, SORETHROAT. CHRONIC- MAY CAUSE KIDNEY DAMAGE, LUNG AND PROSTATE CANCER.

Explanation of Carcinogenicity:CONTAINS C [7440-43-9] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN. Effects of Overexposure:EYES, SKIN, RESPIRATORY AND DIGESTIVE TRACTS

IRRITATION; SHORTNESS OF BREATH; CHEST PAIN; FLU-LIKE SYMPTOMS SUCH AS WEAKNESS, HEADACHE, CHILLS AND MUSCULAR PAIN; NAUSEA, VOMITING, DIARRHEA, SORE THROA T, REDNESS AND PAIN OF EYES

First Aid:GET MEDICAL ATTENTION IMMEDIATELY. EYE:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP/MILD DETERGENT & LARGE AMOUNT OF WATER. INHALED:REMOVE TO FRESH A IR. PROVIDE CPR/OXYGEN IF NEEDED.

ORAL:TREATMENT MUST BE ADMINISTERED BY MEDICAL PERSONNEL. ADVICE TO PHYSICIAN:DO NOT PERFORM CHELATION THERAPY.

Flash Point:NONE

Extinguishing Media:DRY SAND, DRY DOLOMITE, DRY GRAPHITE OR SODIUM CHLORIDE

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

U

nusual Fire/Explosion Hazard:CADMIUM DUST CREATED DURING MACHINING MAY PRESENT A MODERATE EXPLOSION HAZARD WHEN EXPOSED TO FLAME. DUST AND STRONG OXIDIZERS MAY CAUSE FIRE OR EXPLOSION.

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS. VACUUM OR SWEEP UP SPILLAGE. AVOID CREATING DUST. PLACE SPILLAGE IN APPROPRIATE CONTAINER FOR WASTE DISPOSAL. VENTILATE AREA. SPILLS AND RELEASES MAY HAVE TO BE REPORTED TO FEDERAL AND/OR LOCAL AUTHORITIES. Neutralizing Agent:NOT RELEVENT

Handling and Storage Precautions: SHIPPING & STORAGE MUST FOLLOW INSTRUCTIONS AS SPECIFIED IN 29 CFR 1910.1027 BEARING WARNING LABLE: DANGER, CONTAINS CADMIUM. CAUSES LUNG+KIDNEY DAMAGE
Other Precautions: CANCER HAZARD. AVOID CREATING DUST. AVOID CONTAT TO EYES, SKIN AND CLOTHING. AVOID INHALATION OF DUST. WASH THOROUGHLY AFTER HANDLING MATERIAL. K
EEP OUT OF REACH OF SMALL CHILDREN. OBEY

HAZARD WARNING LABEL. USE WITH ADEQUATE VENTILATION.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: IF TLV