

FARWEST PAINT MFG CO -- 800 EXTERIOR WOOD TONES, SAND YELLOW 33617 --
8010-01-294-7135

===== Product Identification =====

Product ID:800 EXTERIOR WOOD TONES, SAND YELLOW 33617

MSDS Date:08/01/1992

FSC:8010

NIIN:01-294-7135

MSDS Number: BVGRL

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emerg

ency Phone Num:206-941-1619

Preparer's Name:NORMA HABEEB

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM SOLVENT

CAS:64742-47-8

Fraction by Wt: 13.72%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:100 PPM

Ingred Name:MINERAL SPIRITS 350

CAS:8032

-32-4
RTECS #:OI6180000
Fraction by Wt: 9.07%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:XYLENE (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 0.78%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PHENYLETHANE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 0.17%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ALKYLBENZENES
CAS:68515-25-3
Fraction by Wt: 0.24%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:40 PPM
ACGIH TLV:40 PPM

Ingred Name:VOC: 372 GRAMS/LITER (LESS WATER)
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: THIS MATERIAL MAY CAUSE
IRRITATION

, SENSITIZATION OR DEFATTING OF SKIN UPON PROLONGED OR REPEATED CONTACT. INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS CAN RESULT IN HEADACHE, DIZZINE SS, NAUSEA & UNCONSCIOUSNESS. PROLONGED/REPEATED OVEREXPOS: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. EYES: EYE IRRITANT

Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS.

=====
===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH W/SOAP & WATER. REMOVE & WASH ANY CONTAMINATED CLOTHING BEFORE REUSE. EYE: FLUSH W/LRG QTY WATER 15 MIN & GET MEDICAL ATTENTION. INGESTION: DON'T INDUCE VOMITING. KEEP WARM, QUIET, GET MEDICAL ATTENTION. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS (CAN BE FATAL). INHALATION: REMOVE TO FRESH AIR IMMED. IF RESPIRATORY SYMPTOMS DEVELOP GET MED AID IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:103F,39C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM,DRY CHEM,WATER FOG,CO2,CLASS B EXTNGSHING AGENT.WATER MAY BE UNSUITABLE AS EXTINGSH AGENT,USE TO COOL NEARBY CNTNRS

Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS. EVACUATE AREA OF UNPROTECTED PERSONNEL. WEAR PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE IN AIR & BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. VENT AREA. ABSORB SPILL W/ABSORBENT (VERMIC,SAWDUST,SAND,ETC), PLACE INTO CLOSED CONTAINERS. IF LARGE SPILL, DIKE AREA TO PREVENT MAT'L FROM ENTERING WATER SYSTEMS OR SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEAN-UP.

=====
===== Handling and Storage =====

Handling and Storage Precaut

ions:AVOID PROLONGED OR REPEATED INHALATION OF HEATED VAPORS OR SPRAY MISTS. KEEP AWAY FROM HEAT OR OPEN FLAME. THIS MATERIAL MAY CAUSE SENSITIZATION.
Other Precautions:DO NOT GET IN EYES, ON SKIN, OR CLOTHING. DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN. DO NOT WELD ON FULL OR EMPTY CONTAINERS. KEEP CONTAINERS CLOSED WHEN NOT IN USE AND PROPERLY LABELED. KEEP OUT OF REACH OF CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory P

rotection:A CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPORS OR SPRAY MISTS WHEN THE TLV OR PEL IS EXCEEDED.

Ventilation:GENERAL VENTILATION IS REQUIRED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS.

Protective Gloves:NITRILE, NEOPRENE OR RUBBER GLOVES REQ'D

Eye Protection:WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:282 TO 420F

Vapor Pres:6.0 @ 20C

Vapor Density:> AIR

Viscosity:82 TO 85 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NIL

Appearance and Odor:WHITE OR COLOR OF TINT, MILD ODOR.

Percent Volatiles by Volume:33.0

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES AND EPOXY HARDENER UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAMES. IF PRODUCT CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS WILL GENERATE HYDROGEN GAS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

=====
===== Disposal Considerations =====

Waste Disposal

Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, & FEDERAL AGENCIES. GROUND HANDLING EQUIPMENT TO PREVENT SPARKS. FOR FURTHER INFORMATION: CONTACT YOUR STATE OR LOCAL WASTE AGENCY OR US EPA RCRA HOTLINE (800- 424-9346 OR 202-382-3000).

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.