

CHEM-TREND INC -- BRITEMOR 555 -- 6850-01-268-6703

=====  
===== Product Identification =====

Product ID:BRITEMOR 555

MSDS Date:02/23/1994

FSC:6850

NIIN:01-268-6703

MSDS Number: BVHKG

=== Responsible Party ===

Company Name:CHEM-TREND INC

Address:1445 W MCPHERSON PARK DR

City:HOWELL

State:MI

ZIP:48844-0860

Country:US

Info Phone Num:517-546-4520

Emergency Phone Num:517-546-4520

Preparer's Name:JLG

CAGE:2W7

38

=== Contractor Identification ===

Company Name:CHEM-TREND INC

Address:1445 W. MCPHERSON PARK DR

Box:860

City:HOWELL

State:MI

ZIP:48844-0860

Country:US

Phone:800-727-7730

CAGE:2W738

Company Name:DUNN R G ASSOCIATES INC

Address:15104 LEE RD SUITE 203-B

Box:City:HUMBLE

State:TX

ZIP:77396-2078

Country:US

Phone:281-441-2001/FAX: 281-441-7772

CAGE:0A272

=====  
===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON,

CAS:64742-47-8

RTECS #:OA5504000

Fraction

by Wt: 40-50%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:HEAVY AROMATIC NAPHTHA (SOLVENT NAPHTHA) THE 40-50% LISTED  
FOR INGRED 1 ALSO INCLUDES % FOR INGRED 2.  
CAS:64742-94-5  
RTECS #:WF3100000  
Other REC Limits:NONE RECOMMENDED

Ingred Name:MINERAL OIL  
CAS:64742-53-6  
RTECS #:PY8036000  
Fraction by Wt: 25-40%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:NAPHTHALENE (SARA III)  
CAS:91-20-3  
RTECS #:QJ0525000  
Fraction by Wt: 49C  
Extinguishing Media:USE FOAM, CARBON DIOXIDE, DRY CHEMICAL.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WHEN  
FIRE FIGHTING IN A CONFINED SPACE.  
Unusual Fire/Explosion Hazard:'EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR  
VAPOR, DO NOT CUT,WELD,ETC. ON THEM. COOL CONTAINERS EXPOSED TO  
INTENSE HEAT WITH WATER TO PREVENT CONTAINER RUPTURE.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL:SOAK UP W/ABSORBENT MATERIAL. ELIMINATE  
SOURCES OF IGNITION. VAPORS ARE HEAVIER THAN AIR & MAY SPREAD  
DISTANCESOR COLLECT IN LOW AREAS. DIKE AREA TO PREVENT RUNOFF,  
RECOVER LIQUID, SOAK UP REMA I NING LIQUID WITH ABSORBENT MATERIAL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:.  
Other Precautions:.

===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:USE RESPIRATOR WHEN ENGINEERING CONTROLS FAIL OR NEED TO BE SUPPLEMENTED. WHEN NEEDED USE ONLY MSHA/NIOSH APPROVED AIR- SUPPLIED RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR.

Ventilation:USE MECHANICAL (GENERAL) AND LOCAL VENTILATION AS NEEDED TO REDUCE ENVIRONMENTAL CONCENTRATIONS TO PERMISSIBLE LEVEL.

Protective Gloves:IMPERVIOUS (NEOPRENE, PVA, NBR, NITRILE)

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:APPROPRIATE CLOTHING TO AVOID SKIN CONTACT.

Work Hygienic Practices:MFR: ? HMIS:USE STRICT CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY EXPOSURE. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health  
NONE

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:459F,237C

Vapor Pres:1 MM

Vapor Density:>1

Spec Gravity:0.91

Evaporation Rate & Reference: