View NSN Online: https://aerobasegroup.ae/nsn/6525-01-063-9559

Product ID:139 7231 KODAK INDUSTREX FIXER AND REPLENISHER 75 LITRES MSDS Date:05/12/1993 FSC:6525 NIIN:01-063-9559 Kit Part:Y **MSDS Number: BVTML** === Responsible Party === Company Name: EASTMAN KODAK CO Address:343 STATE ST **City:ROCHESTER** State:NY ZIP:14650-1115 Country :US Info Phone Num:716-724-6481/716-722-5151 Emergency Phone Num:716-722-5151/716-724-4501 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 80-85%

Ingred Name: AMMONIUM THIOSULFATE CAS: 778

3-18-8 RTECS #:XN6465000 Fraction by Wt: 10-15%

Ingred Name:SODIUM SULFATE ANHYDROUS, SODIUM SULFATE CAS:7757-82-6 RTECS #:WE1650000 Fraction by Wt: 1-5%

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: EXPECTED TO BE A LOW
HAZARD FOR RECOMMENDED HANDLING. EYES: MAY CAUSE TRANSIENT
IRRITATION. SKIN: LOW HAZARD FO
R RECOMMENDED HANDLING. INGESTION:
EXPECTED TO BE A LOW HAZARD.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: EXPECTED TO BE A LOW HAZARD FOR
RECOMMENDED HANDLING. EYES: MAY CAUSE TRANSIENT IRRITATION. SKIN:
LOW HAZARD FOR RECOMMENDED HANDLING. INGESTION: EXPECTED TO BE A LOW HAZARD FOR

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. EYES: FLUSH IMMEDIATELY W/WATER. SKIN: WA

SH W/SOAP & WATER. INGESTION: DRINK

1-2 GLASSES OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point:NONE

Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: FLUSH TO SEWER W/LARGE AMOUNT

S OF WATER. MAY REQUIRE NEUTRALIZATION IF PH 12. ABSORB W/VERMICULITE/OTHER INERT MATERIAL & PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REMOV E RESIDUAL CONTAMINATION.

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED. USE
 W/ADEQUATE VENTILATION.
 Other Precautions: KEEP FROM CONTACT W/OXIDIZING MATERIALS. PREVENT EYE
 CONTACT, MINIMIZE SKIN CONTACT/INHALATION.

=======

==== Exposure Controls/Personal Protection ============

Respiratory Protection:NONE SHOULD BE NEEDED Ventilation:GOOD GENERAL W/10 AIR CHANGES PER HOUR. Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES W/SIDE SHIELDS, GOGGLES Other Protective Equipment:EYE BATH, WASHING FACILITIES, SAFETY SHOWER. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health

Boiling Pt:B.P. Text:>212F Vap or Pres:18 Vapor Density:0.6 Spec Gravity:1.106 pH:4 Solubility in Water:COMPLETE Appearance and Odor:LIGHT YELLOW LIQUID W/SLIGHT VINEGAR ODOR Percent Volatiles by Volume:85/WT

Stability Indicator/Materials to Avoid:YES BASES, SODIUM HYPOCHLORITE, BLEACH, OXIDIZING MATERIALS. Hazardous Decomposition Products:SULFUR DIOXIDE, AMMONIA, CHLORAMINE

Waste Disposa

I Methods:FLUSH TO SEWER W/LARGE AMOUNTS OF WATER IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.