View NSN Online: https://aerobasegroup.ae/nsn/1560-00-620-4227

## CASEWAY INDUSTRIAL PRODUCTS INC -- PS 30, PART B -- 1560-00-620-4227

Product ID:PS 30, PART B MSDS Date:02/23/1994

FSC:1560

NIIN:00-620-4227

Kit Part:Y

MSDS Number: BVZGR === Responsible Party ===

Company Name: CASEWAY INDUSTRIAL PRODUCTS INC

Address:6624 PROSPECT STREET

Box:249

City:CASEVILLE

State:MI ZIP:48725 Country:US

Info Phone Num:517-856-2215

Emergency Pho ne Num:517-856-2215

CAGE:0VHD7

=== Contractor Identification ===

Company Name: CASEWAY INDUSTRIAL PRODUCTS INC

Address:6624 PROSPECT ST

Box:249

City:CASEVILLE

State:MI ZIP:48725 Country:US

Phone:517-856-2215

CAGE:0VHD7

Company Name: ROTODYNE INC

CAGE:81996

======= Composition/Information on Ingredients ========

Ingred Name: DIBUTYL PHTHALATE (SARA III)

CAS:84-74-2

RTECS #:TI0875000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9394

EPA Rpt Qty:10 LBS

**DOT Rpt** 

Qty:10 LBS

Ingred Name:BENZOYL PEROXIDE (SARA III) CAS:94-36-0 RTECS #:DM8575000 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9394

============ Hazards Identification =========================

LD50 LC50 Mixture: NOT GIVEN FOR PRODUCT AS A WHOLE

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:LOW INHALATION HAZARD FOR INDUSTRIAL

HANDLING, ANY MATERIAL THAT CONTACTS TH

E EYE MAY BE IRRITATING OR

MAY CAUSE MECHANICAL INJURY. SKIN CONTACT HAZARD LOW FOR INDUSTRIAL HANDLING.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES: FLUSH WITH WATER

FOR 15 MINUTES WHILE HOLDING EYELIDS

OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN HALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION.

Flash Point Method:COC Flash Point:374F,190C Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN

Extinguishing Media: WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE, FOAM

Fir

FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard: DO NOT USE DIRECT STREAM OF WATER ON FIRE. TOXIC GASES ARE RELEASED DURING COMBUSTION. ======== Accidental Release Measures ============ Spill Release Procedures: WEAR APPROPRIATE PROTECTIVE CLOTHING. SMALL SPILLS MAY BE COLLECTED WITH ABSORBENT MATERI ALS. COLLECT AND CONTAIN FOR DISPOSAL. LARGE SPILLS: FLUSH AREA WITH WATER SPRAY. PREVENT RUNOFF FROM ENTERING DRAINS, SEWERW OR STREAMS. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. ============= Handling and Storage ========================== Handling and Storage Precautions: KEEP FROM CONTACT WITH OXIDIZING MATERIALS. IT IS ADVISABLE TO USE WITH 6 MONTHS. Other Precautions: NONE SPECIFIED BY MANUFACTURER. ===== Exposure Controls/Personal Protection ====== Respiratory Protection: ORGANIC MIST FILTER. Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION TO MAINTAIN EXPOSURE LEVELS. Protective Gloves: VINYL OR RUBBER Eye Protection: SAFETY GLASSES OR GOGGLES Other Protective Equipment: PROTECTIVE CLOTHING AS REQUIRED TO AVOID SKIN CONTACT. AN EMERGENCY EYE WASH STATION AND SHOWER SHOULD BE AVAILABLE. Work Hygienic Practices: WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING. Supplementa I Safety and Health RQ = 10 POUNDS. ======== Physical/Chemical Properties =========== HCC:V1 Boiling Pt:B.P. Text:644F,340C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:NOT GIVEN Vapor Density: NOT GIVEN Spec Gravity:1.042 Evaporation Rate & Reference: < 1 (BUTYL ACETATE = 1) Solubility in Water: INSOLUBLE Appearance and Odor:OIL, COLORLESS LIQUID, CHARACTERISTIC ESTER ODOR ======== Stability and Reactivity Data =========== Stability Indicator/Materia

e Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &

Is to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, OPEN FLAME
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
UNIDENTIFIED ORGANIC COMPOUNDS.

======= Disposal Considerations ===========

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this i nformation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.