

Product ID:77X0200, RED PLASTISOL MSDS Date:11/03/1992 FSC:5970 NIIN:01-163-6786 MSDS Number: BVZJY === Responsible Party === Company Name:STANCHEM INC Address:401 BERLIN ST City:EAST BERLIN State:CT ZIP:06023-9706 Country:US Info Phone Num:203-828-0571 Emergency Phone Num:203-828-0571 CAGE:78520 === Contra ctor Identification === **Company Name:STANCHEM INC** Address:401 BERLIN ST Box:City:EAST BERLIN State:CT ZIP:06023-9706 Country:US Phone:203-828-0571 CAGE:78520

Ingred Name:DIBASIC LEAD PHTHALATE CAS:6838-85-3 Fraction by Wt: 0.5% Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYVINYL CHLORIDE RESIN CAS:9002-86-2 Fraction by Wt: 53% Other REC Limits:NONE RECOMMENDED

=======

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER. Explanation of Carcinogenicity:NOT CARCINOGENIC. Effects of Overexposure:INHALATION: NONE. SKIN: IRRITATION: IRRITATION, DERMATITIS. EYES: PRIMARY IRRITATION. Medical Cond Aggravated by Exposure:SINUS AND DERMATITIS.

First Aid:SKIN-WASH THOR OUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. EYES-IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN. INGESTION-DILUTE WITH CLEAR FLUID THEN IMMEDIATELY CALL A PHYSICIAN OR POISON CONTROL CENTER.

Flash Point:475F,246C

Extinguishing Media:FOAM, "ALCOHOL" FOAM, CARBON DIXIDE, DRY CHEMICAL, WATER, FOG.

Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARA TUS AND

PROTECTIVE CLOTHING. PRODUCT FUSES AT 350F.

Unusual Fire/Explosion Hazard: FIGHT AS VOLITILE LIQUID FIRE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL TO REDUCE PRESSURE.

Spill Release Procedures: AVOID ALL SOURCES OF IGNITION. STOP SPILL AT SOURCE; DIKE AREA TO PREVENT SPREADING. SPILLED MATERIAL SHOULD BE PLACED IN CONTAINERS AND BAKE FOR SOLIDIFICATION.

Handling and Storage Precautions: AVOID EXPOSING PRODUCT TO HEAT ABOVE 150F. STORE BELOW 90F.

Other Precautions: ADEQUATE OVEN VENTILATION AVOID BREATHING FUMES WHILE BAKING.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE REQUIRED WHILE HANDLING THE MATERIAL, BUT CAUTION WHEN BAKING.

Ventilation:LOCAL EXHAUST AS REQUIRED BY JOB CONDITIONS TO KEEP TLV

BELOW ACCEPTABLE LIMITS. REFER TO OSHA 29 CFR 1910.94 Protective Gloves:WEAR IMPERVIOUS GLOVES Eye Protection:USE SAFETY EYEWEAR WITH SPLASH GUARDS. Other Protective Equipment:NONE Work Hygienic Practices:EYE WASH AND SHOWER SHOULD BE AVAILABLE. USE UNDER WELL VENTILATED CONDITIONS. WASH THOROUGHLY AFTER WASHING. Supplemental Safety and Health ALWAYS WASH-UP BEFORE EATING, SMOKING OR USING THE TOILET FACILITIES. DO NOT BREATH VAPOR, DO NOT CONTACT EYES, SKIN AND CLOTHING.

HCC:N1 Boiling Pt:B.P. Text:450-550F Vapor Density:>AIR Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:1%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:NONE Hazardous Decomposition Products:COMBUSTION MAY PRODUCE HYDROGEN CHLORIDE, CARBON DIOXIDE AND/OR CARBON MONOXIDE.

========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this d ocument should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.