

WALTER KIDDE -- NITROGEN -- 4210-01-242-3765

=====
Product Identification
=====

Product ID:NITROGEN
MSDS Date:05/20/1986
FSC:4210
NIIN:01-242-3765
MSDS Number: BVZKN
=== Responsible Party ===
Company Name:WALTER KIDDE
Address:2500 AIRPORT DR
City:WILSON
State:NC
ZIP:27893
Country:US
Info Phone Num:307-744-5487
Emergency Phone Num:919-237-7004
CAGE:NO283
=== Contractor Identification ===
Company Name:WALTER KIDD AEROSPACE INC
Address:2500 AIRPORT DR
Box:City:WILSON
State:NC
ZIP:27893-9604
Country:US
Phone:919-237-7004
CAGE:5V736
Company Name:WALTER KIDDE
Address:2500 AIRPORT DR
Box:City:WILSON
State:NC
ZIP:27893
Country:US
Phone:307-744-5487
CAGE:NO283

=====
Composition/Information on Ingredients
=====

Ingred Name:NITROGEN
CAS:7727-37-9
RTECS #:QW9700000
Fraction by Wt: 100%
OSHA PEL:N/K
ACGIH TLV:ASPHYXIAN

=====
Hazards Identification
=====

=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION OF MODERATE CONCENTRATIONS MAY CAUSE HEADACHE, DROWSINESS, DIZZINESS, EXCITATION, EXCESS SALIVATION, VOMITING & UNCONSCIOUSNESS. LIQUID CONTACT MAY CAUSE FROSTBITE. CHRONIC: NOT APPLICABLE.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARD

S.

Medical Cond Aggravated by Exposure:THE TOXICOLOGY, PHYSICAL & CHEMICAL PROPERTIES OF THE MATERIAL DO NOT SUGGEST THAT OVEREXPOSURE IS LIKELY TO AGGRAVATE EXISTING MEDICAL CONDITIONS.

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR & CALL MD. INGEST: CALL MD IMMED . THIS PROD IS GAS AT AMBIENT TEMP & PRESS. INHAL: REMOVE TO FRESH AIR. GIVE ARTF RESP IF NOT BRTHG. GIVE OXYGEN IF BRTHG IS DFCLT. EYES: IN CASE OF SPLASH CON

TAM, FLUSH EYES W/WATER FOR AT LEAST 15 MIN.

SKIN: FOR EXPOS TO LIQ, WARM FROSTBITE AREA W/WATER (NOT TO EXCEED 105F). IN CASE OF MASSIVE EXPOS, REMOVE CLTHG & SHOWER W/WARM (SUPDAT)

===== Fire Fighting Measures =====

Extinguishing Media:NITROGEN CANNOT CATCH FIRE. USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:USE NIOSH/MSHA APPRVD SCBA FULL PROT EQUIP .

EVACUATE PERS FROM DANGER AREA. DELUGE CNTNR W/WATER SPRAY FROM MAX

DIST UNTIL COOL, THEN MOVE (SUPDAT)

Unusual Fire/Explosion Hazard:GAS CANNOT CATCH FIRE. CNTNR MAY RUPTURE DUE TO HEAT OF FIRE. NO PART OF CNTNR SHOULD BE SUBJECTED TO TEMP > 52C(125F). MOST CNTNRS WILL VENT CONTENTS (SUPDAT)

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE PERSONNEL FROM DANGER AREA. USE NIOSH/MSHA APPROVED SCBA WHERE NEEDED (IN OXYGEN DEFICIENT ATMOSPHERES). VENTILATE AREA WHERE LEAK OCCURRED. TEST

AREA FOR

SUFFICIENT OXYGEN PRIOR TO PERMITTING RE-ENTRY OF PERSONNEL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE & USE W/ADEQ VENT. MIXING TWO OR MORE GASES/LIQUIDIFIED GASES MAY COMBINE TO CREATE UNEXPECTED HAZS. OBTAIN SAFETY INFO FOR EACH BEFORE MIXING.

Other Precautions:NEVER WORK ON A PRESSURIZED SYSTEM. IF THERE IS A LEAK, CLOSE THE CYLINDER VALVE, BLOW DOWN THE SYSTEM BY VENTING TO A SAFE PLACE, THEN REPAIR THE LEAK.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:PER OSHA 29 CFR 1910.134 - RESPIRATOR ACCEPTABLE TO NIOSH/MSHA.

Ventilation:LOCAL EXHAUST PREFERRED. MECHANICAL (GENERAL) ACCEPTABLE.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPROVED SAFETY GLASSES .

Other Protective Equipment:METATORSAL SHOES FOR CYLINDER HANDLING IN ACCORDANCE WITH OSHA 29 CFR 1910.132 AND 1910.

133.

Work Hygienic Practices:GOOD HYGIENE PRACTICE AS WITH ANY INDUSTRIAL CHEMICAL.

Supplemental Safety and Health

FIRE FIGHT PROC: CNTNRS AWAY FROM FIRE AREA IF W/OUT RISK. EXPLO HAZ: WHEN EXPOSED TO ELEVATED TEMPS. FIRST AID PROC: WATER. NOTE TO MD: THERE IS NO SPECIFIC ANTIDOTE. TREATMENT SHOULD BE DIRECTED AT CONTROL OF SYMP & CLINICAL CNDTNS.

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:-319F,-195C

Melt/Freeze Pt:M.P/F.P Text:-346F,-210C

Vapor Pres:GAS @ 20C

Vapor Density:0.967

Spec Gravity:1.2506 (H*2O=1)

Solubility in Water:SLIGHTLY SOLUBLE

Appearance and Odor:COLORLESS, ODORLESS GAS AT AMBIENT TEMPERATURE & PRESSURE.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

UNDER CERTAIN CONDITIONS NITROGEN CAN REACT VIOLENTLY WITH LITHIUM, NEODYMIUM, TITANIUM OR OZONE.

Stability Condition to Avoid:CAUTION. HIGH PRESSURE GAS.

Hazardous Decomposition Pro

ducts:NONE.

===== Disposal Considerations =====

Waste Disposal Methods:SLOWLY RELEASE INTO ATMOSPHERE. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINERS OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.