View NSN Online: https://aerobasegroup.ae/nsn/8010-01-381-0243

Product ID:TT-E-2784 MSDS Date:10/01/1994 FSC:8010 NIIN:01-381-0243 MSDS Number: BVZSC === Responsible Party === Company Name: DEL PAINT MFG Address:3105 EAST RENO City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Info Phone Num:405-672-1431 Emergency Phone Num:800-424-9300 CHEMTREC Preparer's Name: ONEY FLEMING CAGE:39 934 === Contractor Identification === Company Name: DEL PAINT MFG Address:3105 EAST RENO Box:City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Phone:405-672-1431 CAGE:39934 Ingred Name: EKTASOLVE EEH SOLVENT CAS:1559-35-9 RTECS #:KK9625000 Fraction by Wt: 3.32% Other REC Limits:NONE RECOMMENDED Ingred Name: BENZYL ALCOHOL CAS:100-51-6 RTECS #:DN3150000 Fraction by Wt: 3.32% Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYL

AMINOETHANOL LOW VOE CAS:108-01-0 RTECS #:KK6125000 Fraction by Wt: 0.38% Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS Fraction by Wt: 92.98% Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC: 1.8 LB/GL; 211 G/LTR RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and C hronic:CAN CAUSE IRRITATION OF RESPIRATORY PASSAGES.

Effects of Overexposure:INHALATION OF VAPOR OR MIST CAN CAUSE HEADACHES, NAUSEA, IRRITATION OF NOSE, THROAT, AND LUNGS. EYE CONTACT CAN CAUSE SLIGHT IRRITATION. PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE SLIGHT IRRITATION.

Medical Cond Aggravated by Exposure:PRE-EXISTING LUNG DISEASE MAY BE AGGRAVATED BY EXPOSURE.

First Aid:EYE CONTACT: FLUSH WITH LARG E AMOUNTS OF WATER FOR 15 MINUTES, CONSULT PHYSICIAN IF IRRITATION PERSISTS. SKIN CONTACT: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. INGESTION: IF SWALLOWED, GIVE 2 GLASSES OF WATER TO DRINK, CONSULT PHYSICIAN.

Flash Point Method:SCC Flash Point:>212F,>100C Autoignition Temp:Autoignition Temp Text:216 F Lower Limits:NONE Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG Fire Fighting P

rocedures:WEAR SELF CONTAINED BREATHING APPARATUS (PRESSURE DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR.
Unusual Fire/Explosion Hazard:MATERIAL CAN SPLATTER ABOVE 100C. POLYMER FILM CAN BURN.
======================================
Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY, USE CARE TO AVOID FALLING. CONTAIN SPILLS WITH INERT MATERIALS (SAND, EARTH). TRANSFER LIQUIDS AND SOLID DIKING MATERIAL TO
SEPARATE SUITABLE CONTAINERS FO R RECOVERY/DISPOSAL. Neutralizing Agent:NONE
======================================
Handling and Storage Precautions: KEEP FROM FREEZING. Other Precautions: DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATION. Ventilation:NORMAL, SUCH AS A FAN Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES OR GOGGLES Other Protective Equipment:EYE WASH STATION. Supplemental Safety and Health
======================================
Boiling Pt:B.P. Text:212 TO 644F Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C Decomp Temp:Decomp Text:351F,177C Vapor Pres:NONE Vapor Density:> AIR Spec Gravity:1.01 (WATER=1) pH:9 MAX Viscosity:77-95 KU Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:SLIG

HT Appearance and Odor:GRAY LIQUID WITH SLIGHT ODOR Percent Volatiles by Volume:60.6

Stability Indicator/Materials to Avoid:YES THERE ARE NO KNOWN MATERIALS WHICH ARE INCOMPATIBLE WITH THIS PRODUCT. Stability Condition to Avoid:NONE Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD ACRYLIC MONOMERS.

Waste Disposal Methods:KEEP SPILLS AND C LEANING RUN OFF OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER. CONSULT FEDERAL, STATE, OR LOCAL AUTHORITIES FOR PROPER DISPOSAL PROCEDURES CONCERNING HEALTH AND ENVIRONMENT

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.