

BTR VALVE SEALANTS INC -- BTR 950 SEALANT (BULK GRADE) -- 9150-00-257-5360

=====
Product Identification
=====

Product ID:BTR 950 SEALANT (BULK GRADE)

MSDS Date:06/01/1994

FSC:9150

NIIN:00-257-5360

MSDS Number: BWCBP

=== Responsible Party ===

Company Name:BTR VALVE SEALANTS INC

Address:430 N LEXINGTON AVE

City:PITTSBURGH

State:PA

ZIP:15208

Country:US

Info Phone Num:412-244-5251

Emergency Phone Num

:412-247-3235

CAGE:80318

=== Contractor Identification ===

Company Name:AMERICAN SAFETY TECHNOLOGIES (BOUGHT R.H.CARLSON)

Address:565 EAGLE ROCK AVENUE

Box:City:ROSELAND

State:NJ

ZIP:07068

Country:US

Phone:201-403-2600

CAGE:TO015

Company Name:BTR VALVE SEALANTS INC

Address:140 THOMAS RD

Box:City:SULPHUR SPRINGS

State:TX

ZIP:75482

Country:US

Phone:903-439-6465

CAGE:80318

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYESTER RESIN (MFR STATES CAS# IS PROPRIET

ARY)
Fraction by Wt: 85-90%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ORGANOPHILIC CLAY
CAS:71011-24-0
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:15 MG/M3 (SILICA)

Ingred Name:INHIBITORS
Fraction by Wt: 400F,>204C
Extinguishing Media:CARBON DIOXIDE, CHEMICAL FOAM OR DRY CHEMICAL
POWDER.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. TREAT AS
BURNING OIL.
Unusual Fire/Explosio
n Hazard:NONE KNOWN.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE MATERIAL. ADD SUITABLE ABSORBENT
TO SPILL AREA. CLEAN SPILL AREA WITH DETERGENT SOLUTION.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN SEALED CONTAINERS TO AVOID
CONTAMINATION WITH FOREIGN PARTICLES.
Other Precautions:MINIMIZE SKIN CONTACT. WASH
WITH SOAP & WATER BEFORE
EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDER
CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF
CONTAMINATED LEATHER ARTICLES (SHOES) THAT CAN NOT BE
DECONTAMINATED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.
Ventilation:ADEQUATE VENTILATION IN ACCORDANCE WITH GOOD ENGINEERING
PRACTICE IS SUFFICIENT.
Protective Gloves:NEOPRENE RUBBER AS REQUIRED.
Eye Prot

ection:SAFETY GLASSES RECOMMENDED.

Other Protective Equipment:NONE NORMALLY REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

MSDS PRESENTED BY CAGE 80318 FOR CONTRACT NUMBER SP0451-95-MA163.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:NIL

Spec Gravity:1.10

Evaporation Rate & Reference:NIL (ETHER = 1)

Solubility

in Water:NEGLIGIBLE

Appearance and Odor:TAN GREASE-LIKE MATERIAL. SLIGHT FATTY ODOR

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZERS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION MAY PRODUCE CARBON MONOXIDE, CARBON DIOXIDE AND ASPHYXIANTS.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN A FURNACE OR OTHERWISE DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person u

tilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.