

WILLIAM F. NYE, INC. -- NYE RHEOLUBE 723F6 -- 9150-01-116-8168

=====
Product Identification
=====

Product ID:NYE RHEOLUBE 723F6

MSDS Date:11/04/1994

FSC:9150

NIIN:01-116-8168

MSDS Number: BWCGJ

=== Responsible Party ===

Company Name:WILLIAM F. NYE, INC.

Address:12 HOWLAND ROAD

City:FAIRHAVEN

State:MA

ZIP:02719

Country:US

Info Phone Num:508-996-6721

Preparer's Name:GBM

CAGE:DO759

=== Contractor Id

entification ===

Company Name:NYE LUBRICANTS INC

Address:12 HOWLAND RD

Box:City:FAIR HAVEN

State:MA

ZIP:02719

Country:US

Phone:508-996-6721

CAGE:98354

Company Name:WILLIAM F. NYE, INC.

Address:12 HOWLAND ROAD

City:FAIRHAVEN

State:MA

ZIP:02719

Phone:704-628-1711

CAGE:DO759

=====
Composition/Information on Ingredients
=====

Ingred Name:TEFLON (TETRAFLUORO ETHYLENE POLYMER)

CAS:116-14-3

RTECS #:KX4025000

Fraction by Wt: 6.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 TD

UST
ACGIH TLV:10 MG/M3 TDUST

Ingred Name:BARIUM DINONYLNAPHTALNE SULFONATE
CAS:25619-56-1
RTECS #:QM4450000
Fraction by Wt: 1.1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG/M3 (AS BA)
ACGIH TLV:0.5 MG/M3 (AS BA)

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-POSSIBLE SKIN AND EYE
IRRITATION. POLYMER FUME EFEVR AND F
LU-LIKE SYMPTOMS AT
TEMPERATURES ABOVE 250C DUE TO PTFE DECOMPOSITION. CHRONIC-NONE.
Explanation of Carcinogenicity:THIS PRODUCT IS NOT CONSIDERED A HUMAN
CARCINOGEN BY ANY RECOGNIZED SOURCE.
Effects of Overexposure:THERE IS NO EXPERIENCE WITH OVEREXPOSURE.
Medical Cond Aggravated by Exposure:NONE.

=====
===== First Aid Measures =====

First Aid:EYE: WASH THOROUGHLY, CONTACT PHYSICIAN IF IRRITATION
PERSISTS. SKIN: WASH WITH SOAP AND WATER. INHALE: MOVE
TO FRESH AIR
AND REFER TO A PHYSICIAN FOR TREATMENT.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:435F,224C
Extinguishing Media:CO2, FOAM, DRY CHEMICAL, WATER SPRAY.
Fire Fighting Procedures:AVOID SMOKE INHALATION. WATER OR FOAM MAY
CAUSE FROTHING.
Unusual Fire/Explosion Hazard:NONE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WIPE OR SCRAPE UP SPILLAGE AND PLACE IT IN A
C

s to Avoid: YES

STRONG OXIDIZING MATERIALS.

Stability Condition to Avoid: PYROLYSIS.

Hazardous Decomposition Products: CARBONYL FLUORIDE, HYDROFLUORIC ACID GAS, PERFLUOROCARBON OLEFINS, CARBON MONOXIDE, & SMALL AMOUNTS OF OTHER TOXIC FUMES

Conditions to Avoid Polymerization: AVOID CONTAMINATION OF CIGARETTES OR OTHER TOBACCO PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods: MANY STATES CLASSIFY WASTE LUBRICANTS AS HAZARDOUS, WHICH MEANS DISPOSAL ONLY BY A LICENSED FIRM. CONSULT LOCAL, STATE, AND FED REGULATIONS APPLICABLE IN YOUR AREA.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.