View NSN Online: https://aerobasegroup.ae/nsn/6850-01-316-9383

Product ID:D-70 DEVELOPER MSDS Date:03/15/1989 FSC:6850 NIIN:01-316-9383 Kit Part:Y MSDS Number: BWCJH === Responsible Party === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID STREET **City:SANTA MONICA** State:CA ZIP:90404 Country:US Info Phone Num:310-450-1111 Emergency Phone Num:310-450-1111/800-424-930 0(CHEMTREC) CAGE:98733 === Contractor Identification === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 **City:SANTA MONICA** State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 CAGE:98733

Ingred Name:ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 Other REC Limits:NONE RECOMMENDED OSHA PEL:400 PPM ACGIH TLV:400 PPM/500STEL;9394

==========

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHAL: MAY CAUSE MILD IRRITATION. SKIN:MILDY IRRITATING. INGEST:LOW ORDER OF TOXICITY. IRRITATION OF EYES, SKIN, OR NOSE & RESP TRACT. EARLY TO MODERATE CNS DEPRESSION MAY BE EVIDENCED BY GIDDINESS, HE ADACHE, DIZZINESS, NAUSEA. Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NTP/IARC:NOT AVAILABLE. OSHA:NO. Effects of Ov erexposure: IRRITATION OF EYES, SKIN OR NOSE & RESP TRACT. EARLY TO MODERATE CNS DEPRESSION MAY BE EVIDENCED BY GIDDINESS. HEADACHE, DIZZINESS, NAUSEA. Medical Cond Aggravated by Exposure: PRE-EXITING SKIN, EYE, AND RESPIRATAORY DISORDERS MAY BE AGGRAVATED. First Aid:FLUSH EYES OR SKIN WITH WATER. REMOVE VICTIM TO FRESH AIR. GET MED ATTN. Fla sh Point Method:TCC Flash Point:53.0F,11.7C Lower Limits:2 **Upper Limits:2** Extinguishing Media: USE WATER FOG, "ALCOHOL" FOAM, DRY CHEMICAL OR CO2. WARNING:FLAMMABLE. Fire Fighting Procedures: CLEAR FIRE AREA OF UNPROTECTED PERSONNEL. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR. Unusual Fire/Explosion Hazard: CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVETN VAPOR PRESSURE BUILDUP WHICH COULD RESULT IN CONTAINER RUPTURE. ============== Spill Release Procedures: WARNING. FLAMMABLE. ELIMINATE ALL IGNITION

Spill Release Procedures:WARNING.FLAMMABLE.ELIMINATE ALL IGNITION SOURCES.HANDLING EQPMT MUST BNE GROUNDED TO PREVETN SPARKING.WEAR APPROPRIATE RESP & PROT CLOTHING.SOAK UP RESIDUE W/ABSORBENT CLAY/SAND/OR OTHER MATERIAL.PLAC E IN NON-LEAKING CONTAINERS,SEAL. Neutralizing Agent:NONE SPECIFIED BY MFG.

| Handling and Storage Precautions:KEEP | AWAY FROM HEAT/SPARKS/ |
|---------------------------------------|------------------------|
|---------------------------------------|------------------------|

FLAME. WASH WITH SOAP & WATER BEFORE EATING/DRINKING/SMOKING/USING TOILET FACILITIES. Other Precautions: DO NOT STORE OR HANDLE IN ALUMINUM EQPMT AT TEMPERATURE ABOVE 120F. Respiratory Protection: IF EXPOSURE EXCEEDS LIMITS USE NIOSH-APPROVED RESPIRATOR. Ventilation: LOCAL EXHAUST & MECHANICAL (GENERAL) EXPLOSION PROOF TO MAINTAIN TLV. Protective Gloves: CHEMICAL RESISTANT. Eye Protection: GOGGLES IF CONTACT IS LIKELIHOOD. Other Protective Equipment: AS REQUIRED TO MINIMIZE CONTACT. EYE WASH FOUNTAINS & SAFETY SHOWERS SHOULD BE AVAILABLE. Work Hygienic Practices: MINIMIZE CONTACT. Supplemental Safety and Health KIT CONSISTS OF 3 PARTS, PART A (E-59 REMOVER), PART B (D-70 DEVELOPER), PART C (VP-301 HF VISIBLE PENETRANT) SAME NSN. HCC FOR PART B:F3. HCC:F2 Boiling Pt:B.P. Text:180F,82C Melt/Freeze Pt:M.P/F.P Text:-127F,-88C Vapor Pres:33 @68F Vapor Density:2.1 Spec Gravity:0.8 Evaporation Rate & amp; Reference:1.4, (N-BUTYL ACETATE=1) Solubility in Water:LIQUID PART IS SOLUB

Appearance and Odor:WHITE, MILKYT SUSPENSION, MILD ODOR.

Stability Indicator/Materials to Avoid:YES DO NOT STORE OR HANDLE IN ALUMINUM EQPMT AT TEMP >120F. Stability Condition to Avoid:AVOID HEAT, SPARKS, FLAME & CONTACT WITH STRONG OXIDIZING AGENTS. Hazardous Decompositio

n Products:CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED.

Waste Disposal Methods:PLACE IN NON-LEAKING CONTAINERS, SEAL AND DIPSOE AS IGNITABLE HAZ WASTE ACCORDING TO LATEST EPA OR STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner w hatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.