

FARWEST PAINT MFG CO -- PURPLE QUICK DRY ENAMEL COLOR #17100 -- 8010-01-040-3761

=====  
Product Identification  
=====

Product ID: PURPLE QUICK DRY ENAMEL COLOR #17100

MSDS Date: 06/22/1993

FSC: 8010

NIIN: 01-040-3761

MSDS Number: BWFBL

=== Responsible Party ===

Company Name: FARWEST PAINT MFG CO

Address: 4522 S 133 ST

Box: 68726

City: TUKWILA

State: WA

ZIP: 98168-3251

Country: US

Info Phone Num: 206-244-8844

Em

ergency Phone Num: 206-941-1619

CAGE: 6F266

=== Contractor Identification ===

Company Name: FARWEST PAINT MANUFACTURING CO

Address: 4522 SOUTH 133RD ST

Box: City: TUKWILA

State: WA

ZIP: 98168

Country: US

Phone: 206-244-8844

CAGE: 6F266

=====  
Composition/Information on Ingredients  
=====

Ingred Name: (STODDARD SOLVENT) ALIPHATIC HYDROCARBON

CAS: 8052-41-3

RTECS #: WJ8925000

Fraction by Wt: 51%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 500 PPM

ACGIH TLV: 100 PPM; 9394

Ingred Name: VOLITILE OR

ORGANIC CONTENT (PER MSDS:GRAMS/LITER LESS WATER)

RTECS #:9999999VC

Fraction by Wt: 470%

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN:IRRIT, SENSITIZATION, DEFATTING

UPON PROLONGED/REPEATED CONTACT. INHAL:EXCESSIVE VAP/SPRAY MIST

EXPOSURE CAN RESULT IN HEADACHE, DIZZ, NAU, LOSS OF CONS

CIUSNESS.

SOME REPORTS ASSOC REPEATED/PROL ONGED OCCUPATIONAL OVEREXPO TO  
SOLVENTSW/PERM BRAIN & NERVOUS SYS DAMAGE. EYES:IRRIT.

Explanation of Carcinogenicity:PER MSDS:THIS PROD CONTAINS NO KNOWN

CARCINOGENS IN REPORTABLE QUANTITIES AS DEFINED BY NTP, IARC, OSHA,  
EPA.

Effects of Overexposure:SKIN/EYES:IRRITATION. SKIN SENSITIZATION,

DEFATTING. INHAL:HEADACHE, DIZZINESS, NAUSEA, LOSS OF

CONSCIOUSNESS. PERM BRAIN & NERVOUS SYS DAMAGE.

Medical Cond Aggravated by Exposure:N

ONE WHEN USED IN ACCORDANCE WITH

SAFE HANDLING INSTRUCTIONS.

=====  
===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR. IF RESP SYMPTOMS DEVELOP SEEK MED

ATTN @ONCE. SKIN:PROMPTLY WASH W/SOAP & WATER. REMOVE CONTAMINATED

CLOTHING. EYE:FLUSH W/LG QUANTITIES OF WATER FOR 15MINS. SEEK MED

ATTN. INGEST:DONOT INDUCE VOMIT. KEEP PERSON WAR/QUIET. GET MED

ATTN. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL

PNEUMONITIS WHIC

H CAN BE FATAL.

=====  
===== Fire Fighting Measures =====

Flash Point:107F,42C

Lower Limits:0.7

Extinguishing Media:FOAM,CO2,DRY CHEM,WATER FOG OR ANY CLASS B EXT

AGENT.WATER MAY BE UNSUITABLE AS EXT MED BUT HELPFUL IN KEEPING

CNTN COOL

Fire Fighting Procedures:FIREFIGHTERS & OTHERS EXPO TO VAP/PROD OF

COMBUST SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.EVACUATE

AREA OF UPORT PERSONNEL.WEAR PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAP MAY

FORM EXPLOSIVE MIXTURE IN AIR &  
MAY BE IGN BY SPARKS/PILOT LIGHT/ETC.CLOSED CONTAINERS MAY RUPTURE  
WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE  
AREA. ABSORB SPILL W/ABSORBENT MATL SUCH AS  
SAWDUST/VERMICULTIE/SAND. PLACE MATL INTO CLOSED CONTAINER. IF LG  
DIKE AREA TO PREVENT FROM ENTERING WATER SYS/SEW ERS. WEAR PROT  
EQPMT DURING CLEANUP.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED/REPEATED INHAL OF  
HEATED VAP/SPRAY MIST.KEEP AWAY FROM HEAT/OPEN FLAME.MATL MAY CAUSE  
SENSITIZATION.DO NOT GET IN EYE/SKIN/CLOTHING.

Other Precautions:DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN.  
DO NOT WELD ON FULL/EMPTY CONTAINER. KEEP CONTAINER CLOSED WHEN NOT  
IN USE & PROPERLY LABELED. GROUND HANDLING EQPMT TO PREVENT SPARKS.  
EPA RCRA HOT LINE:800-424-9346/202-  
382-3000.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANISTER-TYPE RESP MUST BE WORN TO PREVENT INHAL  
OF VAP/SPRAY MIST WHEN TLV/PEL EXCEEDED.

Ventilation:GEN VENTI REQUIRED DURING NORMAL USE.LOC VENTI MAY BE  
REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPO LEVEL BELOW LIMITS

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:CHEMICAL GOGGLES OR FACE SHIELD.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN  
C

ONTACT. EYEWASH STATION & SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH CONTAMIN CLOTH BEF REUSE.WASH HANDS BEFORE  
EATING/SMOKING.

Supplemental Safety and Health  
WT/GAL:7.7LBS.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:307F,153C

Vapor Pres:2.6

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NIL

Appearance and Odor:PURPLE OILY LIQUID, MILD ODOR.

Percent Volatiles by Volume:65

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

CONTACT WITH STRONG OXIDANTS, ACIDS, BASES & EPOXY HARDENERS UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid: HEAT/SPARKS AND OPEN FLAMES. IF PRODUCT CONTAINS ALUMINUM MOISTURE IN CLOSED CONTAINERS WILL GENERATE HYDROGEN GAS.

Hazardous Decomposition Products: INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

===== Disposal Considerations =====

Waste Disposal Methods: IF DISCARDED, MATERIALS SHOULD BE TREATED AS HAZ WASTE BASED ON CHARACTERISTIC OF IGN AS DEFINED UNDER FED RCRA REGS(40CFR241). DISPOSAL OF MATERIALS REQUIRES COMPLIANCE W/APPLICABLE LABEL/PKG/RECORD KEEP STANDARDS. DISPOSE IAW FED/LOCAL/STATE AGENCIES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.