View NSN Online: https://aerobasegroup.ae/nsn/9620-00-075-9820 DIXON TICONDEROGA CO -- LUBRICATING FLAKE GRAPHITE NO 2 -- 9620-00-075-9820 Product ID:LUBRICATING FLAKE GRAPHITE NO 2 MSDS Date:01/01/1988 FSC:9620 NIIN:00-075-9820 MSDS Number: BWGHY === Responsible Party === Company Name: DIXON TICONDEROGA CO Address:756 BEACHLAND BLVD Box:3504 City: VERO BEACH State:FL ZIP:32964 Country:US Info Phone Num:201-657-2255 Emergency Phone Num:201-657-2255 Preparer's Name: J HEALY SAME

CAGE:72657

=== Contractor Identification ===

Company Name: DIXON TICONDEROGA CO

Address:756 BEACHLAND BLVD

Box:3504

City: VERO BEACH

State:FL ZIP:32964 Country:US CAGE:72657

======= Composition/Information on Ingredients ========

Ingred Name:GRAPHITE; (NATURAL GRAPHITE)

CAS:7782-42-5

RTECS #:MD9659600 Fraction by Wt: 100%

OSHA PEL:15 MPPCF (MFR) ACGIH TLV:2.5 MG/M3 (MFR)

======== Hazards Identification =========

======= LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: COUGH, DYSPNEA, BLACK SPUTUM, FIBROSIS, ETC. CHRONIC:PNEUMOCONIOSIS. Explanation of Carcinogenicity: NOT RELEVANT. Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure: DISEASES OF THE RESPIRATORY AND CARDIOVASCULAR SYSTEM. ======= First Aid Measures ========== First Aid:INGEST:CALL MD IMMEDIATELY . EYE:FLUSH WITH CLEAN WATER FOR @ LEAST 15 MINUTES, SKIN:WASH WITH SOAP AND WATER, INHAL:REMOVE TO FRESH AIR. ============ Fire Fighting Measures ========================= Extinguishing Media: NOT APPLICABLE. MEDIA SUITABLE FOR SURROUNDING FIRE Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. ======== Accidental Release Measures ============ Sp

ill Release Procedures:SWEEP OR VACUUM THOROUGHLY AS POWDERED GRAPHITE IS LUBRICANT AND THEREFORE SLIPPERY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

========== Handling and Storage ==============

Handling and Storage Precautions:STORE IN DRY AREA. GRAPHITE IS ELECTRICALLY CONDUCTIVE, TAKE CARE TO PREVENT CONTAMINATION OF ELECTRIC DEVICES.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =======

Respiratory Protection:NIOSH/MSHA APPROVED DUST MASK IF CONCENTRATION EXCEEDS 15 MPPCF.

Ventilation: MECHANICAL (GENERAL).

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection: ANSI APPROVED SAFETY GLASSES . Other Protective Equipment: NORMALLY NOT REQUIRED.

Work Hygienic Practices: GOOD HOUSEKEEPING RULES SHOULD BE OBSERVED.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

======== Physical/Chemical Properties ===========

Spec Gravity:2.25 (H*20=1)

Solub

ility in Water:NEGLIGIBLE

Appearance and Odor: GRAY - BLACK POWDER, NO ODOR

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS SUCH AS FLUORINE, POTASSIUM PEROXIDE, ETC. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:CO AND CO*2.

======= Disposal Considerations ===========

Waste Disposal Methods:BURY IN LANDFILL. DISPOSAL MUST BE I/A/W FEDERAL

, STATE & LOCAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informati on to their particular situation.