

SAN JUAN INTERNATIONAL,INC. -- SILICONE BRAKE FLUID SJI1020-MIL-46176A,PROD CODE J-1705
-- 9150-01-102-9455

===== Product Identification =====

Product ID:SILICONE BRAKE FLUID SJI1020-MIL-46176A,PROD CODE J-1705

MSDS Date:10/01/1997

FSC:9150

NIIN:01-102-9455

MSDS Number: BWPTH

=== Responsible Party ===

Company Name:SAN JUAN INTERNATIONAL,INC.

Address:27 INDUSTRIAL DRIVE

City:TRENTON

State:NJ

ZIP:0

8619-3244

Country:US

Info Phone Num:609-586-9500

Emergency Phone Num:609-586-9500

CAGE:1EJ92

=== Contractor Identification ===

Company Name:SAN JUAN INTERNATIONAL,INC.

Address:27 INDUSTRIAL DRIVE

City:TRENTON

State:NJ

ZIP:08619-3244

Country:US

Phone:609-586-9500

CAGE:1EJ92

===== Composition/Information on Ingredients =====

Ingred Name:POLY (DIMETHYLSILOXANE)

CAS:63148-62-9

RTECS #:JJ6484500

Other REC Limits:NONE RECOMMENDED

Ingred Name:TRIBUTYL PHOSPHATE

CAS:126-73-8

RTECS #

:TC7700000
Fraction by Wt: 2.25%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:0.2 PPM; 9394

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >3000 MG/KG (EST.)
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: VERY LOW ORAL AND INHALATION
HAZARD. MAY CAUSE SOME SKIN OR EYE IRRITATION ON CONTACT.
TRIBUTYLPHOSPHATE MAY BE
ABSORBED THROUGH THE SKIN. CHRONIC: NONE
SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:EYES: TEARING, IRRITATION. SKIN: IRRITATION.
Medical Cond Aggravated by Exposure:NO DATA FOUND.

=====
===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS
OPEN. GET MEDICAL ATTENTI
ON. SKIN-FLUSH WITH WATER. IF IRRITATION
OCCURS, GET MEDICAL ATTENTION. INHALATION-REMOVE TO FRESH AIR. GET
MEDICAL ATTENTION. INGESTION: IF CONSCIOUS, GIVE WATER TO DRINK &
INDUCE VOMITING, KEEPING VICTIM'S HEAD BELOW HIPS. GET IMMEDIATE
MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:402F,206C
Extinguishing Media:CARBON DIXOIDE, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR FULL
PROTECTIVE
CLOTHING INCLUDING POSITIVE-PRESSURE SELF-CONTAINED BREATHING
APPARATUS. USE WATER TO COOL FIRE EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:NONE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR APPROPRIATE PROTECTIVE GEAR. ABSORB ONTO
VERMICULITE. SWEEP UP INTO APPROPRIATE CONTAINER. WASH SPILL AREA
AFTER MATERIAL PICKUP IS COMPLETE WITH AN APPROPRIATE SOLVENT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

rations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competen
t professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.