View NSN Online: https://aerobasegroup.ae/nsn/6525-01-075-8325

EASTMAN KODAK COMPANY -- 180 5332 RP X-OMAT FIXER & REPLENISHER, PART B 6525-01-075-8325

Product ID:180 5332 RP X-OMAT FIXER & REPLENISHER, PART B MSDS Date:11/29/1995 FSC:6525 NIIN:01-075-8325 Kit Part:Y MSDS Number: BWRCP === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Ph one Num:716-477-3194 MSDS :800- 242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

======= Composition/Info

rmation on Ingredients =========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 60-65% Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETIC ACID (CERCLA) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 15-20% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM ACGIH TLV:10 PPM/15 STEL; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ALUMINUM SULFATE CAS:10043-01-3 RTECS #:BD1700000 Fraction by Wt: 15-20% Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 ACGIH T LV:2 MG/M3; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:D-GLUCONIC ACID CAS:526-95-4 RTECS #:LZ5057100 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM ACETATE CAS:127-09-3 RTECS #:AJ4300010 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHAL:VAPOR IRRITATING. EYE:CAUSES BURNS.VAPOR IRRITATING. SKIN:CAUSES IRRITATION. INGEST:HARMFUL IF SWALLOWED.MAY CAUSE BURNS OF GASTROINTESTINAL TRACT IF SWALLOWED. Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY CLASSIFICATION:IARC/ACGIH/NTP/OSHA:NONE. Effects of Overexposure:VAPOR IRRIT,BURNS/IRRIT EYES,SKIN IRRIT, HARMFUL IF SWALLOWED,BURNS GASTROINTESTINAL TRACT. Medical Cond Aggravated by Exposure:NONE SPECIFIED B Y MANUFACTURER.

First Aid:INHAL:MOVE TO FRESH AIR.TREAT SYMPTOMATIC.GET MED ATTN IF SYMPTONS PERSIST. EYES:IMMED FLUSH W/PLENTY OF WATER FOR @LEAST 15MINS.GET MED ATTN IMMED. SKIN:IMMED REMOVE CONTAMIN CLOTH/SHOES.WASH W/SOAP/ PLENTY OF WATER.GET MED ATTN IF SYMPTOMSOCCUR. INGEST:DO NOT INDUCE VOMIT.GIVE VICTIM A GLASS OF WATER.NEVER GIVE ANYTHING BY MOUTH TO UNCONSC PERSON.CALL PHYSICIAN/POISON CONTRO L CENTER IMMED.

Flash Point:NONE,NON-COMBUST Autoignition Temp:Autoignition Temp Text:NP Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS. Unusual Fire/Explosion Hazard:NONE.

Spill Re

lease Procedures:FLUSH TO SEWER W/LG AMTS OF WATER.OTHERWISE,ABSORB W/VERMI/OTHER INERT MATL,THEN PLACE IN CNTNR FOR CHEM WASTE.CLEAN THOROUGHLY TO REMOVE RESIDUAL CONTAMIN.LG:ABSORB W/VERMI/OTHER INERT MATL,THEN PLAC E IN CNTNR FOR CHEM WASTE.PREVENT RUNOFF(SUPPLEM) Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:DON'T GET IN EYES.AVOID SKIN/CLOTH CONTACT.AVOID BREATH VA

P.USE W/ADEQU VENT.KEEP CNTNR CLSD.KEEP AWAY FROM INCOMPATIBLE SUBSTANCES. Other Precautions: STRONGLY ACIDIC AQU SOLN.PROPERTIES: HI BIOCHEM OXY DEMAND, MAY CAUSE OXY DEPLETION IN AQU SYS.LOW POT TO AFFECT AQU ORGANISMS/2ND WASTE TREATMENT MICROBIAL METABOLISM;HI POT TO AFFECT GERM &/OR EARLY G ROWTH OF SOME PLANTS; LOW POT TO (SUPPLE) Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CON CEN BELOW RECOMMENDED EXPO LIMITS APPROVED RESP MUST BE WORN.RESP TYPE: ORGANIC VAP. IF RESP ARE USED PROGRAM SHOULD BE INSTITUTED TO ASSURE COMPLIANC E WITH OSHA STD 29CFR1910.134. Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS Protective Gloves: IMPERVIOUS GLOVES. Eye Protection: SAF GLASS W/SIDESHIELD, GOGG, FACE SHIELD. Other Protective Equipment: PROTECTIVE CLOTHING APPROPRIATE FOR RISK OF EXPOSUR E. EYEBATH, WASHING FACILITIES, SAFETY SHOWER. Work Hygienic Practices: WASH THOROUGHLY AFT HNDLG. Supplemental Safety and Health SPILL:ENTERING DRAIN/SEWERS/STREAMS.FLUSH SPILL AREA W/WATERSPRAY. OTHER PRECAUT: BIOCONCE. AFT DIL W/LG AMT OF WATER/2ND WASTE TREAT, MATL NOT EXPECTED TO CAUSE ADVERSE ENVIRO EFFECTS. KEY1=C1, PNIND:E(PART A),W(WORK SOLN), TO MAKE 10 GALLONS. HCC:C2 Boiling Pt:B.P. Text:>212F,>100C Melt/ Freeze Pt:M.P/F.P Text:NP Decomp Temp:Decomp Text:NP Vapor Pres:18 @20C Vapor Density:0.6 Spec Gravity:1.16 pH:2.0 Viscosity:NP Evaporation Rate & amp; Reference:NP Solubility in Water:COMPLETE. Appearance and Odor:LIQUID, COLORLESS, VINEGAR ODOR. Percent Volatiles by Volume:85 **Corrosion Rate:NP** Stability Indicator/Materials to Avoid:YES BASES.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition

Products:CARBON DIOXIDE, CARBON MONOXIDE, SULFUR DIOXIDE. HAZ COMBUST PROD:NONE (NON-COMBUSTIBLE).

Waste Disposal Methods:DISCHARGE/TREATMENT/DISPOSAL MAY BE SUBJECT TO NATIONAL/STATE/LOCAL LAWS. FLUSH TO SEWER W/LG AMTS OF WATER. FOR LG AMTS CONTRACT W/LICESNED CHEM DISPO AGENCY. CHEM(S) SUBJ TO REPORTING REQMTS OF SEC 313 TITLE III SARA/40CFR372:NONE.

Disclaimer (provided with this information by the comp iling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.