

EASTMAN KODAK COMPANY -- 841 5580;EKTACOLOR RA DEVELOPER REPLENISHR
RT;PT.A;KAN471101 -- 6750-01-384-7889

===== Product Identification =====

Product ID:841 5580;EKTACOLOR RA DEVELOPER REPLENISHR RT;PT.A;KAN471101

MSDS Date:11/02/1994

FSC:6750

NIIN:01-384-7889

Kit Part:Y

MSDS Number: BWRMR

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composit

ion/Information on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 55-60%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHANOL, 2,2',2"-NITRILOTRI-; (TRIETHANOLAMINE)
CAS:102-71-6
RTECS #:KL9275000
Fraction by Wt: 20-25%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:5 MG/M3

Ingred Name:DIETHYLHYDROXYLAMINE
CAS:3710-84-7
RTECS #:NC3500000
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SUBSTITUTED STILBENE
CAS:82640-05-9
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM CHLORIDE
CAS:7647-14-5
RTECS #:VZ4725000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL:EXPECTED TO BE A LOW HAZARD FOR
RECOMMENDED HANDLING.EYES:MAY CAUSE TRANSIENT IRRITATION.SKIN:LOW
HAZARD FOR RE

COMMENDED HANDLING.INGEST:LOW INGESTION HAZARD.

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%

WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:EYES:TRANSCIENT IRRITATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.GET MEDICAL ATTENTION.EYES:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRA TION IF NEEDED.INGEST:DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.IF CONSCIOUS,GIVE 1-2 GLASSES OF WATER.

===== Fire Fighting Measures =====

Flash Point:100F-200F

Extinguishing Media:WATER SPRAY,DRY CHEMICAL,CARBON DIOXIDE,ALCOHOL FOAM.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FI RE EXPOSED CONTAINERS WITH WATER FOG.

Unusual Fire/Explosion Hazard:COMBUSTIBLE VAPORS MAY ACCUMULATE IN THE HEADSPACE OF THE CONTAINER.FIRE CONDITIONS MAY EVOLVE TOXIC FUMES.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIEL IN AN APPROPRIATE CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.SMALL SPILLS-NEUTRALIZE TO PH 2-12.5;FLU SH TO SE WER WITH PLENTY OF WATER.

Neutralizing Agent:NOT REPORTED.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM HEAT,SPARKS,FLAMES AND INCOMPATIBLE MATERIALS.

Other Precautions:AVOID SKIN AND EYE CONTACT.DO NOT INHALE VAPORS/MISTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IN

NORMAL SERVICE.

Ventilation:USE GENERAL DILUTION VENTILATION.MFR RECOMMENDS 10 AIR CHANGES/HOUR.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health

KEY1;F6.REFER TO PNIND-B(PT.B) ;PNIND-C(PT .C); PNIND W(W/S).

===== Physical/Chemical Properties =====

HCC:F6

Boiling Pt:B.P. Text:>212F,>100C

Decomp Temp:Decomp Text:356F,180C

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.06

pH:10.7

Solubility in Water:COMPLETE

Appearance and Odor:LIQUID;YELLOW;AMINE

Percent Volatiles by Volume:55-60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID TE

MPERATURES ABOVE 80C/176F.

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE,OXIDES OF NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly

or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.