

EASTMAN KODAK COMPANY -- 825 4237 T-MAX RS DEVELOPER AND REPLENISHER, PART B --
6750-01-388-7764

===== Product Identification =====

Product ID:825 4237 T-MAX RS DEVELOPER AND REPLENISHER, PART B

MSDS Date:10/16/1996

FSC:6750

NIIN:01-388-7764

Kit Part:Y

MSDS Number: BWRNG

== Responsible Party ==

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:

US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

== Contractor Identification ==

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Compos

ition/Information on Ingredients =====

Ingred Name:DIETHYLENE GLYCOL
CAS:111-46-6
RTECS #:ID5950000
Fraction by Wt: 95%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETIC ACID (SARA III)
CAS:64-19-7
RTECS #:AF1225000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:1,4-DIPHENYL-3-(PHENYLIAMINO)-1H-1,2,4-TRIAZOLIUM HYDROXIDE
CAS:2218-94-2
Fraction by Wt: 200F,>93C
Lower Limits
:NOT GIVEN
Upper Limits:NOT GIVEN
Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:MAY FORM PEROXIDES OF UNKNOWN STABILITY.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATE
RIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUAL CONTAMINATION.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION. STORE AWAY FROM HEAT AND LIGHT. KEEP FROM CONTACT WITH OXIDIZING MATERIALS. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions:THE ROUTINE USE OF A NONALKALINE (ACID) TYPE OF HAND CLEANER AND REGULAR

CLEANING OF WORKING SURFACES WILL HELP MINIMIZE
THE POSSIBILITY OF A SKIN REACTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN

CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. KEY1:N1.

===== Physical/Chemical Properties =====

HCC:T6

Boiling Pt:B.P. Text:>212F,>100C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Decomp Temp:Decomp Text:NOT GIVEN

Vapor Pres:18

Vapor Density

:0.6

Spec Gravity:1.12

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:COMPLETE

Appearance and Odor:AMBER LIQUID, VINEGAR ODOR

Percent Volatiles by Volume:< 5%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:MINIMIZE EXPOSURE TO AIR. UPON PROLONGED STORAGE, MAY FORM PEROXIDES OF UNKNOWN STABILITY.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXI

DE.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH < 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.