

EASTMAN KODAK COMPANY -- 809 0532, KODAK FLEXICOLOR STABILIZER & REPLENISHER LF --
6750-01-285-1770

===== Product Identification =====

Product ID:809 0532, KODAK FLEXICOLOR STABILIZER & REPLENISHER LF

MSDS Date:07/19/1995

FSC:6750

NIIN:01-285-1770

Kit Part:Y

MSDS Number: BWRXZ

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Co

untry:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Informat

ion on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 70-75%
Other REC Limits:NONE RECOMMENDED

Ingred Name:HEXAMINE (HEXAMETHYLENETETRAMINE)
CAS:100-97-0
RTECS #:MN4725000
Fraction by Wt: 25-30%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM DODECYLBENZENE SULFONATE (CERCLA)
CAS:25155-30-0
RTECS #:DB6825000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:DIPROPYLENE GLYCOL
CAS:110
-98-5
RTECS #:UB8785000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-IONIC SURFACTANT
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:1,2-BENZISOTHIAZOL-3(2H)-ONE
CAS:2634-33-5
RTECS #:DE4620000
Fraction by Wt: 212F,>100C
Vapor Pres:18 MMHG
Vapor Density:0.6 AIR=1
Spec Gravity:1.06
pH:7.7
Solubility in Water:COMPLETE
Appearance and Odor:LIQUID, AMBER, SLIGHT AMINE ODOR.
Percent Volatiles by Volume:70-75

===== Stability and Reactivity D

ata =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, STRONG ACIDS.

Stability Condition to Avoid: STABLE; HOWEVER, MATERIAL CAN DECOMPOSE
ABOVE 295. AVOID TEMPERATURES ABOVE 195C.

Hazardous Decomposition Products: AMMONIA, FORMALDEHYDE. CARBON
MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, OXIDES OF SULFUR.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods: DISC

HARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT
TO NATIONAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE
AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek co
mpetent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.