

DEL PAINT MANUFACTURING COMPANY -- F0201 -- 8010-00-597-8229

===== Product Identification =====

Product ID:F0201  
MSDS Date:08/30/1993  
FSC:8010  
NIIN:00-597-8229  
MSDS Number: BWSSL  
=== Responsible Party ===  
Company Name:DEL PAINT MANUFACTURING COMPANY  
Address:3105 EAST RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Info Phone Num:405-672-1431  
Emergency Phone Num:800-424-9300 CHEMTREC  
Preparer  
's Name:ONEY FLEMING  
CAGE:EO522  
=== Contractor Identification ===  
Company Name:DEL PAINT MANUFACTURING CORP  
CAGE:EO522  
Company Name:DEL PAINT MFG  
Address:3105 EAST RENO  
Box:City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431  
CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTILLATES  
CAS:8002-05-9  
RTECS #:SE7449000  
Fraction by Wt: 27.66%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

Ingred Name:XYLENE

(SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 0.24%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:NONHAZARDOUS INGREDIENTS

Fraction by Wt: 72.10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC: 3.25 LB/GL; 390 G/LTR

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:115F,46C

Autoignition

Temp:Autoignition Temp Text:540 F

Lower Limits:1

Upper Limits:6

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM WATER MAY SPREAD FIRE, USE WATER SPRAY ONLY TO COOL CONTAINERS EXPOSED TO FIRE.

Fire Fighting Procedures:WEAR SCBA(PRESSURE DEMAND MSHA/NIOSH/EQUIVALENT)& FULL PROTECTIVE GEAR.WATER SPRAY MAY BE USED FOR COOLING CNTNR TO PREVENT PRESSURE BLDUP/AUTOIGNIT/EXPLOSION.

Unusual Fire/Explosion Hazard:VAPOR HEAVIER THAN AIR & MAY TRAVEL ALONG GROUND/BE MOVED

BY VENT & IGNITED BY PILOT LIGHTS & OTHER

FLAMES,SPARKS,HEATERS,SMOKING OR OTHER REMOTE IGNITN SOURCES

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:303F,151C

Decomp Temp:Decomp Text:752F,400C

Vapor Pres:2.58

Vapor Density:> AIR

Spec Gravity:1.23 (H2O=1)

Viscosity:77 - 86 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in W

ater:NO

Appearance and Odor:CREAM LIQUID WITH SLIGHT ODOR

Percent Volatiles by Volume:45.97

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT STORE NEAR HEATED SURFACES OPEN  
FLAMES OR IGNITION SOURCES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defe

nse. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.