

DEL PAINT CORPORATION -- F0201 -- 8010-00-616-7495

===== Product Identification =====

Product ID:F0201  
MSDS Date:08/30/1993  
FSC:8010  
NIIN:00-616-7495  
MSDS Number: BWSSV  
=== Responsible Party ===  
Company Name:DEL PAINT CORPORATION  
Address:3105 EAST RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Info Phone Num:405-672-1431  
Emergency Phone Num:800-424-9300 CHEMTREC  
Preparer's Name:ONEY FLEMING

CAGE:EO326  
=== Contractor Identification ===  
Company Name:DEL PAINT CORPORATION \*  
Address:3105 EAST RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431  
CAGE:EO326  
Company Name:DEL PAINT MFG  
Address:3105 EAST RENO  
Box:City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431  
CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTILLATE  
CAS:8002-05-9  
RTECS #:SE7449000  
Fraction by Wt: 27.66%  
Other REC Limits:NONE R

ECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

Ingred Name:XYLENE (SARA 313) (CERCLA)  
CAS:1330-20-7  
RTECS #:ZE2190000  
Fraction by Wt: 0.24%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:NON-HAZARDOUS INGREDIENTS  
Fraction by Wt: 72.10%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC: 3.25 LB/GL; 390 G/LTR  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE CONTACT: IRRITATION, REDNESS,  
TEARING, AND BLURRED VISION. SKIN CONTACT: PROLONGED OR REPEATED  
EXPOSURE CAN CAUSE MODERATE IRRITATION, DEFATTING AND DERMATITIS.  
INHALATION: NASAL AND RESPIRATORY IRRITATION, DIZZINESS, NAUSEA,  
AND HEADACHE. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION,  
NAUSEA, VOMITING & NAUSEA.

Effects  
of Overexposure:IF TLV'S ARE EXCEEDED SKIN CONTACT PRODUCES  
REDNESS. EYE CONTACT PRODUCES REDNESS AND PAIN. INHALATION GIVES  
LABORED BREATHING, DULLNESS, DROWSINESS. INGESTION CAN CAUSE  
ABDOMINAL PAIN AND NAUSEA.

Medical Cond Aggravated by Exposure:DISEASES OF THE RESPIRATORY SYSTEM.

=====  
===== First Aid Measures =====  
=====

First Aid:EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15  
MINUTES, OCCASIONALLY LIFTING EYELIDS. SEEK MEDICAL ATTENTION.

SKIN

CONTACT: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED SKIN WITH SOAP & WATER. I NHALATION: REMOVE TO FRESH AIR, ADMINISTER OXYGEN IF NECESSARY, SEEK MEDICAL ATTENTION. INGESTION: KEEP WARM, QUIET, AND GET MEDICAL ATTENTION. DO NOT INDUCE VOMITING.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC

Flash Point:115F,46C

Autoignition Temp:Autoignition Temp Text:540 F

Lower Limits:1

Upper Limits:6

Extinguishing Media:CARBON DIOXIDE, DRY

CHEMICAL, OR FOAM. WATER MAY

SPREAD FIRE, USE WATER SPRAY ONLY TO COOL CONTAINERS EXPOSED TO FIRE.

Fire Fighting Procedures:WEAR SCBA (PRESSURE DEMAND MSHA/NIOSH) & FULL PROTECTIVE GEAR. USE WATER SPRAY TO COOL CONTAINERS TO PREVENT PRESSURE BLDUP & AUTOIGNITION/EXPLOSION W/HEAT.

Unusual Fire/Explosion Hazard:VAPOR HEAVIER THAN AIR & MAY TRAVEL ALONG GROUND OR BE MOVED BY VENT & IGNITED BY PILOT LIGHT, OTHER FLAMES, SPARK, HEATER, SMOKING OTHER REMOTE IGNITN SOURCES.

===

=====  
Accidental Release Measures  
=====

Spill Release Procedures:VENTILATE THE AREA. COVER SPILL WITH INERT ABSORBENT MATERIAL AND SHOVEL WITH NON-SPARKING TOOL INTO CONTAINER. REMOVE CONTAINERS TO A SAFE AREA AND SEAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A CLEAN DRY AREA. KEEP AWAY FROM SPARKS, FIRE AND REMOTE IGNITION SOURCES.

Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP A WAY FROM

CHILDREN. ALL EQUIPMENT SHOULD BE GROUNDED TO REDUCE STATIC ELECTRICITY HAZARD. USE NON-SPARKING TOOLS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:IF TLV OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED, USE A RESPIRATOR WITH APPROPRIATE CARTRIDGES (MIOSH APPROVED). ENGINEERING OR MANAGEMENT CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

Ventilation:LOCAL EXHAUST MUST BE SUFFICIENT TO KEEP AIRBORNE VAPOR CONCENTRAT

IONS BELOW THE TLV LIMIT.

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:SUGGEST THAT SOURCE OF CLEAN WATER BE AVAILABLE IN WORK AREA FOR FLUSHING EYES & SKIN.WEAR IMPERVIOUS CLOTHING AS NEEDED

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:303F,151C

Decomp Temp:Decomp Text:752F,400C

Vapor Pres:2.58

Vapor Density:> AIR

Spec Gravity:1.23 (WATE

R=1)

Viscosity:77 - 86 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NO

Appearance and Odor:ORANGE LIQUID WITH SLIGHT ODOR

Percent Volatiles by Volume:45.97

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT STORE NEAR HEATED SURFACES, OPEN FLAMES OR IGNITION SOURCES.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATORY CONTROLS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information t

o be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.