

S C JOHNSON WAX -- FREEDOM SPEED STRIPPER, 14610-5-6 -- 7930-01-214-3705

=====
Product Identification
=====

Product ID:FREEDOM SPEED STRIPPER, 14610-5-6

MSDS Date:02/25/1991

FSC:7930

NIIN:01-214-3705

MSDS Number: BWSWN

=== Responsible Party ===

Company Name:S C JOHNSON WAX

Address:1525 HOWE ST

City:RACINE

State:WI

ZIP:53403

Country:US

Info Phone Num:414-631-2777

Emergency Phone Num:800-228-5635

Pr

eparer's Name:TERRY A MEYERS

CAGE:GO109

=== Contractor Identification ===

Company Name:S C JOHNSON WAX

Address:1525 HOWE ST

City:RACINE

State:WI

ZIP:53403-5011

Country:US

Phone:(414)631-2777

CAGE:GO109

Company Name:SC JOHNSON AND SON INC

Address:1525 HOWE ST

Box:City:RACINE

State:WI

ZIP:53403-2236

Country:US

Phone:800-725-6737

CAGE:32204

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHANOL, 2-AMINO-; (MONOETHANOLAMINE)

CAS:141-43-5

RTECS #:KJ5775000

Fraction

by Wt: 6-10%
OSHA PEL:3 PPM
ACGIH TLV:3 PPM/6 STEL

Ingred Name:XYLENESULFONIC ACID, SODIUM SALT; (SODIUM XYLENE SULFONATE)
CAS:1330-72-7
RTECS #:ZE5100000
Fraction by Wt: 3-8%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:ETHANOL, 2-PHENOXY-; (GLYCOL ETHER)
CAS:122-99-6
RTECS #:KM0350000
Fraction by Wt: 10-15%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:2-PROPANOL, 1-BUTOXY-; (GLYCOL ETHER)
CAS:5131-66-8
RTECS #:UA7700000
Fraction by Wt: 1-6%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:SODIUM SILICATE
CAS:1344-09-8
Fraction by Wt: 1-4%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:POLYOXYETHYLENE PHENOL ETHER
CAS:39464-70-5
Fraction by Wt: 1-3%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 60-70%
OSHA PEL:N/K
ACGIH TLV:N/K

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:

NO

Health Hazards Acute and Chronic:ACUTE:DIRECT CONT OF PRODUCT WITH EYES CAN CAUSE SEVERE IRRITATION AND DAMAGE. DIRECT CONTACT OF PRODUCT WITH SKIN CAN CAUSE IRRITATION. IF TAKEN INTERNALLY, PRODUCT MAY CAUSE CORROSIVE DAMAGE TO MOUTH, THROAT OR STOMACH.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:INDIVIDUALS W/CHRONIC RESP DISORDERS SUCH AS ASTHMA, CHRONIC BRONCH, EMPHYSEMA, ETC., MAY BE ADV

ERSELY AFFECTED BY EXPOS TO ANY VAP/AIRBORNE PARTICULATE MATTER. PERSONS W/PRE-EXISTING SKIN (SUPDAT)

=====
===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O₂/ARTF RESP) . SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER. CALL MD . EYES:FLUSH W/WATER FOR @ LEAST 15 MINS, THEN GET PROMPT MED AID. INGEST :DO NOT INDUCE VOMIT. SEEK MED AID AT ONCE. DRINK LARGE AMTS OF WATER/MILK & SEEK MEDICAL AID.

=====
===== Fire Fighting Measures =====

Flash Point:180F,82C

Extinguishing Media:FOAM, CO₂, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:NIOSH/MSHA APPROVED SCBA & FULL PROT EQUIP . NORMAL FIRE FIGHTING PROCEDURES MAY BE USED. COOL & USE CAUTION WHEN APPROACHING/HNDLG FIRE-EXPOS CNTNRS.

Unusual Fire/Explosion Hazard:CORROSIVE MATL. VAPORS MAY ACCUMULATE IN CONFINED SPACES (E.G., PITS, SUMPS, SEWERS) AND INADEQUATELY VENTILATED AREAS.

=====
===== A
ccidental Release Measures =====

Spill Release Procedures:DIKE LG SPILLS. ABSORB W/OIL-DRI OR SIMILAR INERT MATL. SWEEP/SCRAPE UP & CONTAINERIZE. RINSE AFFECTED AREA THORO W/WATER. WEAR/USE APPROP PROT EQUIP.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:WARNING:CONTAINS ALKALI DETERGENT. CAN CAUSE EYE DMG. AVOID CONT W/EYES, SKIN & CLTHG. HARMFUL IF SWALLOWE

D. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:WHEN HNDLG CONCENTRATE, WEAR EYE PROT & RUBB GLOVES.
PROD RESIDUE MAY REMAIN ON/IN EMPTY CNTNRS. ALL PRECAUT FOR HNDLG
PROD MUST BE USED IN HNDLG EMPTY CNTNR & RESIDUE. KEEP FROM
FREEZING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPEC REQUIREMENTS UNDER NORMAL USE CNDTNS.
NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN

Ventilation:GENERAL ROOM VENTIL
ATION ADEQUATE.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPRVD EMER EYE WASH & DELUGE SHOWER .
WHERE GROSS EYE/SKIN CONT MAY MAY BE PROBLEM, WEAR/USE APPROP
(SUPDAT)

Work Hygienic Practices:USE GOOD PERSONAL HYGIENE PRACTICES. WASH THORO
AFTER HANDLING.

Supplemental Safety and Health

PH:13.1-13.4. MED CNDTNS AGGRAVATED:DISORDERS MAY BE MORE SUSCEPTIBLE
TO IRRIT EFTS. WASTE DISP METH:CORR WASTES. WASTE
FROM NORM PROD

USE MAY BE SEWERED TO PUBLIC-OWNED TREATMET WORKS (POTW) I/A/W AP
PLIC FED, ST, & LOCAL PRETREATMENT REQUIREMENTS. OTHER PROT
EQUIP:PROT EQUIP. LAUNDRER CONTAMD CLTHG/EQUIP BEFORE REUSE.

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text: