

GLIDDEN PAINT -- 0600113 LN-601 -- 8040-01-259-9971

=====  
Product Identification  
=====

Product ID:0600113 LN-601

MSDS Date:04/20/1994

FSC:8040

NIIN:01-259-9971

MSDS Number: BWXWB

=== Responsible Party ===

Company Name:GLIDDEN PAINT

Address:925 AUCLID AVE

City:CLEVELAND

State:OH

ZIP:44115

Country:US

Info Phone Num:216-344-8207

Emergency Phone Num:216-344-8207

CAGE:JO648

=== Contractor Identificati

on ===

Company Name:GLIDDEN PAINT

Address:925 EUCLID AVE

City:CLEVELAND

State:OH

ZIP:44115

Country:US

Phone:800-545-2643

CAGE:JO648

Company Name:GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

Address:925 EUCLID AVE

Box:City:CLEVELAND

State:OH

ZIP:44115

Country:US

Phone:800-545-2643/216-344-8207

CAGE:01PD6

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CARBONIC ACID, CALCIUM SALT (1:1), CALCIUM CARBONATE,  
DURAMITE

CAS:471-34-1

RTECS #:FF9335000

Fraction by Wt: 10-

20%  
Other REC Limits:10 MG/CUM (DUST)  
OSHA PEL:5 MG/CUM  
ACGIH TLV:10 MG/CUM

Ingred Name:CLAY (KAOLIN), ALUMINUM SILICATE  
CAS:1332-58-7  
RTECS #:GF1670500  
Fraction by Wt: 30-40%  
OSHA PEL:5 MG/CUM  
ACGIH TLV:10 MG/CUM TOTAL DUST

Ingred Name:SILICON DIOXIDE, CRYSTALLINE QUARTZ, SAND (ANIMAL  
SUFFICIENT/HUMAN LIMITED EVIDENCE BY IARC, NTP). GROUP 2A - \*94-4\*  
CAS:14808-60-7  
RTECS #:VV7330000  
Fraction by Wt: 0.1-1%  
Other REC Limits:0.05 MG/CUM NIOSH  
OSHA PEL:0.1 MG/CUM RESP DUST  
ACGIH TLV:0.1 MG/CU  
M RESP DUST

Ingred Name:3-METHYL PENTANE  
CAS:96-14-0  
RTECS #:SA2995500  
Fraction by Wt: 5-10%  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM

Ingred Name:BUTANE, 2,2-DIMETHYL  
CAS:75-83-2  
RTECS #:EJ9300000  
Fraction by Wt: 1-5%  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM

Ingred Name:BUTANE, 2,3-DIMETHYL-  
CAS:79-29-8  
RTECS #:EJ9350000  
Fraction by Wt: 1-5%  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM

Ingred Name:2-METHYL PENTANE  
CAS:107-83-5  
RTECS #:SA2995000  
Fraction by Wt: 10-20%  
OSHA PEL:1000 PPM  
ACGIH TLV:500 PPM

Ing

red Name:PETROLEUM OIL, HYDROTREATED HEAVY NAPHTHENIC DISTILLATE  
(PETROLEUM), PETROLEUM DISTILLATES, MINERAL OIL (SEVERE)

CAS:64742-52-5

RTECS #:PY8035001

Fraction by Wt: 1-5%

Ingred Name:STEAM-CRACKED, POLYMERS W/LIGHT STEAM-CRACKED PETROLEUM  
NAPHTHA \*94-4\*

CAS:68410-16-2

Fraction by Wt: 10-20%

Ingred Name:1,3-BUTADIENE POLYMER, STYRENE-BUTADIENE POLYMER, SBS, SBS  
(BLOCK POLYMER)

CAS:9003-55-8

RTECS #:WL6478000

Fraction by Wt: 1-5%

Ingred Name:BUTADIENE, STYRENE, DIVINYLBEN  
ZENE POLYMER

CAS:26471-45-4

Fraction by Wt: 5-10%

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF RESPIRATORY  
TRACT/MUCOUS MEMBRANE. ANESTHETIC EFFECT/DEATH. SKIN:

IRRITATION/DERMATITIS. EYES: IRRITATION/CONJUNCTIVITIS. INGESTION:  
LUNG INFLAMMATION & DAMAGE DUE TO ASPIRATION OF MATERIAL INT

O

LUNGS, GI DISTURBANCES, CNS DEPRESSION, INTOXICATION, PARALYSIS,  
CARDIAC FAILURE, DEATH. (SEE SUPP)

Explanation of Carcinogenicity:SEE INGREDIENTS.

Effects of Overexposure:IRRITATION, DROWSINESS, DIZZINESS,

LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING,  
COUGHING, RESPIRATORY PROBLEMS, INTOXICATION, NARCOSIS, DIFFICULTY  
BREATHING, CONVULSIONS, LOSS OF CONSCIOUSNESS, DEFATTING,  
INFLAMMATION

Medical Cond Aggravated by Exposure:EYE, SKIN & RESPIRATORY DISORDE

RS.

=====  
First Aid Measures  
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE & SUPPORT BREATHING.  
HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. SKIN: FLUSH W/WATER.  
WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH IMMEDIATELY W/PLENTY OF  
WAT ER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
Fire Fighting Measures  
=====

Flash Point Method:SCC

Flash Point:1F

Lower Limits:1.2

Upper Limits:7

Exting

uishing Media:DRY CHEMICAL/FOAM, WATER FOG, CO2

Fire Fighting Procedures:WATER MAY BE USED TO COOL & PROTECT EXPOSED  
CONTAINERS. USE FULL PROTECTIVE CLOTHING, EYE PROTECTION & SELF  
CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN  
EXPOSED TO EXTREME HEAT/FIRE. VAPORS MAY IGNITE EXPLOSIVELY AT  
AMBIENT TEMPS. (SEE SUPP)

=====  
Accidental Release Measures  
=====

Spill Release Procedures:VENTILATE W/EXPLOSION P

ROOF EQUIPMENT &

NON-SPARKING TOOLS. EVACUATE. PLACE MATERIAL IN PROPER CONTAINER.

LARGE: SHUT OFF LEAK SAFELY. DIKE & CONTAIN. PUMP TO

STORAGE/SALVAGE VESSELS. RINSE WATER OUT OF SEWERS. SMALL: USE

ABSORBENT TO PICKUP RESIDUE

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE AIR & MAY TRAVEL TO AN IGNITION  
SOURCE & FLASHBACK. VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT  
ELEVATED TEMPS. HEALTH CONT'D: REPEATED/PR

OLONGED OVEREXPOSURE TO

SOLVENTS MAY CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

INTENTIONAL MISUSE/INHALING CONTENTS MAY BE HARMFUL/FATAL.

=====  
Physical/Chemical Properties  
=====

HCC:F2

Boiling Pt:B.P. Text:122F

Spec Gravity:1.127

Appearance and Odor:TAN PASTE.

Percent Volatiles by Volume:49.97

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS, ACIDS.

Stability Condition to Avoid:

ELEVATED TEMPS, STORAGE NEAR ACIDS,  
SPARKS, OPEN FLAME & OTHER IGNITION SOURCES.

Hazardous Decomposition Products:CO, CO2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &  
FEDERAL REGULATIONS. UN 1133.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatso  
ever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.