

SENTRY CHEMICAL CO INC -- ELECTRON AEROSOL ENVIRONMENTALLY PREFERRED DIELECTRIC SOLVNT -- 6850-01-371-8048

===== Product Identification =====

Product ID:ELECTRON AEROSOL ENVIRONMENTALLY PREFERRED DIELECTRIC SOLVNT

MSDS Date:02/03/1995

FSC:6850

NIIN:01-371-8048

MSDS Number: BWZNW

=== Responsible Party ===

Company Name:SENTRY CHEMICAL CO INC

Address:1481 ROCK MOUNTAIN BLVD

Box:748

City:STONE MOUNTA

IN

State:GA

ZIP:30086

Country:US

Info Phone Num:404-934-4242/FAX -0932/800-877-3339

Emergency Phone Num:404-934-4242

CAGE:8S927

=== Contractor Identification ===

Company Name:SENTRY CHEMICAL CO INC

Address:1481 ROCK MOUNTAIN BLVD

Box:748

City:STONE MOUNTAIN

State:GA

ZIP:30086

Country:US

Phone:770-934-4242

CAGE:8S927

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: >60%

Other REC Limits:NONE RECOMME

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INGEST:CAN CAUSE GASTROINTESTINAL  
IRRITATIO. INHALE:ASPIRATION INTO LUNGS MAY CAUSE INJURY.  
EYES:EXPOSURE TO HIGH CONCENTRATIONS OF VAPORS MAY CAUSE SLIGHT  
IRRITATION. SKIN:PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN  
IRRITATION.

Explanation of Carcinogenicity:NO  
T CARCINOGENIC.

Effects of Overexposure:INGESTION-CAN CAUSE NAUSEA, VOMITING.  
INHALATION-EXCESSIVE INHALATION OF VAPORS MAY CAUSE DIZZINESS OR  
HEADACHE. SKIN-REPEATED LONGTERM CONTACT MAY CAUSE EXCESSIVE DRYING  
OR FLAKING OF SKIN.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:INGEST:DO NOT INDUCE VOMITING. PRODUCT CONTAINS HYDROCARBON,  
CALL PHYSICIAN. INHALE:REMOVE TO FRESH AIR.  
IF BREATHING IS  
DIFFICULT, GIVE OXYGEN, CALL PHYSICIAN. EYES:IRRIGATE IMMEDIATELY  
WITH WATER FOR AT LEAST 15 MINUTES, CALL PHYSICIAN. SKIN:WASH OFF  
IN FLOWING WATER OR SHOWER USING SOAP & WATER. REMOVE CONTAMINATED  
CLOTHING & WASH BEFORE REUSE.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:FLAMMABLE AEROSL  
Lower Limits:0.7%  
Upper Limits:6%  
Extinguishing Media:REGULAR FOAM, CO2 OR DRY CHEMICALS.  
Fire Fighting Procedures  
:FIGHT AS A HYDROCARBON FIRE. WEAR  
SELF-CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:AEROSOL CAN WILL BURST IF EXPOSED TO HEAT  
OF FIRE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL:REMOVE ALL SOURCES OF IGNIT!  
ABSORB LIQUID ON ABSORB MATERIAL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE AS LEV

EL 3 AEROSOL (NFPA 30B).

STORE AWAY FROM IGNITION SOURCES & AVOID BREATHING VAPORS. USE  
W/ADEQUATE VENTILATION.

Other Precautions:ELECTRON DIELECTRIC SOLVENT IS COMBUSTIBLE  
(FLASHPOINT