

DEFT CHEMICAL COATING DIV -- 04GY002CAT MIL-C-85285B 36375 TYPE II

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 01-293-3019
MSDS Date: 04/30/1993
MSDS Num: BWZRP
Product ID: 04GY002CAT MIL-C-85285B 36375 TYPE II
MFN: 02
Kit Part: Y
Responsible Party
Cage: 33461
Name: DEFT INC CHEMICAL COATING DIV
Address: 17451 VO
N KARMAN AVE
City: IRVINE CA 92714-6205
Info Phone Number: 714-474-0400
Emergency Phone Number: 714-474-0400
Preparer's Name: NORM GAUL
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 33461
Name: DEFT, INC.
Address: 17451 VON KARMAN AVE
City: IRVINE CA 92614
Phone: 949-474-0400

=====
Item Description Information
=====

Item Manager: GSA
Item Name: POLYURETHANE COATING
Specification Number: MIL-C-85285
Type/Grade/Class: TYPE II
Unit of Issue: KT
UI Container Qty: 0
Type of Container: UNKNOWN

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====
Health Hazards Data
=====

=====
LD50 LC50 Mixture: UNKNOWN

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: ACUTE:INHALATION MAY CAUSE RESPIRATORY IRRITATION & CNS DEPRESSION.CONTACT MAY CAUSE SKIN & EYE IRRITATION.INGESTION MAY CAUSE GI TRACT IRRITATION;CORROSIVE ACTION IN MOUTH,STOMACH & DIGESTIVE TRACT.C HRONIC:PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN DEFATTING,DRYING &

mp; IRRITATION; SENSITIZATION.

Explanation Of Carcinogenicity: NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Signs And Symptions Of Overexposure: INHALED-IRRITATION, HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS OR COMA. EYES-TEARING, REDNESS, SWELLING. SKIN-SWELLING, REDNESS, RASH. INGESTED-NAUSEA, VOMITING.

Medical Cond Aggravated By Exposure: ASTHMA AND ANY OTHER RESPIRATORY DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS. ISOCYANATE SENSITIZATION.

First Aid: INHALED-MOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP & WATER. EYES-FLUSH WITH CLEAN LUKEWARM WATER FOR AT LEAST 15 MINUTES, LIFTING EYELIDS. GET MEDICAL ATTENTION. INGESTED-DO NOT INDUCE VOMITING! NOTHING BY MOUTH IF UNCONSCIOUS. OBTAIN MEDICAL ATTENTION.

=====
Handling and Disposal
=====

=====
Spill Release Procedures: EVACUATE ALL NON-ESSENTIAL PERSONNEL. ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: WASTE MUST BE DISPOSE OF IAW LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. EMPTY CONTAINERS MUST BE HANDLED WITH CARE, DUE TO PRODUCT RESIDUE & FLAMMABLE VAPOR. EPA/RCRA H AZWASTE NUMBERS: D001, F003, F005 (PE R MFR).

Handling And Storage Precautions: STORE IN A COOL, DRY, WELL-VENTILATED PLACE IN TIGHTLY CLOSED CONTAINERS AWAY FROM SOURCES OF IGNITION AND INCOMPATIBLE MATERIALS.

Other Precautions: STORE IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 29 CFR 1910.106.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point Text: 60.0F,15.6C

Lower Limits: 1.05

Upper Limits:

Extinguishing Media: WATER FOG OR SPRAY, CARBON DIOXIDE, DRY CHEMICAL, FOAM OR ALCOHOL FOAM.

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DURING EMERGENCY CONDITIONS OVER EXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

=====

Control Measures

===

=====

Respiratory Protection: IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IN ACCORDANCE WITH 29 CFR 1910.13 4 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation: USE ADEQUATE EXPLOSION-PROOF MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves: COTTON, NEOPRENE, RUBBER, POLYETHYLENE

E

Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: LONG SLEEVED SHIRTS AND LONG LEG TROUSERS ARE RECOMMENDED.

Work Hygienic Practices: WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health: KEY1=F3.

=====

Physical/Chemical Properties

=====

HCC: F3

B.P. Text: >241F,>116C

M.P/F.P Text: UNKNOWN

Decomp Text: UNKNOWN

Vapor Pres: UNKNOWN

Vapor Density: >1

Spec Gravity: 1.002

Viscosity: UNKNOWN

Evaporation Rate & Reference: 0.95 (N-BUTYL ACETATE=1)

Solubility in Water: INSOLUBLE

Appearance and Odor: AMBER LIQUID WITH SOLVENT ODOR.

Percent Volatiles by Volume: 35.2

Corrosion Rate: UNKNOWN

=====

Reactivity Data

=====

Stability Indicator: YES

Stability Condition T

o Avoid: HIGH TEMPERATURES, SPARKS OR OPEN FLAMES.

Materials To Avoid: WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS, SURFACE ACTIVE MATERIALS.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE AND OXIDES OF NITROGEN, TRACES OF HYDROGEN CYANIDE AND HEXAMETHYL DIISOCYANATE (HDI).

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: WILL NOT OCCUR.

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
Transportation Information
=====

Responsible Party Cage: 33461

Trans ID NO: 122855

Product ID: 04GY002CAT MIL-C-85285B 36375 TYPE II

MSDS Prepared Date: 04/30/1993

Review Date: 06/10/1995

MFN: 2

Tech Entry NOS Shipping Nm: METHYL ISOBUTYL KETONE, ETHYL-3-ETHOXYPROPRIONATE

Net Unit Weight: UNKNOWN

Multiple KIT

Number: 0

Kit Part IND: Y

Review IND: Y

Unit Of Issue: KT

Container QTY: 0

Type Of Container: UNKNOWN

Additional Data: PART B OF 2 PART KIT. KIT WILL MAKE 2 QUARTS OF COATING WHEN MIXED.

=====
Detail DOT Information
=====

DOT PSN Code: LFD

DOT Proper Shipping Name: PAINT

DOT PSN Modifier: INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS, VARNISH, POLISH, LIQUID FILLER, AND LIQUID LA

CQUER BASE
Hazard Class: 3
UN ID Num: UN1263
DOT Packaging Group: II
Label: FLAMMABLE LIQUID
Special Provision: B52,T7,T30
Packaging Exception: 150
Non Bulk Pack: 173
Bulk Pack: 242
Max Qty Pass: 5 L
Max Qty Cargo: 60 L
Vessel Stow Req: B

=====
Detail IMO Information
=====

IMO PSN Code: LCP
IMO Proper Shipping Name: PAINT OR PAINT RELATED MATERIAL
IMO PSN Modifier: (INCLUDING PAINT, LACQUER, ENAM
EL, STAIN, SHELLAC SOLUTIONS,
VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING PAINT
THINNING OR REDUCING COMPOUND) o
IMDG Page Number: 3268
UN Number: 1263
UN Hazard Class: 3.2
IMO Packaging Group: I/II *
Subsidiary Risk Label: -
EMS Number: 3-05
MED First Aid Guide NUM: 310

=====
Detail IATA Information
=====

IATA PSN Code: SXI
IATA UN ID Num: 1263
IATA Proper Shipping
Name: PAINT
IATA PSN Modifier: (INCLUDING
PAINT,LACQUER,ENAMEL,STAIN,SHELLAC,VARNISH,POLISH,LIQUID FILLER AND LIQUID
LACQUER BASE)
IATA UN Class: 3
IATA Label: FLAMMABLE LIQUID
UN Packing Group: II
Packing Note Passenger: 305
Max Quant Pass: 5L
Max Quant Cargo: 60L
Packaging Note Cargo: 307
Exceptions: A7,A72

=====
Detail AFI Information
=====

AFI PSN Code: SXI
AFI Proper Shipping Name: PAINT

OR PAINT RELATED MATERIAL
AFI PSN Modifier: (INCLUDING PAINT,LACQUER,ENAMEL,STAIN,SHELLAC
SOLUTIONS,VARNISH,POLISH,LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING
PAINT THINNING OR REDUCING COMPOUNDS)

AFI Hazard Class: 3
AFI UN ID NUM: UN1263
AFI Packing Group: II
Special Provisions: P5
Back Pack Reference: A7.3

=====
HAZCOM Label
=====

Product ID: 04GY002CAT MIL-C-85285B 36375 TYPE II

Cage: 33461

Company Name: DEFT, INC.

Street: 17451 VON KARMAN AVE

City: IRVINE CA

Zipcode: 92614

Health Emergency Phone: 714-474-0400

Label Required IND: Y

Date Of Label Review: 06/09/1995

Status Code: C

Label Date: 06/09/1995

Origination Code: F

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: DANGER

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: Slight

Fire Hazard: Severe

Reactivity Hazard: None

Hazard And Precautions: FLAMMABLE! INH

ALATION MAY CAUSE RESPIRATORY IRRITATION

& CNS DEPRESSION.CONTACT MAY CAUSE SKIN & EYE IRRITATION.INGESTION
MAY CAUSE GI TRACT IRRITATION;CORROSIVE ACTION IN MOUTH,STOMACH &
DIGESTIVE TR ACT.PROLONGED/REPEATED EXPOSURE MAY CAUSE SKIN DEFATTING,DRYING
& IRRITATION.MAY CAUSE LIVER/KIDNEY DAMAGE. TARGET
ORGANS:LUNGS,LIVER,KIDNEYS,EYES,SKIN. FIRST AID:INHALED-MOVE TO FRESH
AIR.OBTAIN MEDI CAL ATTENTION.SKIN-REMOVE CONTAMINATED CLOTHES.WASH WITH SOAP
& WATER.EYES-FLU

SH WITH WATER FOR AT LEAST 15 MINUTES,LIFTING EYELIDS.GET
MEDICAL ATTENTION.INGESTED-DO NOT INDUCE VOMITING! NOTHING BY MO UTH IF
UNCONSCIOUS. OBTAIN MEDICAL ATTENTION.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said infor
mation to have any application, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to the
ir
particular situation regardless of similarity to a corresponding Department
of Defense or other government situation.