View NSN Online: https://aerobasegroup.ae/nsn/7930-01-381-3410 ELSCO INTERNATIONAL -- BLAST OFF RUST 55 GALLON DRUM, H-4 ______ MSDS Safety Information ______ FSC: 8030 NIIN: 01-381-3410 MSDS Date: 01/31/1994 MSDS Num: BXDQH Product ID: BLAST OFF RUST 55 GALLON DRUM, H-4 MFN: 01 Responsible Party Cage: 52790 Name: ELSCO INTERNATIONAL Address: 3407 E STREET City: SAN DIEGO CA 92102 Info Phone Number: 619-696-6609 Emergency Phone Number: 619-696-6609 Preparer's Name: W R MENYHERT Proprietary Ind: Y Published: Y ______ Contractor Summary _____ Cage: 52790 Name: ELSCO INTERNATIONAL Address: 3407 E ST City: SAN DIEGO CA 92102 Phone: 619-696-6609; -8609 (FAX) ______ Item Description Information _____ ______ Ingredients ______ Name: *** PROPRIETARY *** _____ Health Hazards Data ______ LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Skin: NO Ingestion: YES

Route Of Entry Inds - Inhalation: YES

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA:

Effects of Exposure: NAUSEA MAY OCCUR WHEN TAKEN INTERNALLY-NOT TOXIC. NAUSEA OR DIZZINESS MAY OCCUR BUT WOULD BE EXTREMELY RARE. COULD IRRITATE MUC MEMBS. WEAR OSHA/NIOSH/MSHA APPROVED FACE MASK IF EXPOSED TO MATL FOR LO NG PERIODS OF TIME. ALTHOUGH PROD IS INHIBITED & CORROSION CONTROLLED, PRLNGD EXPOS WILL CAUSE DRYING OF SKIN & STREET.

Explanation Of Carcinogenicity: NOT RELEVANT

Signs And Symptions Of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated By Exposure: C OULD CAUSE SLIGHT SKIN RASH IF

OVEREXPOSURE OCCURS. COULD CAUSE EYE DAMAGE BY EXTENDED CONTACT. First Aid: INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O*2/ARTF RESP) (FP N). EYES:IMMEDIATELY FLUSH W/POTABLE WATER FOR A MINIMUM OF 15 MINUTES, SEEK ASSISTANCE FROM MD (FP N). INGEST:DRINK COPIOUS AMOUN TS OF WATER. SKIN:USE REGULAR SOAP OR PLAIN WATER TO WASH MATERIAL OFF SKIN OR CLOTHING.

GET MEDICAL ATTENTION IF IRRITATION OR SYMPTOMS SEEM AGGRAVATED.

Handling and Disposal

Spill Release Procedures: ABSORB SPILLS WITH DRY SAND OR EARTH, THEN PLACE IN CHEMICAL WASTE CONTAINER FOR DISPOSAL. FLUSH RESIDUAL AREA WITH WATER.

Neutralizing Agent: WATER, SODA ASH OR OTHER ALKALINE PRODUCTS.

Waste Disposal Methods: DISPOSE OF ACCORDING TO LOCAL, STATE OR FEDERAL LAWS.
REMEMBER SOME STATES ABSOLUTELY FORBID ANYTHING EXCEPT RAINWATER TO GO INTO DRAINAGE SYSTEMS.

Han

dling And Storage Precautions: STORE IN PLASTIC, RUBBER LINED, OR 316 STAINLESS STEEL CONTAINERS. STORE AWAY FROM EXTREME HEAT. DO NOT GET IN EYES, ON SKIN OR CLOTHING.

Other Precautions: AVOID BREATHING MIST. KEEP CONTAINER CLOSED. KEEP OUT OF REACH OF CHILDREN. USE WITH ADEQUATE VENTILATION.

Fire and Explosion Hazard Information

Flash Point Method: OC Flash Point Text: NONE

Ex

tinguishing Media: MEDIA SUITABLE FOR SURROUNDING FIRE (FP N).

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & amp; FULL PROTECTIVE

EQUIPMENT (FP N).

Control Measures

Respiratory Protection: AVOID BREATHING MIST. IF PRODUCT IS BEING SPRAYED WEAR NIOSH/MSHA APPROVED MASK.

Ventilation: USE WITH ADEQUATE VENTILATION. Protective Gloves: NIOSH/MSHA OR RECOMMENDED.

Eye Protecti

on: ANSI APPROVED CHEM WORKERS GOGGS (FP N). Other Protective Equipment: IF SPRAYING IN WINDY SITUATION WEAR CHEMICAL RESISTANT CLOTHING. Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health: SPEC GRAV:1.11/12.05 BE' (H*2O=1). ______ Physical/Chemical Properties _____ B.P. Text: 270F,132C M.P/F.P Text: 25.0F,-3.9C Vapor Pres: 850 MM/HG Spec Gravity: SUPP DATA Ρ H: 1.8 Evaporation Rate & Evaporation R Solubility in Water: 99.8% BY WEIGHT Appearance and Odor: PURPLE & VISCOUS, LILAC ODOR. ______ Reactivity Data Stability Indicator: YES Materials To Avoid: ALKALINE, SULFIDES AND SULFIDE PRODUCTS. Hazardous Decomposition Products: NONE. Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: NOT RELEVANT _____ _____ Toxicological Information _____ _____ **Ecological Information** _____ _____ MSDS Transport Information _____ _____ Regulatory Information _____ _____ -----Other Information ______ ______ Transportation Information ______ Responsible Party Cage: 52790 Trans ID NO: 131824 Product ID: BLAST OFF RUST 55 GALLON DRUM, H-4 MSDS Prepared Date: 01/31/1994 Review Date: 09/11/1995 MFN: 1 Multiple KIT Number: 0

Review IND

: Y

Detail DOT Information

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail IMO Information

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: BLAST OFF RUST 55 GALLON DRUM, H-4

Cage: 52790

Company Name: ELSCO INTERNATIONAL

Street: 3407 E ST City: SAN DIEGO CA

Zipcode: 92102

Health Emergency Phone: 619-696-6609

Label Required IND: Y

Date Of Label Review: 04/05/1995

Status Code: C

Label Date: 04/05/1995
Origination Code: G
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: DANGER

Respiratory Protection IND: YES

Health Hazard: Moderate Contact Hazard: Severe

Fire Hazard: None

React

ivity Hazard: None

Hazard And Precautions: ACUTE:NAUSEA MAY OCCUR WHEN TAKEN INTERNALLY-NOT TOXIC.
NAUSEA OR DIZZINESS MAY OCCUR BUT WOULD BE EXTREMELY RARE. COULD IRRITATE THE
MUCOUS MEMBRANES. WEAR OSHA/NIOSH/MSHA APPROVED FACE MASK IF EXPOS ED TO
MATL

FOR LONG PERIODS OF TIME. ALTHOUGH PRODUCT IS INHIBITED & amp; CORROSION CONTROLLED, PROLONGED EXPOSURE WILL CAUSE DRYING OF SKIN AND IRRITATION. CHRONIC:NONE LISTED BY MANUFACTURER.

==

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclai

ms all liability for such use. Any person

utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.