View NSN Online: https://aerobasegroup.ae/nsn/6750-01-320-4327

Product ID:847 7184 KODAK EKTACOLOR RA DEVELOPER REPLENISHER RT, PART A MSDS Date:06/21/1995 FSC:6750 NIIN:01-320-4327 Kit Part:Y **MSDS Number: BXFVR** === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET **City:ROCHESTER** State:NY ZIP:14650 Country:US Info Phone Num:716-477-3194 MSDS: 800-242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

====

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 55-60% Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHANOL, 2,2',2"-NITRILOTRI-; (TRIETHANOLAMINE) CAS:102-71-6 RTECS #:KL9275000 Fraction by Wt: 20-25% Other REC Limits:NONE RECOMMENDED ACGIH TLV:5 MG/M3

Ingred Name:DIETHYLHYDROXYLAMINE CAS:3710-84-7 RTECS #:NC3500000 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:STILBENE SULFONIC ACID D ERIVATIVE (SUBSTITUTED STILBENE) CAS:82640-05-9 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM CHLORIDE CAS:7647-14-5 RTECS #:VZ4725000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN: LOW HAZARD FOR RECOMMENDED HANDLING. INGESTION: EXPECTED TO BE A LOW INGESTION HAZARD. Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY CLASSIFICATION:IARC/ACGIH/NTP/OSHA:NONE. Effects of Overexposure:MAY CAUSE TRANSIENT EYE IRRITATION. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:INHALATION: MOVE TO FRES

H AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION IF SYMPTONS PERSIST. EYES: ANY MATERIAL THAT CONTACTS EYE SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. GET MEDICAL ATTENTION.

Flash Point:200F,93C Extinguishing Media:WATER SPRAY, CARBON DIOXIDE (CO2), D RY CHEMICAL, ALCOHOL FOAM. Fire Fighting Procedures:WEAR SCBA AND PROTECTIVE CLOTHING. FIRE OR

EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. Unusual Fire/Explosion Hazard:CLASSIFIED AS COMBUSTIBLE. MATERIAL CONTAINS COMBUSTIBLE SOLVENT THAT MAY ACCUMULATE IN CONTAINER HEADSPACE. ELEVATED TEMPERATURE CAN CAUSE DECOMPOSITION.

Spill Release P

rocedures:ELIMINATE IGNITION SOURCES.NEUTRALIZE IF PH 12.5.FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.OTHERWISE,ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL.PLACE IN CONTAINER FOR CHEMICAL WAS TE.CLEAN SURFACE TO REMOVE RESIDUAL CONTAMINATION. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: USE WITH ADEQUATE VENTILATION. KEEP FROM CONTACT WITH OXIDIZING MATERIALS
KEEP AWAY FROM HEAT/FLAME. KEEP CONTAINER CLOSED. STORE IN COOL PLACE.
Other Precautions: MATL MODERATELY ALKALINE AQU SOLN; MAY CAUSE ADVERSE ENVRIO EFFECTS-HAS NOT BEEN TESTED FOR SUCH.LOW BIOCHEM OXY DEMAND, LITTLE POT TO CAUSE OXY DEPLETION IN AQU SYS; LOW POT TO AFFECT AQU ORGANISMS & 2N D WASTE TREATMENT MICROBIAL (SUPPLEMENT)

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: PER MFG'S MSDS NONE SHOULD BE NEEDED; HOWEVER, IF COND

ITIONS EXCEEDS TLV USE NOISH-APPROVED RESPIRATOR/CARTRIDGES. Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS Protective Gloves: IMPERVIOUS GLOVES. Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES Other Protective Equipment: PROTECTIVE CLOTHING APPROPRIATE FOR EXPO RISK. EYEBATH, WASHING FACILITIES, SAFETY SHOWER. Work Hygienic Practices: WASH THORO AFT HANDLING. FOLLOW GOOD INDUSTRIAL **HYGIENE PRAC** T INCLUDING PREVENTING EYE CONTACT/MIN SKIN CONTACT/INHAL. Supplemental Safety and Health KEY1:F8. THIS ENTRY DESCRIBES PART A OF A THREE PART KIT. SEE THIS SAME NSN, P/N IND'S B, C, AND W, FOR PARTS B, C, AND WORKING SOLUTION DATA. OTHER PRECAUT: METABOLISM; MOD POT TO AFFECT GERMINATION &/ OR EARLY GROWTH OF PLANTS.AFT DILUTES W/LG WATER AMT/2ND WASTE TREATMENT MATL NOT EXPECTED TO CAUSE ADVERSE ENV EFFECTS. = HCC:V4 Boiling Pt:B.P. Text:>212F,>100C Decomp Temp:Decomp Text:356F,180C Vapor Pres:18MM @68F Vapor Density:0.6 Spec Gravity:1.06 pH:10.7 Solubility in Water:COMPLETE Appearance and Odor:YELLOW LIQUID. AMINE ODOR. Percent Volatiles by Volume:55-60

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:MATERIAL CAN DECOMPOSE ABOVE 356F(180C). AVOID TEMPERATURES ABOVE 80C(176F). Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:DISCHARGE/TREATMENT/DISPOSAL MAY BE SUBJECT TO NATIONAL/STATE/LOCAL LAWS. FLUSH TO SEWER W/LG AMTS OF WATER. CONTAINS NO CHEMICALS SUBJECT TO REPORTING REQMTS OF SEC 313/TIT III OF SARA/40CFR PART 372.

Disclaimer (provided with this information by the

compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.