

FARWEST PAINT MFG CO -- SPAR VARNISH -- 8010-00-168-8810

=====
Product Identification
=====

Product ID:SPAR VARNISH

MSDS Date:03/01/1995

FSC:8010

NIIN:00-168-8810

MSDS Number: BXGXT

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-941-1619

CAGE:6F266

=== Contractor Ident

ification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS 350

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 47%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:DOWANOL EP SOLVENT

CAS:2807-30-9

RTECS #:KM2800000

Fraction by Wt: 7%

Other REC Limits:NONE RECOMMEN

DED
OSHA PEL:NONE
ACGIH TLV:NONE

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:103F,39C
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:FOAM,CRY CHEM,WATER FOG,CO2.USE CLASS B
EXTINGUISHING AGENT.WATER UNSUITABLE EXTINGUISHING AGENT,USE TO
COOL CONTAINERS.
Fire Fighting Procedures:FIREFIGHTERS & OTHERS EXPOSED TO VAPORS OR
PRODUCTS OF COMBUSTION SHOULD WEAR SCBA. EVACUATE AREA OF
UNPROTECTED PERSONNEL. WEAR PROTECT
IVE CLOTHING.
Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN
AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHT, ETC. CLOSED
CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:282 TO 387F
Vapor Pres:6.0 @ 68F
Vapor Density:> AIR
VOC Pounds/Gallon:499
Evaporation Rate &
; Reference:SLOWER THAN ETHER
Solubility in Water:NIL
Appearance and Odor:CLEAR LIQUID, MILD ODOR
Percent Volatiles by Volume:63

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES, AND EPOXY HARDENERS
UNDER UNCONTROLLED CONDITIONS.
Stability Condition to Avoid:HEAT, SPARKS, & OPEN FLAMES. IF PRODUCT
CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINER WILL GENERATE
HYDROGEN GAS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.