

LHB INDUSTRIES -- ECO SURE, YELLOW, 13538 (0674-130), 0672D830

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 01-331-6115
MSDS Date: 04/28/1995
MSDS Num: BXHCC
Product ID: ECO SURE, YELLOW, 13538 (0674-130), 0672D830
MFN: 03
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City:
SAINT LOUIS MO 63134
Info Phone Number: 314-522-3141
Emergency Phone Number: 314-522-3141 OR 800-424-9300
Preparer's Name: GREGORY K. MCGOWAN
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

=====
Contractor Summary
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ENAMEL
Specification Number: A-A-2787
Type/Grade/Class: TYPE I
Unit of Issue: PT
UI Container Qty: 0
Type of Container: METAL
=====

Ingredients

Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE (SARA 313) (CERCLA)
% Wt: <21.00
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 74-98-6
RTECS #: TX2275000
Name: PROPANE
% Wt: 14.86
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 1000 PPM
ACGIH TLV: 1000 PPM

Cas: 115-10-6
RTECS #: PM4780000
Name
: DIMETHYL ETHER
% Wt: 8.25
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 110-12-3
RTECS #: MP3850000
Name: 5-METHYL-2-HEXANONE
% Wt: 5.88
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 50 PPM
ACGIH TLV: 50 PPM

Cas: 64742-95-6
RTECS #: ZE2190000
Name: AROMATIC 100
% Wt: 5.88
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 50 PPM

Cas: 64

742-95-6
RTECS #: ZE2190000
Name: AROMATIC 150
% Wt: <2.94
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 5 PPM

Cas: 107-87-9
RTECS #: SA7875000
Name: 2-PENTANONE
% Wt: <2.94
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 200 PPM
ACGIH TLV: 200 PPM

Cas: 108-10-1
RTECS #: SA9275000
Name: 4-METHYL-2-PENTANONE
% Wt: <2.94
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 50 PPM
EPA Rpt Qty: 5
000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 95-63-6
RTECS #: DC3325000
Name: 1,2,4-TRIMETHYLBENZENE (SARA 313)
% Wt: <2.94
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 25 PPM

Cas: 71-36-3
RTECS #: EO1400000
Name: N-BUTANOL (SARA 313) (CERCLA)
% Wt: <2.94
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 50 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS
=====

=====

Health Hazards Data

=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. IN CONFINED AREAS VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITATION TO SKIN, EYES, THROAT AND RESPIRATORY TRACT. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.

Signs A

nd Symptoms Of Overexposure: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE MAY RESULT IN LIGHT HEADEDNESS, STAGGERING GAIT, GIDDI NESS AND POSSIBLE NAUSEA.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS.

First Aid: SKIN OR CLOTHES: WASH WITH SOAP AND WATER. WASH CLOTHES BEFORE REUSE. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONTACT PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUC

E VOMITING. GET IMMEDIATE MEDICAL AID . NEVER GIVE

ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. INHALATION: REMOVE TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION IF NECESSARY. GET MEDICAL AID.

=====

Handling and Disposal

=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA. MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE OF I

N ACCORD W/APPLICABLE FEDERAL, STATE &

LOCAL REGS. DON'T PUNCTURE, INCINERATE (BURN) OR STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TOBURST. DISCARD EMPTY CAN IN TRASH PICK-UP. DO NOT PLACE IN COMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER PRESSURE. DON'T STORE WHERE TEMPS >120F/48.9C. AVOID BREATH SPRAY, MIST, VAPOR. AVOID SKIN & EYE CONTACT

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION.

READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING OR SWALLOWING CO NTENTS MAY BE HARMFUL.

=====

Fire and Explosion Hazard Information

=====

Autoignition Temp Text: 662F

Lower Limits: 2.2%

Upper Limits: 18.0%

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. AVOID SPR

EADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE. USE TO KEEP FIRE EXPOSED
CNTNRS COOL. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING,
RUPTURING, VENTING OF CONTAINERS

Unusual Fire/Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPS
(ABOVE 120F) CONTAINERS MAY VENT, RUPTURE, BURST. AEROSOL CONTAINER. DO NOT
EXPOSE TO TEMPERATURE ABOVE 120F.

=====
Control Measures

=====
Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.
Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT
POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: TO PROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH
STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK OR SMOKE
WHILE USING
PRODUCT.

=====
Physical/Chemical Properties

HCC: V3

Vapor Pres: 70 @ 68F

Vapor Density: >1.522

Volatile Org Content %: 65

Spec Gravity: 1.057

Solubility in Water: INSOLUBLE

Appearance and Odor: YELLOW/PAINT

=====
Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid:
EXTREME HEAT

Hazardous Decomposition Products: CARBON MONOXIDE

Hazardous Polymerization Indicator: NO

=====
Toxicological Information

=====
Ecological Information

=====
MSDS Transport Information

=====
=====
Regulatory Information
=====
=====

Other Information
=====
=====

Other Information: VOC: 65%; 571 G/L
=====
=====

Transportation Information
=====
=====

Responsible Party Code: 0FTT5

Trans ID

NO: 126067

Product ID: ECO SURE, YELLOW, 13538 (0674-130), 0672D830

MSDS Prepared Date: 04/28/1995

Review Date: 06/15/1995

MFN: 3

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: PT

Container QTY: 0

Type Of Container: METAL
=====
=====

Detail DOT Information
=====
=====

DOT PSN Code: DTJ

Symbols: D

DOT Proper Shipping Name: CONSUMER COMMODITY

Hazard Class: ORM-D

Label: NONE

Non Bulk Pack: 156,306

Bulk Pa

ck: NONE

Max Qty Pass: 30KGGROSS

Max Qty Cargo: 30KGGROSS

Vessel Stow Req: A
=====
=====

Detail IMO Information
=====
=====

IMO PSN Code: AKH

IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?

IMDG Page Number: SEE 9022

UN Number: 1950

UN Hazard Class: 9?

IMO Packaging Group: -

Subsidiary Risk Label: -

EMS Number: 2-13
=====
=====

Detail IATA Information
=====
=====

=====
IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG
Max Quant Cargo: 150KG
Packaging Note Cargo: 203
=====

=====
Detail AFI Information
=====

AFI PSN Code: ALR
AFI Symbols: *

AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3
=====

=====
HAZCOM Label
=====

Product ID: ECO SURE, YELLOW, 13538 (0674-130), 0672D830
Cage: 0FTT5
Company Name: LHB INDUSTRIES
Street: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
Zipcode: 63134
Health Emergen
cy Phone: 800-424-9300 CHEMTREC/ 314-522-3141
Label Required IND: Y
Date Of Label Review: 12/16/1998
Status Code: C
Label Date: 12/16/1998
Origination Code: G
Hazard And Precautions: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND
INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. IN CONFINED AREAS VAPORS IN
HIGH CONCENTRATION ARE ANESTHETIC. IRRITATION TO SKIN, EYES, THROAT AND
RESPIRATORY TRACT. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.
REPORTS HAVE ASSOCIATED REPEA

TED

AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLV ENTS WITH PERMANENT BRAIN AND

NERVOUS SYSTEM DAMAGE. OVEREXPOSURE MAY RESULT INLIGHT HEADEDNESS, STAGGERING

GAIT, GIDDINESS AND POSSIBLE NAUSEA.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.