View NSN Online: https://aerobasegroup.com/nsn/8010-01-397-3790

Product ID:WATER MASTER LOW VOC STAIN, HONEY STAIN, LF#RP2-57B MSDS Date:10/04/1993 FSC:8010 NIIN:01-397-3790 **MSDS Number: BXHHK** === Responsible Party === Company Name: ALTERNATIVE MATERIALS TECHNOLOGY, INC Address:1266 HUMBOLDT AVENUE City:CHICO State :CA ZIP:95928 Country:US Info Phone Num:916-894-3585 Emergency Phone Num:916-894-3585 CAGE:0ZXD0 === Contractor Identification === Company Name: ALTERNATIVE MATERIALS TECHNOLOGY, INC Address:1266 HUMBOLDT AVENUE City:CHICO State:CA ZIP:95928 Country:US Phone:916-894-3585 CAGE:0ZXD0 Ingred Name: MINERAL SPIRITS (NIOSH RECOMMENDS A LIMIT OF 350 MG/M3 - 8 HOURS TWA) CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 45-55% Other

REC Limits:NOSH350 MG/M3 8HRTWA OSHA PEL:100 PPM ACGIH TLV:100 PPM

Ingred Name:VOLATILE ORGANIC CONTENT (VOC): 535.8 GRAMS/LITER MINUS WATER. 4.47 POUNDS/GALLON MINUS WATER. RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED

Ingred Name:TOTAL VOLATILE EMISSIONS: 4.47 POUNDS/GALLON. 535.8 GRAMS/LITER. RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED

Flash Point Method:CC Flash Point:111F,44C Lower Limits:1.0

Exti

nguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR ANY CLASS B EXTINGUISHING AGENT. WATER UNSUITABLE, MAY BE USED TO COOL CONTAINERS.

Fire Fighting Procedures: FIREFIGHTERS & OTHER EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: VAPORS MAY FORM AT EXPLOSIVE MIXTURE IN AIR. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT. RAGS, STEEL WOOL & OTHER MATERIAL OR WASTE SOAKED *

Supplemental Safety and Health

Boiling Pt:B.P. Text:315F,157C Vapor Pres:2.0 Vapor Density: