

ALTERNATIVE MATERIALS TECHNOLOGY, INC -- WATER MASTER, LOW VOC STAIN, LF#93,  
MEDIUM OAK -- 8010-01-397-3791

===== Product Identification =====

Product ID:WATER MASTER, LOW VOC STAIN, LF#93, MEDIUM OAK

MSDS Date:11/02/1994

FSC:8010

NIIN:01-397-3791

MSDS Number: BXHHL

=== Responsible Party ===

Company Name:ALTERNATIVE MATERIALS TECHNOLOGY, INC

Address:1266 HUMBOLDT AVENUE

City:CHICO

State:CA

ZIP:95

928

Country:US

Info Phone Num:916-894-3585

Emergency Phone Num:916-894-3585

CAGE:0ZXD0

=== Contractor Identification ===

Company Name:ALTERNATIVE MATERIALS TECHNOLOGY, INC

Address:1266 HUMBOLDT AVENUE

City:CHICO

State:CA

ZIP:95928

Country:US

Phone:916-894-3585

CAGE:0ZXD0

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS (NIOSH RECOMMENDS A LIMIT OF 350 MG/M3 - 8  
HOUR TWA)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 46.27%

Other REC Limits:

NOSH350MG/CUM 8HRTWA  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

Ingred Name:ETHYLENE GLYCOL MONO-2-ETHYLHEXYL ETHER  
CAS:1559-35-9  
RTECS #:KK9625000  
Fraction by Wt: 1%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:EXXATE 600  
CAS:88230-35-7  
Fraction by Wt: 1.93%  
Other REC Limits:50 PPM - 8 HR TWA

Ingred Name:VOLATILE ORGANIC CONTENT (VOC): 496.18 GRAMS/LITER MINUS  
WATER. 4.13 POUNDS/GALLON MINUS WATER.  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED

Ingred Name:TOTAL VOLATILE EMISSIONS: 4.13 P  
OUND/GALLON. 496.18  
GRAMS/LITER.  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED

===== Fire Fighting Measures =====

Flash Point Method:CC  
Flash Point:105F,41C  
Lower Limits:1.0  
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE,OR ANY CLASS B  
EXTINGUISHING AGENT.WATER UNSUITABLE EXTINGUISHER,USE TO COOL  
CONTAINER.  
Fire Fighting Procedures:FIREFIGHTERS & OTHER EXPOSED TO VAPORS OR  
PRODUCTS OF COMBUSTION SHOULD WEAR SELF-CONTAINED BREATHING  
APPARATUS.  
Unusual Fire/Explosion Hazard:VAPOR FORM EXPLOSIVE MIX IN AIR.CLSD  
CNTNRS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.RAGS,STEEL WOOL &  
OTHER MATERIALS OR WASTE SOAKED W/OIL FINISHES MAY \*

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:315F,157C  
Vapor Pres:2.0  
Vapor Density: