

ITW DEVCON/ A DYKEM COMPANY -- TOLE RED DX-296,B-I-C-81496 -- 6850-01-013-9937
===== Product Identification =====

Product ID:TOLE RED DX-296,B-I-C-81496
MSDS Date:06/01/1994
FSC:6850
NIIN:01-013-9937
MSDS Number: BXPVM
=== Responsible Party ===
Company Name:ITW DEVCON/ A DYKEM COMPANY
Address:8501 DELPORT DRIVE
City:ST. LOUIS
State:MO
ZIP:63114
Country:US
Info Phone Num:314-423-0100/800-443-9536
E
mergency Phone Num:800-443-9536/800-424-9300(CHEMTREC)
Preparer's Name:JAMES A SEPER
CAGE:98148
=== Contractor Identification ===
Company Name:ITW DYKEM/ DYMON
Address:805 E OLD 56 HWY
Box:City:OLATHE
State:KS
ZIP:66061
Country:US
Phone:800-443-9536
CAGE:98148

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 31 - 50%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9495

Ingred Name:N-BUTYL ACETATE (CERCLA)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 31 - 50%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:150 PPM
ACGIH TLV:150 PPM/200STEL;9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 1 - 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM
ACGIH TLV:400 PPM/500STEL;9495

Ingred Name:COLLODION (WET NITROCELLULOSE)
CAS:9004-70-0
RTECS #:QW0970000
Fraction by Wt: 1 - 5%
Other
REC Limits:NONE RECOMMENDED

Ingred Name:N-BUTYL ALCOHOL (SARA 313) (CERCLA)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 1 - 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)
CAS:123-42-2
RTECS #:SA9100000
Fraction by Wt: 1 - 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:50 PPM; 9495

Ingred Name:N-PROPYL ACETATE
CAS:109-60-4
RTECS #:AJ36750

00

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM/250STEL;9495

Ingred Name:SOLVENT RED 125 (COBALT COMPOUND)

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYAMIDE RESIN

CAS:68410-23-1

Other REC Limits:NONE RECOMMENDED

Ingred Name:CASTOR OIL

CAS:8001-79-4

RTECS #:FI4100000

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLITILE ORGANIC CONTENT AS LISTED ON MSDS: 6.46 LBS/GAL.

RTECS #:9999999VC

Other REC Limits:NONE RECOMMEND

ED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS,

RESPIRATORY & GI TRACTS. ACUTE- MAY CAUSE EYE & SKIN IRRITATION.

INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION, CNS EFFECTS. MAY
BE ABSORBED THROU

GH SKIN. CAN CAUSE G I TRACT IRRITATION.

ASPIRATION HAZARD. CHRONIC- SKIN SENSITIZATION OR DERMATITIS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, IRRITATION,

REDNESS AND ITCHING OR BURNING SENSATION OF EYES OR SKIN, ABDOMINAL
PAIN, WEAKNESS, CONFUSION

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN

DISORDERS, EYE PROBLEMS OR IMPAIRED CNS OR RESPIRATORY FUNCTION MAY
BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PROD

NTILATION

CONDITIONS EXIST. IF AIRBORNE CONCENTRATION IS HIGH, WEAR A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NEOPRENE, NITRILE, POLYVINYL CHLORIDE

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER, INDUSTRIAL-TYPE WORK CLOTHING, APRON AND BARRIER CREAM FOR EXPOSED SKIN

Work Hy

gienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATIONS, SEE PNI A AND B, SAME NSN.

===== Physical/Chemical Properties =====

HCC:F2

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:163F - 275F

Vapor Density:>1

Spec Gravity:0.84

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in Water:APPRE

CIABLE

Appearance and Odor:RED TRANSPARENT LOW VISCOUSITY LIQUID WITH SWEET SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, AND SMOKE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE

OF IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. INCINERATE IN
APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing
this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.