View NSN Online: https://aerobasegroup.com/nsn/9350-00-153-6811

DRESSER INDUSTRIES INC -- H-W 5-5 BONDING MORTAR -- 9350-00-153-6811

Product ID:H-W 5-5 BONDING MORTAR MSDS Date:03/29/1993 FSC:9350 NIIN:00-153-6811 MSDS Number: BXTMJ === Responsible Party === Company Name: DRESSER INDUSTRIES INC Address: ONE GATEWAY CENTER City:PITTSBURGH State:PA ZIP:15222-1416 Country:US Info Phone Num:412-367-3444 Emergency Phone Num:412-367 -3444 Preparer's Name:S. W. THROWER CAGE:73064 === Contractor Identification === Company Name: DRESSER INDUSTRIES INC Address: ONE GATEWAY CENTER Box:City:PITTSBURGH State:PA ZIP:15222-1416 Country:US Phone:412-367-3444 CAGE:73064 

Ingred Name:QUARTZ CAS:14808-60-7 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED

Ingred Name:CRISTOBALITE CAS:14464-46-1 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED

Ingred Name:

ALUMINA (AS DUST) CAS:1344-28-1 Fraction by Wt: 51-53% Other REC Limits:NONE RECOMMENDED

Ingred Name:ALUMINUM SULFATE CAS:10043-01-3 RTECS #:BD1700000 Fraction by Wt: 5-6% Other REC Limits:NONE RECOMMENDED EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:IRRITANT TO SKIN, EYE, MUCOUS MEMB RANES. Explanation of Carcinogenicity:NONE

Effects of Overexposure: IRRITANT TO SKIN, EYE, MUCOUS MEMBRANES. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:IRRITANTS: WASH FROM SKIN OR FLUSH FROM EYES USING LARGE AMOUNTS OF WATER.

Extinguishing Media:PRODUCT IS A REFRACTORY AND WILL NOT BURN. Fire Fighting Procedures:UNLES S OTHERWISE NOTED, NO FIRE HAZARD. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:NONE SPECIFIED BY MANUFACTURER. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER. Other Precautions:THIS PRODUCT CONTAINS CRYSTALLINE SILICA FOR WHICH THERE IS LIMITED EVIDENCE OF A POSSIBLE ASSO CIATION WITH THE INCIDENCE OF CANCER IN HUMANS.

Respiratory Protection:WHERE AIR CONTAMINANTS CAN EXCEED ACCEPTABLE CRITERIA, USE APPROVED RESPIRATORY PROTECTION EQUIPMENT APPROPIATE TO FORM AND CONCENTRATIONS OF AIR CONTAMINANTS.
Ventilation:LOCAL EXHAUST VENTILATION SHOULD BE PROVIDED IF ROUTINE OPERATION GENERATES DUST IN EXCESS OF ALLOWABLE LIMITS.
Protective Gloves:IMPERMEABLE.
Eye Protection:APPROVED SAFE
TY GLASSES, GOGGLES, SHIELD
Other Protective Equipment:METATARSAL SAFETY SHOES.
Work Hygienic Practices:WASH AFTER HANDLING.
Supplemental Safety and Health NONE.

HCC:N1 Spec Gravity:1.60 Solubility in Water:SLIGHT Appearance and Odor:BUFF TO TAN COLOR. EARTHY ODOR. GRANULAR FORM.

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Sta

bility Condition to Avoid:STORE IN DRY LOCATION PRIOR TO USE.

Waste Disposal Methods:MOST REFRACTORY PRODUCTS MAY BE LANDFILLED. HOWEVER, SINCE YOUR APPLICATION OF THIS PRODUCT MAY CHANGE ITS CHEMICAL CHARACTERISTICS, & SINCE DISPOSAL PROCEDURES MAY VARY WITHIN LOCALE, CONSULT GOVERNM ENT AUTHORITY HAVING JURISDICTION FOR DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This i

nformation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.