

GERARD PACKING AND BELTING CORP -- COMPRESSED RUBBER-BONDED ASBESTOS GASKET SHEET,S 76 -- 5330-00-527-9898

===== Product Identification =====

Product ID:COMPRESSED RUBBER-BONDED ASBESTOS GASKET SHEET,S 76

MSDS Date:02/01/1991

FSC:5330

NIIN:00-527-9898

MSDS Number: BXTMQ

=== Responsible Party ===

Company Name:GERARD PACKING AND BELTING CORP

Address:24 MIDLAND AVENUE

City:HICKSVILLE

State:NY

ZIP:118

01

Country:US

Info Phone Num:516-935-2400

Emergency Phone Num:516-935-2400

CAGE:2G277

=== Contractor Identification ===

Company Name:GERARD PACKING AND BELTING CORP

Address:24 MIDLAND AVENUE

Box:City:HICKSVILLE

State:NY

ZIP:11801

Country:US

Phone:516-935-2400

CAGE:2G277

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Fraction by Wt: 60 - 90%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:

2 FIBERS/CC,A1; 9495

Ingred Name:RUBBER BINDER (NEOPRENE)

Fraction by Wt: TLV.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED OR FOR SYMPTOMS OF OVER EXPOSURE, WEAR NIOSH-APPROVED RESPIRATOR FOR DUST OR AIR-PURIFYING RESPIRATOR. IN EMERGENCY, WEAR A NIOSH-APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS.

Protective Gloves:L  
ATEX OR RUBBER RECOMMENDED

Eye Protection:GOGGLES

Other Protective Equipment:EYE WASH STATION; FULL BODY PROTECTION IF ABOVE TLV

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

NOTE: THE ASBESTOS AND OTHER FIBERS CONTAINED IN THIS MATERIAL ARE BONDED WITH A VULCANIZED RUBBER MATRIX. AIRBORNE ASBESTOS HAZARDS ARE ELIMINATED IF THE COMPOSITE STRUCTURE REMAINS INTACT. IF MATERIAL IS TO BE CUT OR DRILLED,

USE ADEQUATE EXHAUST VENTILATION AND WEAR RESPIRATORY PROTECTION.

=====  
===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NOT RELEVANT

Spec Gravity:1.8 - 2.2

Viscosity:NOT RELEVANT

Evaporation Rate & Reference:NOT RELEVANT

Solubility in Water:INSOLUBLE

Appearance and Odor:BLACK OR WHITE SHEET MATERIAL - ODORLESS

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to

Avoid: CREATION OF DUST OR ASBESTOS FIBERS.

Hazardous Decomposition Products: EMITS TOXIC RUBBER COMBUSTION PRODUCTS. ASBESTOS FIBERS MAY BE RELEASED.

===== Disposal Considerations =====

Waste Disposal Methods: PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. BURY WASTE IN SOLID LANDFILL IF PERMITTED. WASTE SHOULD BE IN SEALED CONTAINER, MARKED WITH WARNING LABEL. MAY BE INCINERATED. OBSERVE ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Dis

claimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.