

EASTMAN KODAK COMPANY -- 803 6832 EKTACOLOR RA BLEACH FIX ADDITIVE --
6750-01-329-6488

=====
Product Identification
=====

Product ID:803 6832 EKTACOLOR RA BLEACH FIX ADDITIVE

MSDS Date:10/17/1997

FSC:6750

NIIN:01-329-6488

MSDS Number: BXTNJ

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194

MSDS: 800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====
Composition/Information on Ingredients
=====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 55-60%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SULFITE

CAS:10117-38-1

RTECS #:WT3530000
Fraction by Wt: 45-50%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION-EXPECTED TO BE A LOW HAZARD
FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL.
EYES-CAUSES IRRITATION. SKIN-CAUSES IRRITATION.
INGESTION-MAY BE HARMFUL IF SWALLOWED. MAY CAUSE IRRITATION OF THE GASTROINTESTINAL
TRACT.
Explanation of Carcinogenicity:IN ADDITION TO THE ABOVE, PRODUCT IS
NEGATIVE W/REGARD TO:ACGIH CANCER, CALIFORNIA CANCER & REPRODUCTIVE
EFFECTS.
Effects of Overexposure:INGESTION-SOME ASTHMATICS OR SULFUR-SENSITIVE
INDIVIDUALS MAY EXPERIENCE WHEEZING, CHEST TIGHTNESS, STOMACH
UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA.
Medical Cond Aggravated by Exposure:SULFUR DIOXIDE GAS
IS IRRITATING TO THE RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE
INDIVIDUALS MAY EXPERIENCE BREATHING DIFFICULTY.

===== First Aid Measures =====

First Aid:IF ANY SYMPTOMS OCCUR, GET IMMEDIATE MEDICAL ATTENTION.
INHALATION:IF SYMPTOMATIC,MOVE TO FRESH AIR. EYE:FLUSH W/PLENTHY OF
WATER FOR 15 MIN. SKIN:WASH W/SOAP & WATER. INGESTION:DRINK 1-2
GLASSES OF WATER. GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting
Measures =====

Flash Point:NONE
Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS &
PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS
DECOMPOSITION PRODUCTS
Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNT OF WATER.
CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CO

NTAMINATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES (STRONG ACIDS).

Other Precautions:USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:USE GOOD GENERAL VENTILATION (10 CHANGES/HR). MATCH

VENTILATION RATES TO CONDITIONS.

Protective Gloves:WEAR IMPERVIOUS GLOVES

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:EYE BATH, WASHING FACILITIES, SAFETY SHOWER. PROTECTIVE CLOTHING APPROPRIATE FOR THE RISK OF EXPOSURE.

Work Hygienic Practices:FOLLOW GOOD INDUSTRIAL HYGIENE PRACTICE WHICH INCLUDES PREVENTING EYE CONTACT & MINIMIZING SKIN CONTACT & INHALATION.

Supplemental Safety and Health

KAN 347367; PCD 10749; P-0006.500

==
===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18 MM

Vapor Density:0.6

Spec Gravity:1.46

pH:9.2

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID, ODORLESS

Percent Volatiles by Volume:55-60

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS

Hazardous Decomposition Products:SULFUR DIOXIDE

Conditions to Avoid Polym

erization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER W/LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.