

EASTMAN KODAK COMPANY -- 106 5275 EKTACHROME R-3000 COLOR DEVELOPER, PART C --
6750-01-273-8178

===== Product Identification =====

Product ID:106 5275 EKTACHROME R-3000 COLOR DEVELOPER, PART C

MSDS Date:10/25/1995

FSC:6750

NIIN:01-273-8178

Kit Part:Y

MSDS Number: BXXMG

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS: 800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Compositi

on/Information on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 90-95%
Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROXYLAMINE SULFATE
CAS:10039-54-0
RTECS #:NC5425000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PENTETIC ACID, PENTA SODIUM SALT
CAS:140-01-2
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SULFURIC ACID (SARA 302/313) (CERCLA)
CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 2%
Other RE
C Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3/3 STEL; 9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:(NITRILOTRIS(METHYLENE)TRIPHOSPHONIC ACID, POTASSIUM SALT
CAS:2235-43-0
Fraction by Wt: 230F,>110C
Vapor Pres:18 MM
Vapor Density:0.6
Spec Gravity:1.12
pH:3
Solubility in Water:COMPLETE
Appearance and Odor:LIQUID, COLOR, ODORLESS.
Percent Volatiles by Volume:85-90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avo

id:YES

NON WITH COMMON MATERIALS & CONTAMINANTS W/WHICH THE MATERIAL MAY REASONABLY COME IN CONTACT.

Stability Condition to Avoid:HOWEVER, MATERIAL CAN DECOMPOSE ABOVE 110C (230F). AVOID TEMPERATURES ABOVE ROOM TEMPERATURE.

Hazardous Decomposition Products:NONE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS
. FLUSH TO SEWER W/LARGE AMOUNTS OF WATER. SINCE 'EMPTY' CONTAINERS RETAIN PRODUCT RESIDUES, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing thi

s
document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.