

DEL PAINT CORP. -- F0201 -- 8010-00-598-5932

===== Product Identification =====

Product ID:F0201
MSDS Date:08/30/1993
FSC:8010
NIIN:00-598-5932
MSDS Number: BYCLW
=== Responsible Party ===
Company Name:DEL PAINT CORP.
Address:3105 E. RENO
City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Info Phone Num:405-672-1431/FAX 405-672-0804
Emergency Phone Num:800-424-9300 24 HRS
Preparer's Name:ONEY FLEMIN

G

CAGE:JO954
=== Contractor Identification ===
Company Name:DEL PAINT CORP.

Address:3105 E. RENO
City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Phone:405-672-1431/FAX 405-672-0804

CAGE:JO954
Company Name:DEL PAINT MFG
Address:3105 EAST RENO
Box:City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Phone:405-672-1431
CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM (COAL OIL)
CAS:8002-05-9
RTECS #:SE7175000
Fraction by Wt: 44.89%
Other REC Limit

s:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 0.33%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NONHAZARDOUS INGREDIENTS

Fraction by Wt: 54.78%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

Ingred Name:VOLATILE ORGANIC COMPOUNDS 3.25 LBS/GL, 390 G/LTR

RTECS #:9999999VO

Other REC L

imits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION, REDNESS, TEARING,
BLURRED VISION. SKIN: POSSIBLE IRRITATION, DEFATTING, DERMATITIS
W/PROLONGED/REPEATED EXPOSURE. INHALATION: NASAL/RESPIRATORY
IRRITATION, DIZZINESS, NAUSEA, HEADACH E. INGESTION:

POSSIBLE

GASTROINTESTINALIRRITATION, NAUSEA, VOMITING.

Effects of Overexposure:IF TLV'S EXCEEDED, SKIN CONTACT PRODUCES
REDNESS. EYES: REDNESS/PAIN. INHALATION: LABORED BREATHING,
DULLNESS, DROWSINESS. INGESTION: ABDOMINAL PAIN, NAUSEA.

Medical Cond Aggravated by Exposure:RESPIRATORY DISEASES.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMOUNT WATER 15 MINUTES OCCASIONALLY
LIFTING EYELIDS. GET MEDICAL AID. SKIN: REMOVE CONT

AMINATED

CLOTHING. WASH W/SOAP & WATER. INHALATION: GET FRESH AIR, GIVE OXYGEN IF NECESSARY. GET MEDICAL AID. INGESTION: KEEP WARM, QUIET. GET MEDICAL AID. DO NOT INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC

Flash Point:100F,38C

Lower Limits:1.1

Upper Limits:6.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM. WATER MAY SPREAD FIRE, USE WATER SPRAY ONLY TO COOL CONTAINERS EXPOSED TO FIRE.

Fire Fighting P

rocedures:SCBA (MSHA/NIOSH OR EQUIV.) & FULL PROTECTIVE

GEAR. PREVENT POSSIBLE PRESSURE BUILD-UP, AUTOIGNITION, EXPLOSION TO EXTREME HEAT BY COOLING W/WATER SPRAY.

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR. MAY TRAVEL & BE IGNITED BY PILET LIGHTS, OTHER FLAMES, SPARKS, HEATERS, SMOKING, OTHER REMOTE IGNITION SOURCES.

=====
Accidental Release Measures
=====

Spill Release Procedures:VENTILATE AREA. COVER SPILL W/INERT ABSORBENT MATERIAL

& SHOVEL W/NON-SPARKING TOOLS INTO CONTAINER. REMOVE CONTAINER TO SAFE AREA & SEAL.

Neutralizing Agent:NONE

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN CLEAN, DRY AREA. KEEP AWAY FROM SPARKS, FIRE, REMOTE IGNITION SOURCES.

Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM CHILDREN. ALL EQUIPMENT SHOULD BE GROUNDED TO REDUCE STATIC ELECTRICITY HAZARD. USE NONSPARKING TOOLS.

=====
Exposure

Controls/Personal Protection
=====

Respiratory Protection:IF TLV OF PRODUCT OR ANY COMPONENT EXCEEDED, USE RESPIRATOR W/APPROPRIATE CARTRIDGES (NIOSH APPROVED). ENGINEERING OR MANAGEMENT CONTROL SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

Ventilation:LOCAL EXHAUST MUST BE SUFFICIENT TO KEEP AIRBORNE VAPOR CONCENTRATION BELOW TLV.

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS.

Other Protective Equipment:CLEAN FLUSHING WATER SOURCE SUGGESTED.

IMPERVIOUS CLOTHING AS NEEDED.

Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:303F,151C
Melt/Freeze Pt:M.P/F.P Text:NA
Decomp Temp:Decomp Text:752F,400C
Vapor Pres:2.58
Vapor Density:>AIR
Spec Gravity:1.23
pH:NA
Viscosity:77-86KU
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NO
Appearance and Odor:OLIVE GREEN LIQUID W/SLIGHT ODOR
Percent Volatiles by Volume:45.97
Corrosion Rate:NA

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:DO NOT STORE NEAR HEATED SURFACES, OPEN
FLAMES, IGNITION SOURCES.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE, LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.