

INCO ALLOYS INTERNATIONAL INC -- MONEL W.E. 190N -- 3439-00-230-1706

=====
Product Identification
=====

Product ID:MONEL W.E. 190N

MSDS Date:12/01/1990

FSC:3439

NIIN:00-230-1706

MSDS Number: BYFFR

=== Responsible Party ===

Company Name:INCO ALLOYS INTERNATIONAL INC

Address:1401 BURRIS RD

City:NEWTON

State:NC

ZIP:28658-1754

Country:US

Info Phone Num:704-465-0356

Emergency Phone Num:704-465-0356

CAG

E:9Z762

=== Contractor Identification ===

Company Name:INCO ALLOYS INTERNATIONAL INC

Address:1401 BURRIS RD

Box:City:NEWTON

State:NC

ZIP:28658-1754

Country:US

Phone:800-624-3411

CAGE:9Z762

=====
Composition/Information on Ingredients
=====

Ingred Name:BARIUM CARBONATE

CAS:513-77-9

RTECS #:CQ8600000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG BA/M3

ACGIH TLV:2 MG BA/M3

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9495

Ingred Name:CALCIUM FLUORIDE (AS F)
CAS:7789-75-5
RTECS #:EW1760000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:COPPER (SARA 313) (CERCLA)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 15-40%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2 MG/M3 FUME; 9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:MANGANESE (SARA 313)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9495

Ingred Name:NICKEL (SARA 313) (CERCLA)
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 40-70%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9495

Ingred Name:SODIUM FLUORALUMINATE
CAS:15096-52-3
RTECS #:WA9625000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2.5 MG (F)/M3
ACGIH TLV:2.0 MG (AL)/M3

Ingred Name:SODIUM

SILICATE
CAS:1344-09-8
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICON DIOXIDE
CAS:14808-57-0
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TITANIUM
CAS:7440-32-6
RTECS #:XR1700000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9495

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHALATION OF WELDING FUMES MAY CAUSE NERVOUS SYSTEM AND MUSCLE IRREGULARITIES, IRRITATION OF EYES, NOSE, THROAT, AND RESPIRATORY SYSTEM, METAL FUME FEVER. CHRONIC: INHALATION OF FUMES MAY CAUSE CANCER, FLUOROSIS AND AFFECT LUNG FUNCTION.

Explanation of Carcinogenicity:CONTAINS NICKEL WHICH IS LISTED BY BOTH IARC AND NTP.

Effects of Overexposure:INHALATION: NAUSEA, DIZZINESS, DRYNESS OF NOSE AND THROAT, COUGHING, WHEEZING AND SHORTNESS OF BREATH. EYES: REDNESS, TEARING, BLURRED VISION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NEEDED. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER.

D WATER. INGESTION: DO NOT INDUCE VOMITING. SEE DOCTOR.

=====
Fire Fighting Measures
=====

Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:NON-FLAMMABLE; BUT SPARKS AND WELDING ARC MAY IGNITE COMBUSTIBLES DURING USE.

=====
Accidental Release Measures
=====

Spill Release Procedures:PICK UP

RODS. SWEEP UP OR MOP. PLACE RESIDUE

IN A CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:REMOVE ANY COMBUSTIBLES FROM WORK AREA: SPARKS OR WELDING ARC COULD IGNITE NEARBY COMBUSTIBLES.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR OR FOR WELDING

FUMES OR SUPPLIED AIR RESPIRATOR IN CONFINED SPACES OR WHERE FUME CONCENTRATION EXCEEDS REGULATORY LIMITS.

Ventilation:USE MECHANICAL OR LOCAL EXHAUST OR BOTH TO MAINTAIN LEVELS OF FUMES BELOW REGULATORY LIMITS.

Protective Gloves:WELDERS WORK GLOVES

Eye Protection:WELDERS HELMET WITH CORRECT LENSES

Other Protective Equipment:CLOTHING TO PROTECT ENTIRE BODY FROM SPARKS.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:N1

Solubility in Water:INSOLUBLE

Appearance and Odor:WELDING ELECTRODES ARE METALLIC SILVER COLORED WIRE WITH A FLUX COATING OR CORE

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decompos

ition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaim
s all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.