

METALLURGICAL TECHNOLOGIES,INC -- METEC 4160C COMP. 1 -- 3439-01-388-5661

=====
Product Identification
=====

Product ID:METEC 4160C COMP. 1
MSDS Date:08/01/1991
FSC:3439
NIIN:01-388-5661
MSDS Number: BYHMH
=== Responsible Party ===
Company Name:METALLURGICAL TECHNOLOGIES,INC
Address:14435 MAX ROAD
City:PEARLAND
State:TX
ZIP:77581
Country:US
Info Phone Num:713-485-7765
Emergency Phone Num:713-485-7
765
CAGE:63726
=== Contractor Identification ===
Company Name:METALLURGICAL TECHNOLOGIES,INC
Address:14435 MAX ROAD
Box:City:PEARLAND
State:TX
ZIP:77581
Country:US
Phone:713-485-7765
CAGE:63726

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM
CAS:7429-90-5
RTECS #:BD0330000
Fraction by Wt: 87%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:10 MG/M3

Ingred Name:SILICON
CAS:7440-21-3
RTECS #:VW0400000
Fraction by Wt: 13%
Other REC Limits:NONE RECOMMENDED

=

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

==== First Aid Measures =====

====

First Aid:INHALATION-REMOVE PERSON FROM SOURCE, IF NOT BREATHING,
PERFORM CPR, IF BREATHING ADMINISTER OXYGEN. INGESTION-HAVE PERSON
DRINK WATER OR MILK AND INDUCE VOMITING. GET MEDICAL ATTENTION.

==== Fire Fighting Measures =====

Flash Point:NONE
Autoignition Temp:Autoignition Temp Text:650C
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:CLASS D EXTINGUISHINH AGENT OR DRY INERT GRANULAR
MATERIAL (EG. SAND).
Fire Fighting Procedures:USE
EXTREME CARE TO PREVENT DUST CLOUD
FORMATION. SMOTHER FIRE WITH CLASS D EXTINGUISHER. DO NOT USE CLASS
A,B OR C RATED EXTINGUISHERS.
Unusual Fire/Explosion Hazard:ALUMINUM POWDER MAY BE EXPLOSIVE WHEN
DEPERSED IN AIR.

==== Accidental Release Measures =====

Spill Release Procedures:THIS MATERIAL IS NON TOXIC AND CAN BE DISPOSED
OF AS IF IT WERE COMMON PLASTIC WASTE.
Neutralizing Agent:NA

==== Handling and Storage =====

====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.
Other Precautions:NONE.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED DUST RESPIRATORS.
Ventilation:LOCAL EXHAUST-YES.
Protective Gloves:YES.
Eye Protection:SAFETY GLASSES OR GOGGLES.
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE

==== Physical/C

hemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:1076F,580C

Decomp Temp:Decomp Text:NA

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:1.4 G/CM3

pH:NA

Viscosity:NA

Evaporation Rate & Reference:NA

Appearance and Odor:METALLIC GREY - SILVER POWDER. NO ODOR.

Percent Volatiles by Volume:NA

Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OPEN FLAME/FIRE.

Stability Condi

tion to Avoid:OPEN FLAME/FIRE.

Hazardous Decomposition Products:POISONOUS GAS OR FUMES ON
DECOMPOSITION.

Conditions to Avoid Polymerization:FIRE MAY PRODUCE POISONOUS OR
IRRITATING FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:SWEEP UP AND TREAT AS COMMON PLASTIC WASTE.LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.