

FERNDALE LABORATORIES INC -- MASTISOL -- 6510-01-321-5603

===== Product Identification =====

Product ID:MASTISOL

MSDS Date:05/03/1994

FSC:6510

NIIN:01-321-5603

MSDS Number: BYPFC

=== Responsible Party ===

Company Name:FERNDALE LABORATORIES INC

Address:708 W EIGHT MILE RD

City:FERNDALE

State:MI

ZIP:48220-2422

Country:US

Info Phone Num:313-548-0900/800-621-6003

Emergency Phone Num:313-548-0900/800-6

21-6003

CAGE:28867

=== Contractor Identification ===

Company Name:FERNDALE LABORATORIES INC

Address:708 W EIGHT MILE RD

Box:City:FERNDALE

State:MI

ZIP:48220-2422

Country:US

Phone:313-548-0900/800-621-6003

CAGE:28867

===== Composition/Information on Ingredients =====

Ingred Name:ETHANOL (ETHYL ALCOHOL), TECSOL, ALCOHOL, SYNASOL

CAS:64-17-5

RTECS #:KQ6300000

Other REC Limits:1900 MG/CUM

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM

Ingred Name:MASTIC (RESIN), GUM MASTIC

CAS:61789-92-2

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGESTION OF LARGE QUANTITIES MAY
CAUSE CNS DEPRESSION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:HEADACHE, DROWSINESS, INABILITY TO CONCENTRATE,
NAUSEA, VOMITING.

=====
===== First Aid Measures =====

First Aid:
INHALATION: REMOVE TO FRESH AIR/WELL VENTILATED AREA. EYES:
FLUSH W/WATER. SKIN: FLUSH W/WATER & WASH W/SOAP & WATER. OBTAIN
MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Extinguishing Media:DRY CHEMICAL, FOAM, CO2.
Fire Fighting Procedures:WEAR A SELF-CONTAINED BREATHING APPARATUS IN
POSITIVE PRESSURE MODE W/FULL FACEPIECE .

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE AN A
BSORBENT MATERIAL TO CONTROL & CLEAN
UP.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A TIGHT CONTAINER IN A COOL
DRY PLACE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR AN ORGANIC CANISTER MASK FOR LARGE AMOUNTS.
Ventilation:LOCAL EXHAUST.
Work Hygienic Practices:USE GOOD HYGIENIC PRECAUTIONS.
Supplemental Safety and Health
BOILING POINT INFORMATION IS FOR PURE ETHYL A

LCOHOL.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:173F (SUPP)

Spec Gravity:0.85-0.9

Solubility in Water:PARTIAL

Appearance and Odor:AMBER COLOR LIQUID W/AROMATIC ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS.

Stability Condition to Avoid:OPEN FLAMES.

Hazardous Decomposition Products:CO2 CAN FORM ON INCOMPLETE COMBUSTION.

===== Disposal Consi

derations =====

Waste Disposal Methods:DISPOSE OF ABSORBED MATERIAL IN A LAND-FILL
IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document sh

ould seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.