

MILITEC INCORPORATED -- MILITEC-1 -- 9150-01-415-9112

=====
Product Identification
=====

Product ID:MILITEC-1
MSDS Date:11/06/1996
FSC:9150
NIIN:01-415-9112
MSDS Number: BYVYW
=== Responsible Party ===
Company Name:MILITEC INCORPORATED
Address:2111 WILSON BLVD #400
City:ARLINGTON
State:VA
ZIP:22201
Country:US
Info Phone Num:703-528-8371
Emergency Phone Num:703-528-8371
CAGE:NO555
=== Contractor I
dentification ===
Company Name:MILITEC INC
Address:11828 PIKA DR
Box:City:WALDORF
State:MD
ZIP:20602
Country:US
Phone:301-893-3910
CAGE:0KXE0
Company Name:MILITEC INCORPORATED
Address:2111 WILSON BLVD; #400
Box:City:ARLINGTON
State:VA
ZIP:22201
Country:US
Phone:703-528-8371/703-528-2614
CAGE:NO555

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED

=====
Hazards Ident
=====

ification =====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY TRACT. ACUTE- MAY CAUSE EYES & SKIN IRRITATION. PROLONGED/REPEATED SKIN CONTACT CAUSES DEFATTING. INHALATION OF VAPORS/OIL MIST MAY CAUSE IRRITATION. INGESTION MAY CAUSE NAUSEA. ASPIRATION HAZARD. CHRONIC- MAY CAUSE DERMATITIS.

IS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, NAUSEA

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. EYES:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WIPE OFF EXCESS. WASH SKIN WITH SOAP & WATER. ORAL:DO NOT

INDUCE VOMITING. IF CONSCIOUS, RINSE MOUTH. SEEK MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:410F,210C

Autoignition Temp:Autoignition Temp Text:715F

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:USE STANDARD PRECAUTIONS FOR OIL FIRE.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. RECOVER FREE OIL IF POSSIBLE. ABSORB SPILL WITH INERT MATERIAL SUCH AS SAND, CLAY, EARTH & SHOVELD INTO CONTAINERS FOR LATER DISPOSAL. PREVENT RUN-OFF TO ENTER WATERWAYS, SEWERS. ALL RESPONSE ACTIVITIES MUST COMPLY WITH HAZWOPER.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT & INCOMPATIBLE

ES.

KEEP OUT OF REACH OF CHILDREN.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. DISCARD LUBRICANT-SOAKED SHOES. REMOVE LUBRICANT-SOAKED CLOTHING AND LAUNDRER BEFORE RE-USE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS, WEAR A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR.

Ven

tilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).

Protective Gloves:NITRILE OR NEOPRENE RECOMMENDED

Eye Protection:SAFETY GLASSES, FACE SHIELD RECOMMENDED

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

=====

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:527F,275C

Melt/Freeze Pt:M.P/F.P Text:-45F,-43C

Vapor Pres:NOT GIVEN

Vapor Density:NOT GIVEN

Spec Gravity:1.142

Viscosity:43.4CST @100F

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:SLIGHT

Appearance and Odor:CLEAR AMBER COLOR LIQUID, MILD ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG

REDUCING AGENTS

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:MAY PRODUCE FUMES, SMOKE, CARBON MONOXIDE, CARBON DIOXIDE AND HYDROGEN CHLORIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE IN COMPLIANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS. RCRA EMERGENCY NUMBER: 800-424-9346. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS OR UNDERGROUND WATER SUPPLY. INCINERATION IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.