

TECHNOLUBE PRODUCTS DIV (LUBRICATING SPECIALTY CO) -- A0900 MIL-F-17111B POWER TRANSMISSION FLUID -- 9150-01-263-7243

=====
Product Identification
=====

Product ID:A0900 MIL-F-17111B POWER TRANSMISSION FLUID

MSDS Date:06/04/1993

FSC:9150

NIIN:01-263-7243

MSDS Number: BYXKV

==== Responsible Party ===

Company Name:TECHNOLUBE PRODUCTS DIV (LUBRICATING SPECIALTY CO)

Address:3365 E SLAUSON AVE

City:VERN

ON (FORMALLY IN LOS ANGELES)

State:CA

ZIP:90058

Country:US

Info Phone Num:213-581-2036

Emergency Phone Num:213-581-2036, CHEMTREC 800-424-9300

Preparer's Name:RICHARD J. EBERHARDT

CAGE:8Y842

==== Contractor Identification ===

Company Name:LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address:3365 E. SLAUSON AVE

Box:City:LOS ANGELES

State:CA

ZIP:90058

Country:US

Phone:562-776-4033; FAX:562-776-4003

CAGE:8Y842

Company Name:NAUGHTON ENERGY CORP

Address:RT 940

Box:709

City:POCONO PINES

State:PA

ZIP:18350-0709

Country:US

Phone:570-646-0422

CAGE:1DL10

Company Name:TECHNOLUBE PRODUCT COMPANY

Address:8015 PARAMOUNT BLVD.

Box:City:PICO RIVERA

State:CA

ZIP:90660-4811

Country:US

Phone:562 776-4000 GEN: 562-776-4000

CAGE:2X769

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROTREATED MIDDLE PETROLEUM DISTILLATE

CAS:64742-46-7

RTECS #:JN9379645

Fraction by Wt: 85%

Other REC Limits:NONE RECOMMENDED

=====

LD50 LC50 Mixture:TLV- 5 MG/M3 AS OIL MIST

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: NORMALLY DOES NOT CAUSE ILL EFFECTS EXCEPT IN VERY SENSITIVE PERSONS. CHRONIC: PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN IRRITATION AND INFLAMMATION.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:SKIN-IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH PREEXISTING SKIN DISORDERS SHOULD AVOID CONTACT WITH PRODUCT.

===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES. SEE DOCTOR IF IRRITATION DEVELOPS. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH MILD SOAP & WATER. SEE DOCTOR IF IRRITATION DEVELOPS. INHALED-REMOVE TO FRESH AIR. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION A

S NEEDED. INGESTED-DO NOT INDUCE VOMITING! CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:>212F,>100C

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:DO NOT ENTER ANY CONFINED AREA WITHOUT SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:SLIGHTLY COMBUSTIBLE; WHEN HEATED ABOVE FLASH POINT WILL RELEA

SE FLAMMABLE VAPORS WHICH CAN BURN IN OPEN OR BE EXPLOSIVE IN CONFINED SPACES.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. WIPE OR MOP UP OR ABSORB WITH DIATOMACEOUS EARTH OR OTHER INERT MATERIAL AND PLACE IN A CONTAINER FOR LATER DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE AWAY

FROM

SOURCES OF IGNITION AND STRONG OXIDIZING AGENTS. PROPER FOOTWEAR REQUIRED. AVOID EXCESSIVE MISTING-SLIPPERY.

Other Precautions:DISCARD CONTAMINATED LEATHER GLOVES AND SHOES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCB A, AS

REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NITRILE RECOMMENDED.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:CHEMICAL RESISTANT APRON AND BOOTS.

DLA-HMIS: EYE WASH.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:392F,200C

Vapor Pres:1

Spec Gravity:0.860

Evaporation Rate & Reference: