

MAINTEX INC -- SHOWER, TUB & TILE (HARD WATER/SCUM REMOVER) -- 7930-01-398-0855

===== Product Identification =====

Product ID:SHOWER, TUB & TILE (HARD WATER/SCUM REMOVER)

MSDS Date:06/11/1994

FSC:7930

NIIN:01-398-0855

MSDS Number: BYZBQ

=== Responsible Party ===

Company Name:MAINTEX INC

Address:13300 E NELSON AVE

City:LA PUENTE

State:CA

ZIP:91746-1516

Country:US

Info Phone Num:818-961-1988

Emergen

cy Phone Num:800-255-3924 (CHEMTEL)

Preparer's Name:ALI ABYANE

CAGE:0PWJ2

=== Contractor Identification ===

Company Name:MAINTEX INC

Address:13300 NELSON AVE

Box:City:CITY OF INDUSTRY

State:CA

ZIP:91746

Country:US

Phone:818-961-1988

CAGE:0PWJ2

===== Composition/Information on Ingredients =====

Ingred Name:GLYCOLIC ACID

CAS:79-14-1

Fraction by Wt: 15-20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

Ingred Name:VOC = 4%

RTECS #:9999999VO

Other REC Lim

its:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRIT. DAMAGE W/BRIEF CONTACT LIQUIDS/MISTS. POS PERM INJURY W/EXTENDED CONTACT. SKIN: IRRIT BY VAPORS. VAPOR/LIQ/MISTS CORROSIVE. INHAL: IRRIT/BURNS W/EXTENDED CONTACT. INGEST: BURNS TISSUES. C HRONIC-SKIN: ALL

ERGIC REACTIONS  
W/OVEREXPOSURE.

Effects of Overexposure:INGEST: ABDOMINAL PAIN, NAUSEA, VOMITING. EYES: STINGING, WATERING.

Medical Cond Aggravated by Exposure:INHALATION/INGESTION: POSSIBLE AGGRAVATION OF PREEXISTING LUNG DISEASE.

===== First Aid Measures =====

First Aid:EYES: REMOVE CONTACTS. IMMEDIATELY FLUSH W/LOTS WATER >15 MINUTES. CALL DR. SKIN: WASH W/SOAP & WATER. INHALATION: IF DISCOMFORT, GET FRESH AIR. IF BREATHING DIFFICULT , IMMEDIATELY GET MEDICAL AID. IN GESTION: GET PLENTY WATER. DO NOT INDUCE VOMITING. WASH OUT MOUTH AREA. CALL DR.

===== Fire Fighting Measures =====

Flash Point:>250F,>121C

Extinguishing Media:WATER SPRAY, FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures:POSITIVE PRESSURE SCBA W/FULL FACEPIECE FOR FIREFIGHTERS.

Unusual Fire/Explosion Hazard:USE WATER FOG/SPRAY TO COOL/LOWER PRESSURE OF FIRE-EXPOSED CONTAINERS, TO FLUSH VAPORS AWAY.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL: MOP/RINSE AREA. LG, >55 GL: WEAR RUBBER BOOTS, GLOVES, APPROPRIATE PROTECTIVE CLOTHES. SHUT OFF LEAK IF SAFE. DIKE/CONTAIN. TRANSFER LIQ TO PLASTIC DRUMS/CONTAINERS FOR RECOVERY/DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM CHILDREN. DO NOT GET IN/ON EYES, SKIN, CLOTHES. DO NOT TAKE INTERNALLY.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED IF PROPERLY DILUTED.  
Protective Gloves:RUBBER - DECREASES DRYNESS OF SKIN.  
Eye Protection:CHEM SPLASH GLASSES/FACE SHIELD ADVISED\*  
Other Protective Equipment:\*ESPECIALLY W/CONCENTRATE.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

HCC:C2  
Boiling Pt:B.P. Text:212F,100C  
Melt/Freeze Pt:M.P/F.P Text:>32F,>0C  
Vapor Pres:1  
Spec Gravity:1.08  
pH:1-2  
Evapo  
ration Rate & Reference: