

MARATHON POWER TECHNOLOGIES -- 6140 NICKEL CADMIUM BATTERY -- 6140-00-959-4180

===== Product Identification =====

Product ID:6140 NICKEL CADMIUM BATTERY

MSDS Date:11/01/1995

FSC:6140

NIIN:00-959-4180

MSDS Number: BZFYC

=== Responsible Party ===

Company Name:MARATHON POWER TECHNOLOGIES

Address:8301 IMPERIAL DR

Box:8233

City:WACO

State:TX

ZIP:76714-8233

Country:US

Info Phone Num:817-776-0650

Emergen

cy Phone Num:817-776-0650

CAGE:74025

=== Contractor Identification ===

Company Name:MARATHON POWER TECHNOLOGIES CO

Address:8301 IMPERIAL DR

Box:City:WACO

State:TX

ZIP:76712-6588

Country:US

Phone:254-741-5405

CAGE:74025

===== Composition/Information on Ingredients =====

Ingred Name:CADMIUM (SUSPECTED HUMAN CARCINOGEN BY IARC, SUPSECTED  
CARCINOGEN BY NTP, IARC - GROUP 1) \*96-2\*

CAS:7440-43-9

RTECS #:EU9800000

Other REC Limits:A2 CARCINOGEN

OSHA PEL:0.05 MG/CUM (CD)

ACGIH TL

V:2 MG/CUM  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:CADMIUM HYDROXIDE (SUSPECTED HUMAN CARCINOGEN BY IARC,  
SUSPECTED ANIMAL CARCINOGEN BY IARC - GROUP 1) \*96-2\*  
CAS:21041-95-2  
OSHA PEL:0.05 MG/CUM (CD)  
ACGIH TLV:0.06 MG/CUM

Ingred Name:NICKEL (SUSPECTED ANIMAL/HUMAN CARCINOGEN BY IARC GROUP 2B,  
SUSPECTED CARCINOGEN BY NTP) \*96-2\*  
CAS:7440-02-0  
RTECS #:QR5950000  
Other REC Limits:1 MG/CUM  
OSHA PEL:1 MG/CUM  
ACGIH TLV:1 MG/CUM IC

Ingred Name:NICKEL HYDROXIDE (SUSPECTED CARCIN  
OGEN BY NTP, IARC GROUP  
2B) \*96-2\*  
CAS:12054-48-7  
RTECS #:OR7040000  
OSHA PEL:1 PPM  
ACGIH TLV:1 PPM  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:POTASSIUM HYDROXIDE  
CAS:1310-58-3  
RTECS #:TT2100000  
Other REC Limits:2 MG/CUM (CEILING)  
OSHA PEL:2 MG/CUM  
ACGIH TLV:2 MG/CUM (CEILING)  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:LITHIUM HYDROXIDE  
CAS:1310-65-2  
RTECS #:OJ6307070  
OSHA PEL:0.025 MG/CUM  
ACGIH TLV:0.025 MG/CUM

===== Hazards Identification =====

=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: FUMES MAY CAUSE  
RESPIRATORY SYSTEM IRRITATION. EYES: IRRITATE TISSUES. EXPOSURE MAY  
CAUSE KIDNEY DYSFUNCTION & LUNG INJURY. CADMIUM & NICKEL FUMES ARE  
TOXIC & CAN CAUSE DEATH.  
Explanation of Carcinogenicity:SEE INGREDIENTS.  
Effects of Overexposure:IRRITATION, CHEST PAIN, COUGHING, SWEATING,  
CHILLS, SHORTNESS OF BR  
EATH, WEAKNESS.  
Medical Cond Aggravated by Exposure:RESPIRATORY SYSTEM DISORDERS,  
PROSTATE DISORDERS, LIVER & KIDNEY DISORDERS, VISION PROBLEMS.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. INHALATION: REMOVE TO FRESH  
AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING  
FIRE.  
Fire Fighting Procedures:WEAR PROPER PROTECTIVE EQUIPMENT & SCBA W/FULL  
FACE PIECE OPERATED IN POSITIVE PRESSURE MODE.  
Unusual Fire/Explosion Hazard:CONTACT W/STRONG OXIDIZERS MAY CAUSE  
FIRE/EXPLOSION.

===== Accidental Release Measures =====

Spill Release Procedures:BATTERY & CELL CASES WILL NORMALLY CONTAIN  
MATERIALS OF CONCERN. USE INDUSTRIAL ABSORBENT TO COLLECT LIQUID  
POSTASSIUM HYDROXIDE.

===== Handling and Storage ==  
=====

Handling and Storage Precautions:FOR TRANSPORTATION PURPOSES THESE  
SEALED NICKEL CADMIUM BATTERIES ARE NON-HAZARDOUS & NOT SUBJECT TO  
ANY OF THE PROVISIONS REGULATED.  
Other Precautions:DON'T INVERT. AVOID BREATHING CRUSHING/OTHERWISE  
DESTROYING THE PHYSICAL INTERGRITY OF THE CELL/BATTERY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A DUST/MIST MASK WHEN HANDLING THE LIQUID  
IN THE BATTERY, POSTASSIUM HYDRO

XIDE SOLUTION.  
Ventilation:LOCAL EXHAUST  
Protective Gloves:RUBBER  
Eye Protection:GOGGLES/FACE SHIELD  
Other Protective Equipment:PROTECTIVE CLOTHING TO MINIMIZE SKIN CONTACT.  
Supplemental Safety and Health  
BOILING POINT: 765F CADMIUM. MELTING POINT: 320.9F CADMIUM. SPECIFIC GRAVITY IS FOR POTASSIUM HYDROXIDE.

===== Physical/Chemical Properties =====

HCC:N1  
Boiling Pt:B.P. Text:(SEE SUPP)  
Melt/Freeze Pt:M.P/F.P Text:(SEE SUPP)  
Spec Gravity:2.044  
Solubility in  
Water:INSOLUBLE (CADMIUM)

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS, NITRITE, NITRIC ACID.  
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:CELLS & BATTERIES MAY BE RETURNED AT SENDERS EXPENSE TO A PERMITTED TREATMENT, STORAGE, DISPOSAL FACILITY IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.