View NSN Online: https://aerobasegroup.ae/nsn/6530-01-339-6927

AMSCO INTERNATIONAL -- 400009-319 SONIC DETERGENT -- 6530-01-339-6927

Product ID:400009-319 SONIC DETERGENT MSDS Date:09/01/1993 FSC:6530 NIIN:01-339-6927 **MSDS Number: BZGBX** === Responsible Party === Company Name: AMSCO INTERNATIONAL Address:1002 LUFKIN RD City:APEX State:NC ZIP:24502-5000 Country:US Info Phone Num:919-362-0842/814-870-8276 **Emergency Phone Num:919** -362-0842/814-870-8276 Preparer's Name:LORI HALLER CAGE:GO471 === Contractor Identification === **Company Name: AMSCO INTERNATIONAL** Address:1002 LUFKIN RD City:APEX State:NC ZIP:24502-5000 Country:US Phone:919-362-0842 CAGE:GO471 Company Name: AMSCO SCIENTIFIC Address:1002 LUFKIN RD Box:City:APEX State:NC ZIP:27902 Country:US Phone:919-362-0842 CAGE:0T1E8

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000

Ingred Name:TETRASODIUM

SALT OF ETHYLENEDIAMINETETRAACETIC ACID, SODIUM EDTA, SODIUM (DI) ETHYLENEDIAMINE TETRAACETATE \*95-4\* CAS:64-02-8 RTECS #:AH5075000

Ingred Name:SODIUM POLYACRYLATE CAS:68479-09-4

Ingred Name: PROPRIETARY BLEND TSRN 08613600-5035P

Ingred Name: PROPRIETARY BLEND TSRN 08613600-5037P

Ingred Name:SILICATE BINDERS (SODIUM SILICATE) \*95-4\* CAS:1344-09-8 ACGIH TLV:10 MG/CUM

Ingred Name: POTASSIUM SILICATE, POTASSIUM METASILICATE \*96-1\* CAS:1312-76-1

======================== Hazards Identific

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: SEVERE IRRITATION. SKIN: IRRITATION UPON REPEATED CONTACT. INHALATION: IRRITATION. INGESTION: HARMFUL. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION.

First Aid:EYES/SKIN: FLUSH W/PLENTY OF WATER FOR 15 MINS. INHALATION: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEEDED. INGESTION: DON'T INDUCE VOMITING. GIVE MILK/WATER TO DILUTE MATERIAL. OBTAIN MEDICAL ATTENTI ON IN ALL CASES.

Flash Point:NONE Extinguishing Media:WATER, CO2/FOAM Fire Fighting Procedures:WEAR POSITIVE-PRESSURE SCBA. Unusual Fire/Explosion Hazard:WILL NOT BURN BUT MAY SPLATTER IF TEMP EXCEEDS 2 12F.

Spill Release Procedures: CONTAIN & SOAK UP W/INERT ABSORBENT & SCOOP INTO A COVERED CONTAINER FOR DISPOSAL.

Ventilation:GENERAL LOCAL EXHAUST VENTILATION Protective Gloves:RUBBER/NEOPRENE Eye Protection:CHEMICAL GOGGLES Supplemental Safety and Health PRODUCT IS USED W/SONIC ENERGY SYSTEM.

Boiling Pt:B.P. Text:212F Vapor Pres:17 Vapor Density:0.62

Spec Gravity:1.14 pH:12 Solubility in Water:COMPLETE Appearance and Odor:CLEAR LIGHT YELLOW LIQUID W/BLAND ODOR

Stability Indicator/Materials to Avoid:YES ACIDS, STRONG OXIDIZING AGENTS, REDUCING AGENTS & CHLORINE. Hazardous Decomposition Products:FIRE: CO, CO2 & NITROUS OXIDES. CONTACT W/METALS: HYDROGEN GAS

Waste Disposal Methods:DISPOSE OF IAW/FEDERA L, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this infor mation to their particular situation.