

DEVOE COATINGS CO DIV OF GROW GROUP INC -- #137C0910 DEVGRIP 137 EPOXY PRIMER,
NON-SKID CLEAR CONVERTER -- 8010-01-397-3987

===== Product Identification =====

Product ID:#137C0910 DEVGRIP 137 EPOXY PRIMER, NON-SKID CLEAR CONVERTER

MSDS Date:05/17/1994

FSC:8010

NIIN:01-397-3987

Kit Part:Y

MSDS Number: BZLSF

=== Responsible Party ===

Company Name:DEVOE COATINGS CO DIV OF GROW GROUP INC

Address:4000

DUPONT CIR

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Info Phone Num:502-897-9861

Emergency Phone Num:800-424-9300

Preparer's Name:LOUIS F. HOLZKNECHT

CAGE:1HK86

=== Contractor Identification ===

Company Name:DEVOE COATINGS CO

Address:4000 DUPONT CIRCLE

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-897-9861

CAGE:1HK86

===== Composition/Information on Ingredients =====

Ingred Name:AMINE COMPOUND (LD50 ORAL RAT 5 GM/KG)

Fraction by Wt:

70.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:N-BUTYL ALCOHOL (SARA 313)(CERCLA)(VP = 4.2 MMHG)(LD50 ORAL
RAT 2.5 GM/KG, LC50 4HR RAT 8000 PPM)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 30.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPMC

ACGIH TLV:50 PPMC

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:VOC = 265.5 GM/L

RTECS #:9999999VO

Fraction by Wt: NA

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: SKIN/EYES: IRRITATION. MAY BE
HARMFUL IF ABSORBED THROUGH SKIN. INHAL: RESP TRACT IRRIT,
HEADACHE, NAUSEA, DIZZINESS, WEAKNESS, FATIGUE.

UNCONSCIOUSNESS/EVEN RESP ARREST W/EXTREME EXPOSURE. ING EST:
STOMACH/INTESTINAL IRRIT/NAUSEA/VOMITING/DIARRHEA.

Effects of Overexposure:POSSIBLE PERMANENT BRAIN, NS DAMA
GE W/CHRONIC

EXPOSURE. POSSIBLE LUNG DISEASE W/CHRONIC EXPOSURE SPRAY MIST &/OR
SANDING DUST. NOTE: INTENTIONAL MISUSE BY DELIBERATELY
CONCENTRATING/INHALING CONTENTS MAY BE HARMFUL/FATAL.

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE W/SAFE
HANDLING & USE OF INFORMATION.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH IMMED W/LOTS WATER >15 MIN. GET MED AID. SKIN:
WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES. GET

MED AID IF IRRIT

PERSISTS. INGESTION: CALL DR. IMMED. INHAL: GET FRESH AIR IF TROUBLE BREATHING. IF CONTINUED TROUBLE BREATHING GET IMMED MED AID. BREATHING STOPPED, RESTORE BREATHING W/CPR. GET IMMED MED AID.

===== Fire Fighting Measures =====

Flash Point:100F,38C

Lower Limits:1.4

Extinguishing Media:CO2, DRY CHEMICAL, FOAM (CLASS B FIRE).

Fire Fighting Procedures:FULL PROTECT EQUIP W/SCBA. WATER SPRAY MAY BE INEFFECTIVE, FOG NOZZLES PREFERRED

D. COOL FIRE-HEAT EXPOSED CLSD

CNTNRS. PREVENT PRESSURE BUILD-UP/AUTOIGNITION.

Unusual Fire/Explosion Hazard:KEEP CNTNRS TIGHTLY CLSD. KEEP FROM HEAT/ELECTRICAL EQUIP/SPARKS/FLAME. CLSD CNTNRS MAY EXPLODE IN EXTREME HEAT. DON'T CUT/WELD ON/NEAR CNTNR AS MAY IGNITE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNIT SOURCES. AVOID BREATHING VAPORS. VENTILATE AREA. BEFORE CLEAN-UP REFER TO HAZ CAUTION INFO. CONTAIN SPILL/

REMOVE W/INERT ABSORBENT/NONSPARKING TOOLS. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

===== Handling and Storage =====

Handling and Storage Precautions:ISOLATE FROM HEAT/SPARKS/FLAMES. DON'T SMOKE. PREVENT VAPOR BUILD-UP W/CONTINUOUS FLOW FRESH AIR. DON'T STORE >120F, NEAR FIRE/OPEN FLAME. STORE LG*

Other Precautions:AMTS IN BUILDINGS TO COMPLY W/OSHA 1910.106. KEEP CNTNR CLSD WHEN NOT USING. DON'T TRANSFER TO BOTTLES/UNLABELED

CNTNRS. DON'T REUSE EMPTY CNTNRS. IF MAT'L PART OF 2 COMPONENT PROD, MIXTURE WILL HAVE HAZARDS OF BOTH COMPONENTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DON'T BREATHE VAPORS/SPRAY MIST/SANDING DUST.NIOSH/MSHA APPROVED MECHANICAL FILTER RESPRTR.IN RESTRICTED VENTILATION, NIOSH/MSHA APPROVED CHEM/MECHANICAL FILTER FOR PARTICULATES/VAPOR.CONFINED AREAS, NIOSH/MSHA APPROVED AIR-SUPPLY RESPRTR/HOODS

Ventilation:GEN DILUTION/LO

CAL EXHAUST VENT. TO KEEP AIR CONTAM CONC