

SIKKENS AEROSPACE -- EPOXY COATINGS, 443-3 -- 8010-00-009-1962

===== Product Identification =====

Product ID:EPOXY COATINGS, 443-3

MSDS Date:02/01/1986

FSC:8010

NIIN:00-009-1962

MSDS Number: CBQCG

=== Responsible Party ===

Company Name:SIKKENS AEROSPACE

Address:20846 S. NORMANDIE AVE

City:TORRANCE

State:CA

ZIP:90502

Country:US

Info Phone Num:213-320-6800

Emergency Phone Num:213-320-6800

CAGE:OO27

4

=== Contractor Identification ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

Company Name:SIKKENS AEROSPACE FINISHES DIVISION

Address:20846 S NORMANDIE

City:TORRANCE

ZIP:90502

Phone:(213) 320-6800

CAGE:OO274

===== Composition/Information on Ingredients =====

Ingred Name:2-BUTANONE; (METHYL ETHYL KETONE) (MEK) (SARA 313) (CERCLA)

VP:70, LEL:1.8%

CAS:78-93-3

RTECS #:EL6475000
Fraction by Wt: 20-25%
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA 313) (CERCLA) VP:22, LEL:1.2%

CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 5-10%
OSHA PEL:200 PPM
ACGIH TLV:S, 50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE VP:7, LEL:1.0%

CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5-10%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Nam

e:ACETIC ACID, BUTYL ESTER; (N-BUTYL ACETATE) (CERCLA) VP:8,

LEL:1.7%

CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 5-10%
OSHA PEL:150 PPM
ACGIH TLV:150 PPM/200STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHANOL, 2-BUTOXY-; (2-BUTOXYETHANOL) VP:1, LEL:1.1%

CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 80C
Vapor Pres:1 TO 70
Vapor Density:>1
Spec Gravity:1.2 (H*2O=1)
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WHITE L

IQUID WITH A KETONE/FRUITY ODOR.

Percent Volatiles by Volume:60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, INORGANIC ACIDS, SPARKS AND OPEN FLAMES.

CONTACT WITH MOISTURE.

Stability Condition to Avoid:STORAGE AT HIGH TEMPERATURE.

Hazardous Decomposition Products:ON COMBUSTION, CO, CO*2.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE I/A/

W FEDERAL, STATE & LOCAL

REGULATIONS . TREAT AS HAZARDOUS WASTE. CONSULT CHEMICAL WASTE
DISPOSAL AND/OR TREATMENT ENTITY. REFER TO CONTROL MEASURES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.