

COLUMBUS CHEMICAL INDUSTRIES INC -- MERCURY -- 6810-00-281-7452

===== Product Identification =====

Product ID:MERCURY
MSDS Date:05/01/1994
FSC:6810
NIIN:00-281-7452
MSDS Number: CBQHT
=== Responsible Party ===
Company Name:COLUMBUS CHEMICAL INDUSTRIES INC
Address:N 4335 TEMKIN RD
City:COLUMBUS
State:WI
ZIP:53925
Country:US
Info Phone Num:414-623-2140 / FAX 414-623-2577
Emergency Phone Num:414-623-2140
CAGE:5Y144
=== Contractor Identification ===
Company Name:COLUMBUS CHEMICAL INDUSTRIES INC
Address:N 4335 TEMKIN RD
Box:8
City:COLUMBUS
State:WI
ZIP:53925-0008
Country:US
Phone:920-623-2140
CAGE:5Y144

===== Composition/Information on Ingredients =====

Ingred Name:MERCURY (SARA 313) (CERCLA)
CAS:7439-97-6
RTECS #:OV4550000
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C, 0.1 MG/M3; Z-2
ACGIH TLV:S,0.025 MG/M3; A4;96
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

==

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION OF VAPORS/MISTS MAY CAUSE IRRITATION, SENSITIZATION AND NEUROTOXICITY. SKIN CONTACT MAY CAUSE IRRITATION, SENSITIZATION, NEUROTOXICITY AND NEPHROTOXICITY. EYE CONTACT MAY CAUSE IRRITATION, CORNEAL INJURY OR BURNS.

INGESTION MAY CAUSE NEUROTOXICITY AND NEPHROTOXICITY. CHRONIC: SEE SUPPLEMENTAL.....

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of

Overexposure:INHALED-DYSPNEA,COUGH,FEVER,NAUSEA,VOMITING,DIARRHEA,S TOMATITIS,SALIVATION,METALLIC TASTE,BRONCHITIS,PNEUMONIA,PULMONARY EDEMA,ACIDOSIS,RENAL DAMAGE.SKIN-REDNESS,IRRITATION;SEE INHALED(ABSORPTION).EYES-IRRITATION,BURNS.

INGESTED-NECROSIS

OFMOUTH,THROAT,ESOPHAGUS,STOMACH;VIOLENT PAIN,PROFUSE VOMITING,DEATH.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES,LIFT LIDS.SKIN-REMOVE CONTAMINATED CLOTHES.WASH WITH MILD SOAP & WATER.INHALED-REMOVE TO FRESH AIR.ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION AS NEEDED.INGESTED-SEEK MEDICAL ATTENTION.GASTRIC LAVAGE W/

5%

SOLUTION OF SODIUM FORMALDEHYDE SULFOXYLATE,FOLLOWED BY 2% SODIUM BICARBONATE & FINALLY LEAVE 230 CC OF SODIUM FORMALDEHYDE SULFOXYLATE IN STOMACH.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & FULL FIRE FIGHTER'S PROTECTIVE GEAR. USE WATER TO COOL FIRE EXPOSED CONTAINERS. MOVE CONTAINERS FROM AREA I

F POSSIBLE.

Unusual Fire/Explosion Hazard:USE WATER IN FLOODING AMOUNTS AS A FOG.

AVOID BRETAHING CORROSIVE AND POISONOUS VAPORS. KEEP UPWIND.

===== Accidental Release Measures =====

Spill Release Procedures:DO NOT TOUCH SPILLED MATERIAL. ISOLATE & DENY ENTRY. WEAR PROPER PERSONAL PROTECTIVE CLOTHING. STOP LEAK IF NO RISK. TAKE UP WITH SAND OR OTHER ABSORBENT AND PLACE IN CONTAINERS FOR LATER DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURE

R.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE IN CLOSED, UNBREAKABLE CONTAINERS AWAY FROM SOURCES OF HEAT. PROTECT FROM PHYSICAL DAMAGE.

Other Precautions:MERCURY EVAPORATES VERY SLOWLY. SPILLED MERCURY FORMS MANY TINY GLOBULES THAT WILL EVAPORATE FASTER THAN A SINGLE POOL AND CAN DEVELOP A SIGNIFIGANT CONCENTRATION OF VAPORS IN AN UNVENTILATED AREA. SU CH VAPORS ARE POISONOUS.

=====

== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:RUBBER.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:EYE WASH STATION & SAFETY SH

OWER. PROVIDE

PREPLACEMENT AND PERIODIC MEDICAL EXAMS FOR THOSE EXPOSED ON REGULAR BASIS.

Work Hygienic Practices:WASH HANDS AFTER HANDLING & BEFORE EATING, DRINKING, USING TOILET OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

CHRONIC: PROLONGED OR REPEATED EXPOSURE MAY CAUSE VISUAL DISTURBANCES, MERCURIALISM., DERMATITIS, ANURIA. NOTE: PHYSICAL EXAMS SHOULD PLACE EMPHASIS ON CNS, SKIN, LUNGS, LIVER, KIDNEYS & GI TRACT.

=====

===== Physical/Chemical Properties =====

HCC:T6

Boiling Pt:=357.2C, 675.F

Melt/Freeze Pt:=-38.9C, -38.F

Vapor Pres:0.0012

Vapor Density:7.0

Spec Gravity:13.6

Solubility in Water:INSOLUBLE

Appearance and Odor:SILVER-WHITE, HEAVY, MOBILE, LIQUID METAL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACETYLINIC CMDS, AMMONIA, BORON, DIIODOPHOSPHIDE, ETHYLENE OXIDE,
METALS, METHYL AZIDE, METHYLSILANE, OXYGEN, OXID
IZERS

Stability Condition to Avoid:DOES NOT READILY IGNITE. FLAMMABLE

POISONOUS GASES MAY ACCUMULATE IN TANKS AND HOPPER CARS. MAY IGNITE
COMBUSTIBLES.

Hazardous Decomposition Products:THERMAL DECOMPOSITION PRODUCTS INCLUDE
TOXIC MERCURY VAPORS AND OXYGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DLA-HMIS: DISPOSE OF IN ACCORDANCE WITH LOCAL,
STATE AND FEDERAL ENVIRONMENTAL REGULATIONS. EPA/RCRA HAZWASTE
NUMBER=D009.

Discl

claimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.