

NAZDAR CO -- ENAMEL PLUS GLOSS SCREEN INK, 59134 -- 8010-00-782-0443

=====
Product Identification
=====

Product ID:ENAMEL PLUS GLOSS SCREEN INK, 59134

MSDS Date:08/08/1994

FSC:8010

NIIN:00-782-0443

MSDS Number: CBQLL

=== Responsible Party ===

Company Name:NAZDAR CO

Address:1087 N NORTH BRANCH ST

City:CHICAGO

State:IL

ZIP:60622

Country:US

Info Phone Num:312-943-8338

Emergency Phone Num:800-424-930

0 (CHEMTREC)

CAGE:FO883

=== Contractor Identification ===

Company Name:NAZDAR CO

Address:1087 N NORTH BRANCH ST

City:CHICAGO

State:IL

ZIP:60622-4234

Country:US

Phone:312-943-8338

CAGE:FO883

Company Name:NAZDAR COMPANY

Address:1087 N NORTH BRANCH ST

Box:City:CHICAGO

State:IL

ZIP:60622-4292

Country:US

Phone:312-943-8338;800-736-7636

CAGE:76708

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC; (PETROLEUM
DISTILLATE;

ALIPHATIC HYDROCARBON) VP: 2.0 @ 20C

CAS:64742-88-7

Fraction by Wt: 15-25%

OSHA PEL:100 PPM (MFR)

ACGIH TLV:100 PPM (MFR)

Ingred Name:BARIUM SULFATE

CAS:7727-43-7

RTECS #:CR0600000

Fraction by Wt: 0-30%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST

Ingred Name:PIGMENTS (MIXTURE)

Fraction by Wt: 5-15%

OSHA PEL:15 MG/M3 (MFR)

ACGIH TLV:10 MG/M3 (MFR)

Ingred Name:LEAD; (COMPOUNDS) (SARA 313) (CERCLA)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 2-30%

OSHA PEL:SEE 1910.1025

ACGIH TLV:0.15 M

G/M3 DUST

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ALIPHATIC PETROLEUM DISTILLATE; (PETROLEUM DISTILLATE;

ALIPHATIC HYDROCARBON) VP: < 10 @ 25C

CAS:64742-96-7

Fraction by Wt: 0-10%

OSHA PEL:> 14 PPM (MFR)

ACGIH TLV:N/K

Ingred Name:PETROLEUM HYDROCARBON; (PETROLEUM DISTILLATE; ALIPHATIC

HYDROCARBON) VP: 0.8 @ 20C

CAS:64742-47-8

RTECS #:OA5504000

Fraction by Wt: 0-5%

OSHA PEL:100 PPM (MFR)

ACGIH TLV:100 PPM (MFR)

Ingred Name:ANTIMONY (SARA 313) (CERCLA)

CAS:7440-36-0

RTECS #:CC402

5000

Fraction by Wt: 0-2%

OSHA PEL:0.5 MG/M3

ACGIH TLV:0.5 MG (SB)/M3

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:HEAVY AROMATIC NAPHTHA (SOLVENT NAPHTHA); (PETROLEUM
DISTILLATE; AROMATIC HYDROCARBON) VP: < 3 @ 25C

CAS:64742-94-5

RTECS #:WF3100000

Fraction by Wt: 0-2%

OSHA PEL:100 PPM (MFR)

ACGIH TLV:N/K

Ingred Name:CHROMIUM (COMPOUNDS) (SARA 313) (CERCLA)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: